

Douglas County Surveyor's Record of
Government Corners Renewed

T. 30 S. T. S. R. 3 W. R. W. W. M.

KORKE-CHAPMAN CO., EUGENE, ORE. 97101

176

Cl. Corner to Secs. 3 and 2, T31-3W. (S. Bdry. T30-3)
Found - I. Pipe at Closing Corner, See Ren. #45, T31-3W.
Orig. 32", now 34" Laurel S. 36° W. 15.8 ft.
Orig. 32" Fir, N. 18° E. 28.4 ft. Had been opened for scribe "31".
Orig. 24" Laurel S. 67° E. 54.5 ft.
11", now 12" Fir S. 48° E. 24.6 ft. scribed S2 T31SR3W BT.
12", now 15" Laurel N. 84° E. 17.2 ft., bark scribed.
6", now 9" Fir S. 73° W. 13.0 ft., shows good scars.
6", now 7" W. Fir N. 4° W. 20.0 ft., shows good scars.
Set - Brass Cap At Cor. Mkd: County Surveyor's Office, 1965
T30S R3W
C.C.S 3 / S 2
T31S R3W

As noted, corner lies about 100.0 ft. from top of ridge.

177

Sec. Cor. to Secs. 1 & 2 only, T31-3W. (S. Bdry, Sec. 36, T30-3W)
Found - 1/2" I. Pipe at Corner, See Ren. #51, T31-3W.
Orig. 14", now 18" W. Fir S. 34° W. 12.8 ft., opened, showing scribe.
15" W. Fir, now down. N. 22° E. 49.0 ft.
11" W. Fir, now down. S. 35° E. 35.2 ft.
10" Chinquapin Snag S. 34° W. 34.8 ft.
15", now 17" Maple S. 87° W. 34.8 ft., scribe visible.
Set - Brass Cap At Cor. Mkd: County Surveyor's Office, 1965
T30S R3W
S 36
S 2 / S 1
T31S R3W

New BT: 12" W. Fir N. 27 1/2° E. 85.3 ft.
scribed T30S R3W S36 CS BT.

178

South 1/4 Corner to Section 36 only. (N. Bdry, T31-3W.)
Found - No trace of Corner Stone.
Orig. 6", now 9" Cedar N. 77 1/2° E. 19.1 ft. Opened for scribe.
Orig. 6", now 12" Fir S. 47 1/4° E. 12.5 ft., shows good scar.
Set - Brass Cap at 1/4 Cor. Mkd: County Surveyor's Office, 1965
T30S R3W
1/4 S 36

Both trees Original & in good condition. No need for new trees.

179

Sec. Cor. to Sections 35 and 36 only, (N. Bdry, T31-3W)
Found - No trace of I. Pipe as recorded Ren. #74.
Orig. 11", now 13" Cedar N. 56° E. 11.3 ft., scribe visible.
Orig. 13" Cedar, now down, N. 51° W. 12.0 ft.
12", now 13" Laurel N. 75° W. 44.4 ft., bark scribed.
14", now 15" Laurel S. 80° E. 23.0 ft. scribed S2 BT.
10" Cedar N. 7° E. 44.4 ft. scribe visible S36 BT.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1965
T30S R3W
S 35 / S 36
S 2
T31S R3W

New BT: 24" Doug. Fir N. 65 1/2° W. 21.0 ft.
scribed T30S R3W S35 CS BT.

180

South

1/4 Corner to Section 35 only, T30-3W.
Found - 1" I. Pipe 1.0 ft. N. of 1/4 Corner, See Ren. #60. #225
28" Cedar Stump S. 33° E. 37.2 ft., find bearing S.B. S. 30° E.
18", now 19" Hemlock N. 30° W. 40.1 ft., find bearing S.B. N. 33° W.
Shows good scar & pitched over scribe.
Corner Tree is Stump.
Set - Brass Cap 1.0 ft. N. of Corner Tree, alongside I. Pipe, Mkd: County Surveyor's Office, 1965
T30S R3W
1/4 S 35
T31S R3W
New BT: 5" Hemlock N. 57° E. 24.2 ft. scribed 1/4 S35 CS BT.

John M. Powell
Frank Jones & Joe Brady
December 1965
C. S. File No. 52/63

RE-RENEWED SEE CORNER NO. #225