

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 30 S. T. S. R. 3 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

192

$\frac{1}{4}$  Corner to Sections 9 and 16.  
Found - 40" DiFir, now Stump, N. 42° W. 9.3 ft., shows good scar.  
12" D.Fir, now Stump, S. 27 $\frac{1}{2}$ ° W. 28.4 ft., opened for scribing.  
Set - Brass Cap at Cor. Mkd: County Surveyors T30S R3W  
Office, 1966  $\frac{S}{S} \frac{9}{16}$

New BT's: 6" Laurel S. 83° E. 24.1 ft. mkd.  $\frac{1}{4}$  S 16 CS BT.  
4" D. Fir N. 60° E. 8.8 ft. mkd.  $\frac{1}{4}$  S 9 CS BT.  
ED OK 6/93 - LANG - M123 - 14

193

Sec. Cor. to Sections 8 - 9 - 16 - 17.  
Found - I. Pipe at Sec. Cor., See Ren. #43. #217  
Orig. 18" D.Fir, now 24", N. 15° E. 35.0 ft., shows good scar.  
Orig. 26" D. Fir, now 31", S. 56° W. 18.0 ft. (Dist. is 19.0 ft.)  
shows good old scar & bark scribe.  
Orig. 26" D. Fir, now Stump, N. 13° W. 33.0 ft. Stump has  
been opened.  
13" D. Fir, now Snag, S. 66° E. 53.2 ft., scribe visible.  
Set - Brass Cap at Cor. Mkd: County Surveyors T 30S R 3 W  
(alongside I.P.) Office, 1966  $\frac{S}{S} \frac{8}{17} \frac{S}{S} \frac{9}{16}$

New BT: 10" Cedar N. 32° W. 8.5 ft. mkd. T30S R3W S 8 CS BT.  
No other trees available.  
Note - Corner lies N.W. of cutting corner & in heavy reprod.

194

$\frac{1}{4}$  Corner to Sections 3 and 2.  
Found - 1960 County Surveyor's Brass Cap at  $\frac{1}{4}$  Corner, See Ren. #85.  
12" Chinquapin S. 18° W. 4.3 ft., scribe visible " $\frac{1}{4}$  S3 CSBT".  
10" Fir N. 41° E. 20.9 ft., scribe visible " $\frac{1}{4}$  S2 CS BT".  
New BT: 7" D. Fir N. 51° W. 17.4 ft. scribed  $\frac{1}{4}$  S 3 CS BT.  
Sept. 1, 1967

195

$\frac{1}{4}$  Corner to Sections 14 and 23.  
Found - Orig. 6" D.Fir, now 7" down & burnt, N. 37 $\frac{1}{2}$ ° W. 10.9 ft.,  
Tree had been opened, Faint scribe, "S" "B".  
Orig. 5" D.Fir, now stump flush with ground, S. 66 3/4° W.  
4.6 feet.  
6", now 8" Corner Tree with rotted face, tried to get  
a ring count but tree gree too slow to count.  
Calls from ravines hit pretty good on top of ridge.  
Set - Brass Cap at  $\frac{1}{4}$  Cor. Mkd: County Surveyor T 30 S R 3 W  
Office  $\frac{1}{4}$   $\frac{S}{S} \frac{14}{23}$   
1967  
New Bering Objects: RR Spike in top of 42" Stump S. 75° W. 31.5 ft.  
RR Spike in top of 28" Stump N. 4° W. 29.4 ft.  
Note - This corner lies on top of small ridge running about N.-S.

196

$\frac{1}{4}$  Corner to Sections 22 and 23.  
Found - Orig. 18" Fir, now down & rotten, S. 37° W. 5.6 ft.,  
scribe found "/" "S" "BT".  
Orig. 30" Cedar, now down, burnt & rotten, N. 42° E. 23.8 ft.,  
mark found in tree which looks like scribe.  
Set - Brass Cap at  $\frac{1}{4}$  Cor. Mkd: County Surveyors T 30 S R 3 W  
Office, 1967  $\frac{1}{4}$  S 22 | S 23  
New BT's: 7" D. Fir S. 86° W. 13.8 ft. mkd.  $\frac{1}{4}$  S 22 CS BT.  
6" D. Fir S. 41° E. 12.6 ft. mkd.  $\frac{1}{4}$  S23 CS BT.

197

$\frac{1}{4}$  Corner to Sections 23 and 24.  
Found - Orig. 10", now 13" Fir, S. 5° E. 6.6 ft. (Snag top & burnt)  
Opened for scribe "BT".  
Orig. 12" Fir, now stob, S. 77° W. 5.3 ft.  
1" I. Pipe at  $\frac{1}{4}$  Corner, See Ren. #49.  
15", now 16" Laurel, N. 41° W. 30.0 ft., bark scribed " $\frac{1}{4}$ ".  
Reblazed & Rescribed: " $\frac{1}{4}$  S23 CS BT".  
New BT: 14" D. Fir North 13.3 ft. mkd.  $\frac{1}{4}$  S24 CS BT.  
Note - This corner is 330 ft. west of the road.

John M. Powell  
Cliff Stone  
Oct. 27, 1966  
C. S. File No. 54/52

John M. Powell  
Frankline Jones & J. Brady  
September, 1967  
C. S. File No. 54/52

RE-RENEWED