Douglas County Surveyor's Record of Government Corners Renewed

T 30 T. S. R 3 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21981

210

C O N T. -

Set - A 1"x30" Iron pipe with brass cap stamped:
Douglas Co. Surveyor T 30 S
1976 R 3 W | R 2 W
S 36 | S 31
Closing Corner

New BT -A 12" Hemlock bears N.80°E., 34.3 ft. mkd. "T30S R2W S31 CS BT" in a double blaze.

A. Victor Cangie
Jim Cook
Mike Tompkins
Co. Surveyor's Office
Sept. 14, 1976
C.S. 59/24

9/14/76

211

Center West 1/16, Sec. 7.

Found - 1965 BLM Brass cap properly stamped approximately 4 inches above ground, firmly set.
A 6" now 11" Cedar, bears N.64°W., 66.1 ft. (Rec. N.66°W., 67.3 ft.) Tree has well healed blaze.
A8" now 13" Fir, bears S.78°E., 47.2 ft. (Rec. S.79°E., 47.8 ft.) Tree has a well healed blaze.

Note: Iron pipe (Rec. S.57°E., 15.2 ft.) set by Thompson in 1956 Not Found.

L.E. Monrean
P.L. Earle
Doug. Co. Surveyors Office
Nov. 2, 1976
C.S. 59/26

11/2/76

212

1/4 Corner for Secs. 14 and 15

Found - 5/8" Brass Rod 18" below ground. Ren. #92
A 16" now 22" Hemlock bears N.21°W., 34.7 ft. Tree has partially healed double blaze, some scribing visible. Ren. #200
A 21" now a 22" Hemlock stump bears N.4°E., 55.2 ft. Tree blazed and scribed "1/4 S14 CS BT".
A 72" Fir stump (orig. line tree) bears S.1 1/2°W., 113.5 ft. (Rec. 108.9 ft.)

Set - 1" x 30" I.P. with brass cap attached directly over 5/8" Brass rod, cap is stamped "Douglas County Surveyor" T30S R3W 1/4 S15 S14 1977.

New BT - A 12" yew Wood bears S.0 1/2°W., 53.7 ft. (to center of tree at BT blaze height.) Tee double blazed and scribed "1/4 S14 CS BT".

Larry E. Monrean
R. B. Kimberling
Doug. Co. Surveyors Office
4/26/77
C.S. 59/31

April 26, 1977

213

Section Corner for Secs. 15, 14 22 and 23.

Found - 1" I.P. with flagging laying downhill 20 ft. (west) of corner.
A Burned orig. 29" now 30" Fir stump at record S.10 1/2°E., 19.8 ft. No marks visible, we opened an apparent blaze and found scribe marks "BT". See Ren. #93 and 1972 Gov't Resurvey
An Orig. 28" now 32" burned Fir snag bears record N.45°W., 19.1 ft. We opened apparent blaze and found scribe marks "BT"
A Fir, orig. 14" now 15" bears S.26°W., 55.8 ft. (Rec. S.24°W. 55.6 ft. (, badly barked on east side and butned, with partial scribe marks visible on pitched over blaze.
A Fir, ~~unrecorded~~, 17" bears S.52°W., 75.7 ft. (Rec. S.50°W., 73.9 ft.)with fragmentary scribe. Marks visible on partially healed blaze. REN.# 199
A Fir 49" bears N.41 1/2°E., 189.6 ft. (Rec. 124.4 ft.) single blazed and scribed "T30S R3W S14 BT".

Set - An I.P. 30" long, 2" Diam. 20" in the ground with brass cap mkd. Douglas County Surveyor T30S S15 S14 S22 S23 R3W 1977.

Note: Corner is on a 33° Westerly slope 40 ft. north of draw in logged off unit.

G. Langlitz
R. B. Kimberling
April 27, 1977
C.S. 59/31

4/27/77

JAN 79

214

1/4 Corner for Secs. 13 and 24

Found - A Fir stump 36" now 48", bears S.55°E., (Rec. S.35°E.) 13.2 ft. I chop openhealed blaze and find scribing "BT".
A Fir stump, 24" now 35", bears N.87 1/2°E., (Rec. N.80°E.) 40.9 ft. with visible scribing "BT" in a chopped open blaze.

Set - A 1" x 36" Iron pipe with brass cap set 4" above ground and marked: "Douglas County Surveyor" T 30 S R 3 W
1978 1/4 S 13 / S 24

New BT's- A 12" D. Fir bears N.11°E., 16.0 ft. I double blaze and scribe "1/4 S13 CS BT".
A 5" White Fir bears S.22°E., 16.4 ft. I double blaze and scribe "1/4 S24 CS BT".

R. B. Kimberling
P.L. Earle
Doug. Co. Surveyors Office
June 5, 1978
C.S. 60/11

1-79

6/5/78