

Douglas County Surveyor's Record of  
Government Corners Renewed

30 T.S. 4 R.W.W.M.

Ben B. Irving  
Witnesses

L. H. Smick  
Harch Clough  
J. I. Worthington

Feb. 5 to 7, 1927.

Vol. 3 P. 273 cs 3/63

Ext. L. D. L. C. #37

N.W. EXTERIOR DONATION LAND CORNER # 37 JACOB SLIPPERY  
D.L.C.

39

I identify the location of this corner by a 14" Black Oak. The Government field notes call for a 12" White Oak S. 85° E., 70 lks. The black oak when chopped out carried the old scribe marks in excellent condition although rot was beginning to show.

I renewed this corner by driving a 36" iron bar 30" in the ground and an oak post 3" x 3" x 36" marked D.L.C. 37 C.S. from which

A Black Oak bears S. 61° E., 72.5 ft. marked D.L.C. 37 C.S. B.T.

Ben B. Irving D.C.S.  
Witnesses

Wm. Crear  
R. L. Irving

Nov. 29, 1927.

Vol. 3 P. 278 cs 53/37 on 1st page

S.E. CORNER OF CLAIM 44.

40

Replaced from original B.T. standing and in excellent condition which was chopped out. Set a stone 6" x 6" x 18" for corner stone marked with crows foot.

Original B.T. bears N. 89° W., 648 lks. 36" Black Oak  
New B.T. bears S. 80° W., 22 lks. 12" Fir

S.W. CORNER OF CLAIM 44.

41

Replaced from original B.T. standing but interior badly rotted and splintered. Original revealed growth plainly visible as is also latter scribe marks. Old B.T. bears N. 20° E. instead of N. 20° W. as recorded in original notes.

Set auto axle with gear attached for corner, from which  
Original B.T. Black Oak 36" bears N. 20° E., 323 lks. dist.  
New B.T. 18" Fir South 15 lks. dit.

Ben B. Irving, Deputy  
Witnesses

Wm. Crear

R. L. Irving

Feb. 28, 1928.

CS 37/133

TWP. CORNER OF SECTION 36 OF T. 29 R. 4--SECTION 31 T. 29 S. R. 3 W.--SECTION 6 T. 30 S., R. 3 W.,--and SECTION 1 T. 30 S., R. 4 W.

42

Identified by old rotted stake down and bearing faint scribe marks and original B.T.s. O.B.T. in section 36 down and rotting. B.T. in Section 31 broken off and dead. B.T. in section 1 dead and B.T. in section 6 alive but blazes having been chopped out are badly rotted.

Set a cedar post 4" x 6" x 12" for corner, scribed T. 29 S., S. 31 on N.E. face--R. 3 W. S. 6 on S.E. face--T. 30 S. S. 1 on S. face--R. 4 W. S. 36 on N.W. face.

New B.T.s as follows  
A 15" Black Oak N. 60° 5' W., 45.5 lks. scribed T. 29 S., R. 4 W., S. 36 C.S. B.T.

A 12" Fir N. 53° E., 29.8 lks. scribed T. 29 S., R. 3 W., S. 31 C.S. B.T.

O.B.T. A 14" Black Oak S. 79° 20' E., 477 lks. not chopped out or remarked

A 14" Black Oak S. 84° 10' W., 61 lks. scribed T. 30 S., R. 4 W., S. 1 C.S. B.T.

CLOSING SECTION CORNER ON EAST SIDE OF SECTION 1.

43

This corner set as instructed by U.S. Survey Office. Set by proportional measurement between the closing section corner between 1 and 12 and the N.E. corner of the township. Set a 3" x 36" pipe driven 32" in the ground. Marked

A 30" White Oak N. 70° 45' W., 62 lks. scribed 1/4 S. 1 C.C. C.S. B.T.

A 8" White Oak S. 43° 50' W., 20 lks. scribed 1/4 S. 1 C.C.