

Douglas County Surveyor's Record of
Government Corners Renewed

30 T. S. 4 R. W. W. M.

H. L. Eppstein
Wit.
N. E. Richardson
Wm. Rechor
Henry Rechor
Oct. 26, 1928

✓ W. CORNER TO $\frac{1}{2}$ CORNER BETWEEN 8 and 9.
Set For Axle for corner from

A 40" Black Oak S. 75° 03' W., 27 lks. O. B. T.
Marked
A 18" Fir N. 57° W., 27 lks.

53

✓ CLOSING SECTION CORNER BETWEEN 24 and 25.

Location identified from one original B. T. a Laurel
S. W., 25 lks. Drove an old Buggy axle 1" x 60" for
corner.

A 12" Oak N. 86° 19' W., 54.7 ft. T. 30S., R. 4W., S. 24
C. C. C. S. B. T.
A 20" Fir S. 48° 39' W., 40.3 ft. T. 30S., R. 4W., S. 25
C. C. C. S. B. T.
A 22" White Oak S. 7° 9' E., 79.2 ft. T. 30S., R. 4W.,
S. 50 C. C. C. S. B. T.

February 19, 1930.

54

✓ N. W. CORNER OF JACOB ANSLER D. L. C. # 51

Location identified from Fir B. T. which I remark. Oak
B. T. figures rotted out but position checks. Drove
Spike into root for corner.

A 36" Tan Oak N. 30° E., 39 lks. marked S. W. Cor. Cl. 50
Cl. 50 C. S. B. T.

55

✓ S. W. CORNER OF D. L. C. 51.

Identified from location of N. W. and S. E. corners
of claim. Comes in water of South Umpqua River. Chisel
X on rock.

A 14" Fir N. 10° W., 446 lks. marked S. W. Cor. Cl. 51
C. S. B. T.
A 14" Cedar N. 45° E., 396 lks. marked S. W. Cor. Cl. 51
C. S. B. T.

56

✓ CLOSING SECTION CORNER BETWEEN 22 and 23.

Location identified from one original B. T. a
S. W. 10" in ground. Remarkd original B. T. ~~BLM RESURVEY~~

✓ CENTER SECTION OF 22.

Stake 4" x 4" x 3" from which
A White Fir 18" diam. marked S. W. Cor. Cl. 51, 31.7 ft.
A 14" Fir S. 44° W., 11.5 ft.
A 14" Black Oak N. 24° E., 47.6 ft.
marked C. S. - B. T. N. 81° 00' E., 64.9 ft.

58

✓ CORNER BETWEEN SECTIONS 22 and 23.

Set from old B. T. S. Set 1" x 1" Iron Bar for
corner. Marked with B. T.

A 14" Fir S. 44° W., 11.5 ft.
A 14" Black Oak N. 24° E., 47.6 ft.

Old trees still up.

59

✓ N. E. CORNER OF D. L. C. # 43.

Location identified by a rock with X chiseled on the top.
While I was on the ground, a State Highway Department grader
cut the top off of this rock, which is located in the edge
of the road. Underneath this rock was another rock marked
with a X with dimensions of 8" x 10". A bottle was
buried alongside. The rock which was on top was turned
over and placed with its top flush with ground and marked
with cross. This rock is 8" x 10" x 18".

A Maple 24" diam. bears S. 2° 45' W., 86.0 ft.
An Oak 54" diam. bears N. 83° 35' W., 161.0 ft.
A Fir 20" diam. bears N. 55° 15' E., 126.2 ft.

All blazed and scribed N. E. D. L. C. 43 C. S. B. T.

60

✓ $\frac{1}{2}$ COR. BETWEEN 9-16

Set 1" Iron Bar with the following B. T.
8" Fir bearing S 31

RE-RENEWED, SEE CORNER NO. 144-69

61

(SEE ALSO #44)

Ben B. Irving D. C. S.
Wit.
N. E. Richardson
R. L. Irving
Feb. 26, 1940.
V. 46-E. 55

F. C. Frear
Wit.
Andy Moore
N. E. Richardson
Walt Hutchinson
Dec. 31, 1938
V. 15-E. 11

C. E. Roberts Ben B. Irving Dep. Co. Surveyor
Wit. J. I. Irving
Marion Perdue V. N. Poole
July 22, 1927
March 8, 1930