

Douglas County Surveyor's Record of  
Government Corners Renewed

30 T. S. 4 R. W. W. M.

✓  $\frac{1}{4}$  CORNER BETWEEN SECTIONS 23 and 24. 62  
Location identified from an original B.T., an Oak 48" diam. N.73°E., 67 lks. Chopped out scribe marks barely visible. Drove an iron pipe 1" x 48", 2" underground and set a rock 6" x 8" x 15" marked  $\frac{1}{4}$  S. along side top flush with ground, from which  
A Laurel 24" diam. bears N.36°W., 35.7 ft. marked  $\frac{1}{4}$  S. 23 C.S.B.T.  
An Oak 12" diam. bears N.36°E., 54.4 ft. marked  $\frac{1}{4}$  S. 23 C.S.B.T.

Ben B. Irving D.C.S.  
Witnesses  
N. E. Richardson  
R. L. Irving  
February 26, 1940.  
V16-E.55

✓ WITNESS TO  $\frac{1}{4}$  CORNER BETWEEN 15 and 16. 63  
Set from stone 15" x 12" x 5" marked on top. Set from original B.T. in excellent shape. *W.C. (JMB)*

✓ SECTION CORNER 15, 16, 21 and 22. 64  
Location identified from an original B.T. an Oak snag N.10°W., 35 ft. scribe marks visible. Drove an Iron pipe for corner from which  
A White Oak 14" diam. bears S.64°50'W., 227.5 ft. Marked T.30S., R.4W., S.16 C.S.B.T.  
A Fir 42" diam., bears N.33°50'E., 218.5 ft. marked T.30S., R.4W., S.15 C.S.B.T.  
A Fir 28" diam. bears S.67 $\frac{1}{2}$ °E., 139.6 ft. marked T.30S., R.4W., S. 22 C.S.B.T.  
A White Oak 16" diam. bears S.76°11'W., 317.9 ft. marked T.30S., R.4", S.21 C.S.B.T.

C.S. 30/49  
C.S. 53/96

CORNER BETWEEN SECTIONS 23, 24, 25, and 26. 65  
Renewed corner by setting a white quartz boulder 9" x 18" x 20" in mound of stone on left bank of South Umpqua. *SEE CORNER NO. 117*

F. Cain  
Mar. 23,  
1923

S.W. COR. DLC # 48 66  
Renewed from stump scribe marks showing  
B. O.-NW Corner Days Creek Store Bldg. S67°12'E 42.2 ft.  
SE Corner Lyles Service Sta. Bdg. S64°24'W 92.5 ft. *SEE ALSO REN # 248*

INTERIOR COR. DLC #48 67  
Renewed from Orig. BT set  $\frac{1}{2}$ " iron pipe.  
20" W. Oak S 5° W 44.88 ft. *SEE CORNER NO. 243*

SE COR. DLC #48 68  
Renewed by chaining North and West  
Set  $\frac{1}{2}$ " iron pipe.  
Marked 8" W. Oak N 3° 30' W 46.2 ft.  
10" Fir S 68°30' W 24.3 ft. *(SEE ALSO # 35)*

$\frac{1}{4}$  COR. BETWEEN 9-16 69  
Set 1" Iron Bar with the following B. T.  
8" Fir bearing S 21° W 3.96 ft. dist. *144*  
30" Fir bearing N 62° 45' E 16.5 ft. dist. *(SEE ALSO # 41)*

SEC. COR. 8-9-16-17 70  
Set a 1" I. Pipe with a brass cap marked County Surveyor; T 30 S, R 4 W, 819 with the following witness trees;  
17/16 20" W. Oak bearing S 13° 00' E 174.92 ft. dist.  
Remarked a 12" Oak marked by H. L. Eppstein.  
Jan. 26, 1948  
*(SEE ALSO # 16)*

FP SE BT  
BC 2 SE BT  
BY Larry Maday  
2/27/48 1118-48

B. B. Irving  
Cnty Surv.  
N. G. Richardson  
M. E. Godfrey  
L. S. Kershner  
Witnesses  
05. 39/155

G. J. Wenderoth  
Dep. Co. Surv.  
Nov. 1945