

Douglas County Surveyor's Record of  
Government Corners Renewed

30 S T. S. 4 W R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97196

SEC. COR. 20-29

Determined by O. B. T.

A B. Oak 36" diam., bears N 33° E, 32.0 ft. dist. 207  
At corner point set 1" x 30" I.P. 25 in. in ground, from which  
A W. Oak 7" diam. bears N 78° E, 11.9 ft. dist. marked  $\frac{1}{4}$ S, 2880, B.T.  
A W. Oak 6" diam. bears S 82° E 16.3 ft. dist. marked  $\frac{1}{4}$  S, 2880, B.T.  
A Cedar 9" diam. bears S 3° W, 25.3 ft. dist. marked  $\frac{1}{4}$  S, B.T.

79

John H. Markham, Jr.-Eng.  
Geo. & Wm. Vaughn- Witnesses  
December 23, 1950  
C.S. 40/496

$\frac{1}{4}$  SEC. COR. (WEST SIDE) SEC. 30

A W. Oak 40" in diam. bears S 30° W, 264.0 ft. dist. from truck axle  
and post scribed. This W. Oak has old scribe visible and has been  
remarked 1581, B.T. and is O.B. T. 223  
Tree should be S 0° 30' W, 264.0 ft. dist. as called for in field notes.  
True corner point would lie very close to present North and South fence  
and approx. 260 ft. North of fence corner. *J.H.M.*

80

COR. 13-14-23-24

Found 20" B. Oak N 61° W 23.7 ft.  
26" B. Oak N 4° E 27.0 ft.  
Oak Stump S 55° W 12.5 ft.

No other trees available.  
7/8" iron rod for corner.

81

Geo. J. Wenderoth  
F. Sincomb - Wit.  
August, 1950

C.C. SEC. 13-24

Set by measurement and topography.

Truck axle for corner.

6" W. Oak N 22° 15' E 25.4 ft.  
12" B. Oak S 46° 35' W 15.9 ft.

82

Geo. J. Wenderoth  
February, 1951

INNER D.L.C. 47 CORNER

As stone was too small for corner, replaced with  $\frac{3}{4}$ " iron pipe

16" W. Oak S 73° W 194.0 ft. unrooted.

Scribed the following B.T.s

20" W. Oak S 86° 40' W 198.2 ft.  
24" W. Oak S 20° 05' E 65.5 ft.

83

See C.S. 76

Geo. J. Wenderoth  
February, 1951

NORTH  $\frac{1}{4}$  COR. SEC. 5

This corner was never set by government. At midpoint on township line

I set a 1" x 24" iron pipe, from which

A Fir 12 in. diam. bears S 21° E, 109.0 ft. dist. marked  $\frac{1}{4}$  S, S 5, B.T.

A Laurel 20 ins. diam. bears S 52° W 73.0 ft. dist. marked  $\frac{1}{4}$  S5, T 30 S,  
R 4 W, 2880, B. T.

84

April 7, 1951  
C.S. 40/296

N.E. COR. SEC. 5

Determined by O. B. T.

A Fir 28 ins. diam. bears S 45° E, 7.0 ft. dist. O. B. T.

A Fir 27 ins. diam. bears S 33° W, 20.0 ft. dist. O. B. T.

I remark both trees.

At corner point set 1" x 24" iron pipe.

85

John H. Markham  
Wit. Geo. Vaughn  
Don Jeathers

Section corner 29-30-31 & 32

Location determined from old BT, a laurel stump N 15° E 26.0

A fir snag 14" dia. S 66° E 51.0'; A laurel 14" dia. S 67° W  
24.0'. At corner found a stonemonument.

Drove a 1"x30" pipe alongside stone and marked bearing trees

Fir 20" dia. N 77° E 26.0 ft.

Cedar 14" dia N 15° W 53.0 ft.

Laurel 24" dia. S 8° W 26.0 ft.

Fir 18" dia. S 25° E 64 ft.

86

John H. Markham Jr.  
Wit. Geo. Vaughn  
June 12 1951  
CS 40/296

6-12-51.