

Douglas County Surveyor's Record of
Government Corners Renewed

T 30 S T. S. R 4 W R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97196

87

July 25, 1951

Section Corner 5-6-7-8
Black Oak 26" diam. bears N 65° E, 40.0' distant, remarked
S.C. S 6, B.T.
Black Oak 10" diam. bears S 55° E, 56.0' distant, remarked
S.C. S 8, B.T.
White Oak 22" Diameter bears N 88° W, 40.0' distant, remarked
S.C. S 5, B.T.
Laurel 8" diam. bears S 52° W, 22' distant remarked S.C. S 7, B.T.
At corner point set 1" x 30" Iron Pipe from which:
corner bears North 2610'
corner bears West 254.0'
corner bears East 2695'
RENEWED SEE CORNER NO. 232
There is a fence running East and West from corner.

88

July 18, 1951

NORTH 1/4 SEC. COR. SECTION 6 (determined by O.B.T.)
A Fir 20" diam. bears S 42° W, 8.0' distant, old B.T.
At corner point found wood post and set 1" x 30" Iron Pipe at a
16" Fir which I marked on the North and South face, 1/4 S, S 6, B.T.
from which the corner to 31 | 32 bears N 76 1/2° E, 691.0' distant
6
The south 1/4 corner Section 31 bears S 76 1/2° W, 2076.0' distant.

~~THE CORNER OF LOT 4, SECTION 6 (by proportional measurement)
At the corner point on township line I set a 2" x 2" wood post
from which
A Fir 8" diameter bears S 45° W, 15.5' distant marked Lot 4, B.T.
A Fir 16" diameter bears S 37° E, 15.5' distant marked
1/16 S, B.T.~~ *not a 1/4 of section corner*

July 24, 1951

WEST 1/4 CORNER, SECTION 6 (determined by O.B.T.) **FOR SEC. 6 ONLY**
A Black Oak 10" diameter bears N 20° W, 280', found scribe
At corner point set 1" x 30" Iron Pipe from which
A Fir 36" diameter bears N 81° W, 10.0' distant marked 1/4 S, S 1, B.T.
A Laurel 10" diameter bears N 29° E, 18.0' distant marked
1/4 S, S 6, B.T.
This corner lies on top of a spur ridge on the West edge of a
large opening. **EYA S1 T30SR5W NOT SET BY GOV'T SURVEY**

89

Nov. 2, 1951

1/4 CORNER 5-8 **SEE #134**
Reported only. A Laurel 8" diameter bears N.39° E, 18.0' distant,
chopped out, scribe showing. Could not find other tree. Corner lies
50' North of side ridge on North slope. I blazed a line West from corner
for a 1/4 mile. **SEE LITTLE'S LETTER dated 3/60 in C.S. 5/85**

90

Nov. 2, 1951

North 1/4 sec. Cor. Sec. 3, T.30S R 4 W, W.M. **FD OK BY G. LAVIS 10-92 4117-1**
At the midpoint on the Twp. line between the NW and Ne corner of
sec. 3, I drove a 1"x30" I.P. from which
A Cedar 9" diam. bears S50° E, 13.0' dist. marked 1/4 S 53, B.T.
A Cedar 5" diam. bears S 15° E, 9.0' dist. mkd. 1/4 S 53, B.T.
N.W. Cor. sec. 3 bears West 2673'
N.E. Cor. sec. 3 bears East 2673'
Sec. Cor. 34 - 35 bears East 342.0'

91

Nov. 2, 1951

N.E. Cor. of Sec. 3 T.30S, R 4 W., W.M. as det. by O.B.T. **SEE #14**
A Fir stump bears S 73 W. 14 1/2' dist. O.B.T.
At corner point set 1"x30" I.P. from which
A Cedar 6" diam. bears S8° W, 66 1/2' dist. mkd. 53, 2880, B.T.
corner bears East 165.0'
Fork in read bears S58 W, 88.0'
Corner lies just along West edge of upper road.

92

*Should be checked
old notes do not call
for fir stump - see
removed by fence
1919
checked + found
O.K. J.H.M.*

John H. Markham Jr.
Witness
Geo. Vaughn

John H. Markham Jr.
Witness
Dennis & Geo. Vaughn.

John H. Markham Jr.,
Witness
Dennis and Geo. Vaughn.

*Copy from No. 14
Geo. Vaughn*

*C.S. 40/286
File 30000 L.C.*

*C.S. 40/386
File 30000 L.C.*