

Douglas County Surveyor's Record of
Government Corners Renewed

30 T. S. 4 R. W. W. M.

KONE-CHAPMAN CO., EUGENE, ORE. 97198

N.W. Corner of section 3 T.30 R.4 W.W.M.

I could read scribe on both O.B.T. s and rescribed them.

At corner point set 1"x30" I.P. from which

A Fir 9" diam. bears S 46E, 27.5' dist. mkd. S3 B.T.

A Cedar 15" diam. bears S6E, 31.0' dist. mkd. S3 B.T.

O.B.T.s are as follows:

A Laurel 17" diam. bears S 65 E, 22.0'

A Fir 48" diam. bears 58 W, 16.0'

SEE ALSO # 93
150

RE-RENEWED, SEE CORNER NO. 189

See also C. S. File No. 42/257. (1957 survey)

Witness
John H. Markham Jr.
Dennis and Geo Vaughn
Feb. 13, 1952

C.S. 40/386 & C.S. 40/386
Nov. 2 1951
C.S. 40/386

1/4 Section corner 21 - 28.

A dead B.O. snag fallen bears S 55°E, 215.0 feet distant.

I chopped out this B.T. and found scribe.

At corner point I set 1" x 30" I.P., from which

A B.O. 7" in diam. bears N 68°W, 112.0 feet distant. mkd. S3

S 28° T 30 S R 4 W, B.T.

Fence corner bears N 68°W, 78.0 feet distant.

Farm house on Beals Creek bears N 9° W (Var. 18°30')

Corner lies on steep east slope

Sec. corner 21, 22, 27, & 28 bears East 2522.0 feet.

RE-RENEWED, SEE CORNER NO. #276

Witness
John H. Markham Jr.
Wit: Frank Harrison
Feb. 13, 1952

C.S. 40/386
Feb. 13, 1952

East 1/16 corner between Sec. 21 - 28

At the mid-point between NE corner and North 1/4 corner

Sec. 28, I drove 1/2" I.B. from which

A Fir 18" in diam. bears West 29.0 feet dist. mkd. 1/16s, B.T.

Center of road bears west, 65.0 feet dist.

There is an old fence running east and west from corner.

RE-RENEWED, SEE CORNER NO. #275

Witness
John H. Markham Jr.
Frank Harrison, Witness
Feb. 13, 1952

C.S. 40/386
Feb. 13, 1952

E C SECTION 24 and 25

Found 1" I. Bar.

12" Oak, N 86°19'W. 54.7 feet.

other tree gone.

Scribe, 16" B. Oak, S 61°50'W. 77.9 feet.

RE-RENEWED, SEE CORNER NO. 171

1/4 CORNER EAST SIDE SECTION 24.

Put 1/2 way between section corners 3/4" I. Pipe.

8" W. Oak, N 41°45'W. 12.5 feet.

8" W. Oak, S 36°50'W. 7.5 feet.

RE-RENEWED, SEE CORNER NO. #296

Witness
Geo. Wenderoth
Wit: J. Ritter
April, 1951

C.S. 41/111

INNER CORNER G.T.DAYS D.L.C.NO. 47

3/4" Iron Pipe. Old B.T. is uprooted. (Rev # 83)
New B Ts.

20" W. Oak S 86°40' W. 198.2 feet

24" W Oak S 20°05' E. 65.5 feet

Geo. Wenderoth
Wit: Ralph Little
Feb. 1951

Witness
Geo. Wenderoth
Wit: J. Ritter
April, 1951
C.S. 41/117

C.S. 41/117