

Douglas County Surveyor's Record of
Government Corners Renewed

30 T. S. 4 R. W. W. M.

ROKE-CHAPMAN CO., EUGENE, ORE. 97196

Wenderoth
Feb. 1952

John H. Markham Jr. - - June 2, 1953 - - Work done for Stomar Lbr. Co.
Witness - - B. E. Blomgren
Notes in Sur. file 41/161

John H. Markham Jr. - - June 9, and June 10, 1953.
Work done for Stomar Lbr. Co.
Witness - - B. E. Blomgren
Notes in Surveyors file 41/161

SECTION 30 3/4 DRILL 1/16 CORNER WHICH IS NORTHWEST CORNER
OF THE SOUTHEAST QUARTER OF THE NORTHWEST QUARTER:

- 38" White Oak N. 72 degrees 23' East, 69.2 Ft.
- 16" White Oak S. 81 degrees 05' East, 178.8 Ft.
- 16" White Oak N. 66 degrees 37' West, 190.6 Ft.

99

1/4 Section corner 20-21, T30S, R4W, W.M. as det. by O.B.T. 100
 A 30" W.O. bears N12W, 244' dist. I remarked 1/2 S20, B.T.
 A 40" B.O. bears S70E, 172.0' dist. I fd. scribe and remarked
 19 32' B.T.
 At corner point set 1" X 30" axle with 6" flange up.
 A 10" B.O. bears N80E., 30.0' dist. marked 1/2 S 21 B.T. #277
 Fences run N-E and W. Fence corner bears N57W, 11 1/2' dist.

RE-NEWED, SEE CORNER NO. #277

Section corner 19, 20, 29, and 30, T30S, R4W, W.M. as det. by O.B.T.s. 101
 A 15" W.O. snag bears N20°E., 30.0' dist. fd. old scribe.
 A 35" B.O. windfall bears S60E., 195.0' dist. found scribe.
 A W.O. 20" bears N56W, 30.0' dist. 206
 At corner point set 1" X 20" axle with 6" flange up.
 from which
 A B.O. 40" diam. bears N26W., 49.0' dist. mkd. S19 B.T.
 A 10" W.O. bears N73E., 33.3' dist. mkd. S20 B.T.
 A 12 " W.O. bears S28E., 73.3 dist. mkd. S29 B.T.
 A W.O. 30" diam. bears S57° W., 137.)' dist. mkd. S30 B.T.
 A fence runs N and S from corner.

Section corner 20-21-28-29, T30S, R4W, W.M. as det. by O.B.T. 102
 A 35" B.O. bears N2W., 121.0' O.B.T.
 A 26" W.O. bears N3E., 126.0' O.B.T.
 A 14" W.O. bears S34E., 55.0' O.B.T.
 At corner point set 1" X 30" axle with 6 1/2" flange up.
 from which
 A 8" W.O. bears S42E., 23.4' dist. mkd. S28 B.T.
 A 10" W.O. bears N54W., 18.2' dist. mkd. S20 BT.
 A 12" W.O. bears N17E., 13.0' dist. mkd. S21 B.T.
 Fence corner bears N77W., 25.0' dist.

1/4 section corner 19/30, T30S, R4W, W.M., as det. by O. B. T.s. 103
 A 24" Fir bears N80E., 11.0'. ← see cor. #49
 A 30" Fir stump bears S45W, 44'.
 A 30" Fir bears S 45 E., 46'.
 At corner pt. set 1" X 30" iron pipe
 from which
 A maple 13" diam. bears S2W., 13 1/2' dist. mkd. 1/2 S 2880 B.T.
 There is a fence running N & W from corner.
 Sec. line bears S 82° W.
 Sec. line bears S 87°30' E. (Var. 20°00').

S. E. corner of D. L. C. no. 37, T 30 S, R 4 W., W. M. as det. by OBT. 104
 A 14" B.O. snag bears N 50° W., 18.5' dist. -- found scribe.
 At cor. pt. set 1" X 20" iron pipe from which - - - -
 A 18" B.O. bears N54W., 60.0' dist. mkd. CL 37 B.T.
 A 12" La. bears West 36.0' dist. mkd. CL 37, T30S, R4W., B.T. 220
 Fences run N & W from corner.

1/4 section corner 18/19, T30S, R4W, W. M. as det. by O. B. Ts. 105
 A 40" B. O. stump bears N84E., 50.0' dist. --found old scribe.
 A 30" B.O. stump bears S20E., 23.0' dist. --found old scribe.
 At corner point set 3/4" X 96" iron pipe with metal plate on top
 mkd. 1/4 18/19. from which - - - -
 A 10" B.O. bears N17W 78.0' dist. mkd. 1/2 S 18 2880 B.T.
 A 9" La bears S40E., 63.0' dist. mkd. 1/2 S 19, T30S, R4W., 2880 B.T.
 A steel gate bears S69W 95.0' --Power pole #12/33 bears S69W, 115.0'.
 S.E. cor. CL. #37 bears S 33.0' & E. 314'. A 3way fence Cor. bears S28E. 41' 0.57.