

Douglas County Surveyor's Record of  
Government Corners Renewed

30

T. S.

4

R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97196

John H. Markham Jr.  
Witness:  
J. D. Phillips  
Done for Stomar Imbr. Co.  
October 26, 1954  
C. S. File 41/308.

1/4 section corner to secs. 7 & 8. 112  
Determined by:  
A 30 inch B. O. stump (6 feet high and alive) bears N.65°E.,  
83.8 feet dist. and a 30 inch W. O. bears N.20°W., 327.0 feet,  
both O. B. T.'s.  
At corner point:  
Set 3/4 inch x 20 inch reinforcing rod and pile of stones, 237  
from which  
A 15 inch W. O. bears N.18°E., 80.0 feet dist. mkd. 1/4 S 8 B. T.  
A 33 inch B. O. bears S.65°W., 68.0 feet dist. mkd. 1/4 S 7 B. T.  
A fence line bears south 137 feet.  
Corner lies 137 feet north of 100 acre field in So. Umpqua bottom.

A. R. Evans, Deputy County Surveyor  
July, August, 1951.  
C. S. File No. 45/69.

Closing corner to sections 6 and 7. 113  
Found 3/4" x 2" I. Bar <sup>See Cor. # 37</sup> 4 original B. T.'s. Blazed and scribed new trees:  
20" Fir - N.25°E., 34.0 feet, mkd. T30S, R4W., S - 6, C. S. B. T.  
30" "Y" Fir - S.35°E., 29.0 feet mkd. T 30, R 4, S - 7, C. S. B. T.  
*Fr. O.K. 8/65 J.W. Byrum*

R. M. Thompson  
Dec. 17, 1955.  
C. S. File No. 42/171.

1/4 corner sec. 7, T 30 S, R 4 W., <sup>ONLY</sup> and ~~secs. 12, T 30 S, R 5 W.~~ 114  
Set 5/8 inch Iron Rod by proportional measurement. *J.W.B. 1946*  
Blazed and Scribed:  
20" Fir, N.40°E., 23.2 feet mkd. 1/4 S 7, T 30, R 4, R.E. 2741, C.S.B.T.  
14" Fir, N.29°W., 23.0 feet mkd. 1/4 S 12, T 30, R5, R.E. 2741, C. S. B. T.

Harrison M. Munger  
August 10, 1955.  
C. S. File No. 42/177.

Section corner to secs. 7 & 18, T30S, R4W., and secs. 12 & 13, T30S, R5W. 115  
Set 5/8 inch Iron Rod from 2 Orig. B. T.'s. SEE CORNER NO. 244  
Blazed and scribed New B. T.'s:  
30" Fir, N.34°E., 27.5 feet, mkd. T30S, R4W., S 7, C. S. B. T.  
10" Pine, N.22°W., 18.1 feet, mkd. T30, R5, S 12, C. S. B. T.  
20" Pine, S.15°E., 33.7 feet mkd. T30, R4, S 18, C. S. B. T.

H. L. Eppstein,  
County Surveyor.  
Dec. 5, 1928.  
Vol. 3, P. 288-9.

1/4 sec. corner to secs. 2 and 3. 116  
Found 1 inch iron pipe and 14 inch Cedar B. T., S.81°E., 24.5 feet.  
Marked new B. T.:  
14 inch I. Cedar, S.4°10'E., 29.3 feet. *SEE COR. # 78*

Section corner to secs. 23, 24, 25 and 26. 117  
Old corner could not be found. — *SEE COR. # 65*  
Set new corner by double proportion.  
Built a stone monument three feet high of river boulders, using a large,  
relatively cubic, quartz rock to mark the exact corner.  
Marked four trees:  
18 inch Alder bears N.76°00'E., 267.0 feet, marked as follows:  
S24 T30S R4W BT 3571 (in wood)  
30 inch Fir bears S.22°30'E., 279.0 feet, marked as follows:  
NW cor CL 51 CS (in bark, and faint: I freshened it)  
56 inch Fir bears N.70°00'W., 210.0 feet, marked as follows:  
S23 T30S R4W BT 3571 (in bark).  
24 inch Fir bears S.80°00'W., 206.7 feet, marked as follows:  
S26 T30S R4W BT 3571 (in wood). SEE CORNER NO. 254  
The Alder and 30 inch Fir are on East bank of river, and will probably  
not be disturbed, though they are on bank opposite the corner. The  
other Firs are in an area being logged and may be felled.

Center 1/4 corner to section 9. 118  
Point for corner established by proportional measurement.  
At point for corner, Set stake in field,  
From which marked B. T.'s:  
22 inch W. Oak, S.3°E., 420 lks.  
12 inch Alder, S.47°W., 372 lks.