

Douglas County Surveyor's Record of
Government Corners Renewed

30 T. S. 4 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

James W. Byron, Deputy
M. Godfrey
S. Bilow
July 30, 1958
C. S. File No. 49/45

Closing Corner to Sections 12 & 13.
Found - Orig. 14", now 22" W. Oak S.79°W. 495.0 ft. I find good scribing "BT". 137
Fir Stump, now 36" that checks bearing & distance for Orig. N. W. BT. Stump has been badly burned & partly rotted, no scribing found.
Set Brass Cap at Corner Mkd: C.C. $\frac{R4W}{S12} \frac{R3W}{S18}$ T30S County Surveyor's Office, 1958
New BT: 10" W. Oak bears S.41°W. 186.0 ft. scribed C. C. 13 T30S R4W CS BT.
Chisled + 3" high & B O in solid rock outcropping on vertical face 12" above ground. Exposed Ledge 3' x 3' x 3' faces S.20°W. N.36°W. 23.0 ft. from Corner.

Willis M. Ausland
For Al Roe
Jan. 1942
Entered 12/17/58
C.S. File 36/17
c.s. 30/49

$\frac{1}{4}$ Section Corner between Secs. 16 & 21. SEE ALSO #143 138
Set Gun Barrel for $\frac{1}{4}$ Corner from Witness Tree,
12" Fir S.66°W. 16 lks., standing & in good shape.

Section Corner to Sections 16, 17, 20, & 21. 138-A
Set Gun Barrel for Section Corner from 2 Witness Trees:
28" Fir N.20°E. 10 lks., good shape.
30" Fir N.47 $\frac{1}{2}$ °E. 19 lks., good shape. SEE #133 224
New Witness Trees:
20" Fir S.74°W. 22.0 ft.
8" Fir S.18°W. 36.5 ft.

John H. Markham, Jr.
Wit. R. G. Boyd
For Stomar Lbr. Co.
Dec. 16, 1958
C.S. File No. 42/356

Section Corner to Sections 22, 23, 26, & 27. 201 139
as determined by O.B.T's.
42" Fir N.24°E. 17.2 ft. O.B.T.
24" Fir (logged) Stump bears S. 1°E. 69.0 ft. dist. O.B.T. fd. scribe.
42" Fir S.79°W. 30.5 ft. O.B.T.
36" Fir N.29°W. 53.0 ft. O.B.T.
At Corner Point found Stone and Set 2"x 40" Steel Shaft from which:
16" Laurel bears S.82°E. 26.0 ft. dist. mkd. S826 BT.
14" Laurel bears N.30°E. 8.5 ft. mkd. S23 B.T.
10" Laurel bears N.29°W. 39.4 ft. mkd. S22 T30S B.T.
14" Fir bears N.58°W. 44.2 ft. mkd. S22 B.T.
Top of ridge bears West 120.0 ft.

James W. Byron, Deputy
Milo Godfrey
S. A. Bilow
Feb. 19, 1959
For Al. Rowe
C. S. File No. 51/5 - RM/- 28

Section Corner to Sections 15, 16, 21, & 22. 140
Found - 1 $\frac{1}{2}$ " Iron Pipe at Corner. SEE COR. #64
Now 28" B.O. N.70°W. 334.4 ft., I open & find good scribing, scribed 1940 (ring count).
Now 30" Fir Stump shows good scribing.
18" W. Oak shows good scars. I do not open, checks record distance 227.5 ft. I find bearing should be N.16°W., record N.34°50'W.
Set Brass Cap at Corner Mkd: County Surveyor's Office, 1959 $\frac{S16}{S21} \frac{S15}{S22}$ T30S R6W
New BT's: 30" B.Oak bears N.72°E. 199.3 ft. scribed S15 T30S R4W CS BT.
Rescribe now 24" B.Oak that bears N.70°W. 334.4 ft., S16 T30S R4W CS BT.

Renew Witness Corner to Sections 9, 10, 15, & 16. 141
Found - 1" Iron Pipe at Wit. Cor. & Stewart's BT., now 18" B.O. S.31°W. 18.5 ft., shows scar, I do not open. - SEE COR. #23
New BT's: 33" B. Oak bears S.13°E. 35.5 ft. scribed S15 T30S R4W CS BT WC.
28" B. Oak bears N.33°W. 57.7 ft. scribed WC S10 T30S R4W CS BT.
13" W.Oak bears N.81°E. 197.0 ft. scribed S10 T30S R4W WC CS BT.
Wit. Cor. 192.49 ft. West To Section Corner. CORNER NO. 198