

Douglas County Surveyor's Record of  
Government Corners Renewed

30 T. S. 4 R. W. W. M.

MOKE-CHAPMAN CO., EUGENE, ORE. 21881

Center  $\frac{1}{4}$  of Section 16. 143  
Set Brass Cap at Corner Mkd: C $\frac{1}{4}$  S16 T30S R4W CS BT 1959.  
From Which:  
14" R. Fir bears N.20°E. 53.6 ft. scribed C $\frac{1}{4}$  S16 CS BT.  
20" B. Oak bears N.25°W. 43.5 ft. scribed C $\frac{1}{4}$  S16 CS BT.

$\frac{1}{4}$  Section Corner to Sections 9 & 16. 144  
Found - 1 $\frac{1}{4}$ " Car Axle at Corner. - SEE GOES #144 & 6944 #274  
4 Stumps that have been cut low that check bearings  
& distances as recorded. No scribing Found.  
New BT's: 16" R. Fir bears N.30 $\frac{1}{2}$ °E. 64.4 ft. scribed  $\frac{1}{4}$  S 9 CS BT  
46" R. Fir bears N.19° W. 275.7 ft. scribed  $\frac{1}{4}$  S9 CS BT.

$\frac{1}{4}$  Section Corner to Sections 16 & 21. SEE ALSO #138 143  
Found - Rifle Barrel at Corner & Both Original BT's.  
Set  $\frac{3}{4}$ " Iron Rod alongside Rifle Barrel at  $\frac{1}{4}$  Corner. # 204

$\frac{1}{4}$  Section Corner to Sections 34 & 35. 144-A  
At the proportional distance, I set  $\frac{3}{4}$ " x 30" Iron Rod for  
 $\frac{1}{4}$  Corner from which:  
12" Fir bears S.42°E. 24.0 ft. dist. mkd.  $\frac{1}{4}$  S35 B.T.  
12" Fir bears S.74°W. 21.0 ft. dist. mkd.  $\frac{1}{4}$  S34 B.T.  
7" La. bears N.43°W. 13.6 ft. dist. mkd.  $\frac{1}{4}$  S34 B.T. #266  
N.E. Corner 34 bears North 2600.0 ft.  
S.E. Corner 34 bears South 253.0 ft.

Section Corner to Section 26, 27, 34, & 35. 145  
as determined by O.B.T.'s. #269  
40" Fir bears N.58°E. 45.5 ft. dist., O.B.T.  
24" Maple Snag bears N.44°W. 49.5 ft. dist. O.B.T.,fd. scribe.  
At Corner Point found Stone & Set  $\frac{1}{2}$ " x 24" Iron Rod from which:  
18" Yew bears N.78°W. 58.0 ft. dist. mkd. S27 B.T.  
4" La. bears S.5°E. 28.0 ft. dist. mkd. S35 B.T.  
4" Chip. " S46°E. 48.0 ft. dist., mkd. S35 B.T.  
4" Maple " N.67°E. 18.0 ft. dist. mkd. S26 B.T.

S. E. Corner Section 34. 146  
At a Point 198.0 ft. East of N.W. Corner Section 2, I set  
 $\frac{3}{4}$ " x 30" Iron Pipe from S.C. from which: #258  
8" La. bears S.60°E. 27.5 ft. dist. mkd. S2 T31S R4W BT.  
30" Cedar " S.40°W. 18.5 ft. dist. mkd. S2 X B.T.  
6" La. bears N.77°W. 19.0 ft. dist. mkd. S34 B.T.  
5" Fir bears N.18°E. 13.8 ft. dist. mkd. S35 B.T.  
Section Corner  $\frac{3}{2}$  bears West 198.0 ft.

East  $\frac{1}{4}$  Section Corner Section 35 only, 147  
As determined by O.B.T.  
At Corner Point found 50" Fir Snag, bark scribed " $\frac{1}{4}$ S" on  
West face & Set  $\frac{3}{4}$ " x 30" Iron Pipe from which:  
40" Fir bears N.22°E. 35.0 ft. O.B.T.  
12" La. bears N. 7°W. 26.5 ft. dist., mkd.  $\frac{1}{4}$  S35 T30S R4W B.T.  
7" La. bears S.81°E. 17.6 ft. dist. mkd.  $\frac{1}{4}$  S36 B.T.  
8" Fir bears S.43°W. 13.9 ft. dist., mkd.  $\frac{1}{4}$  S35 B.T.  
C.C. Section 35-36 bears South 381.0 ft.

S.W. Corner Section 36, 148  
as determined by O.B.T.  
24" Fir bears S.31°W. 23.1 ft. O.B.T.  
10" La. Snag " S.41°E. 12.5 ft. O.B.T.  
At Corner Point, Set  $\frac{3}{4}$ " x 30" Iron Pipe from which:  
13" Fir bears S.76°W. 4.5 ft. dist. mkd. S1 X B.T.  
12" Fir bears N.63°W. 7.5 ft. dist. mkd. S35 B.T.  
7" La. bears N.75°E. 20.1 ft. dist. mkd. S36 T30S R4W B.T.

James W. Byron, Deputy  
Milo Coffey  
S. A. Bilow  
For Al Rowe  
Feb. 19, 1959  
C.S. File No. 51/5 - RM 28

John H. Markham, Jr.  
Witness: R. G. Boyd  
Stomar Lumber Co.  
February 22-24, 1959  
C. S. File No. 424356