

Douglas County Surveyor's Record of
Government Corners Renewed

30 T. S. 4 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21801

continuing -

C. C. Section 2/1 bears West 344.0 ft.
East 1/4 Corner 35 bears North 381.0 ft.

John H. Markham, Jr.
R. G. Boyd, Wit.
For Stomar Lbr. Co.
April 29, 1959
C. S. File No. 42/356

S. E. Corner Section 36, T30S R4W, & S.W. Cor. Sec. 31, T30S R3W, only. 149
As determined by O. B.T.'s:
13" La. bears S31°W. 26.4 ft. dist. O.B.T., fd. scribe. 174
13" La. bears N.16°W. 33.0 ft. O.B.T., fd. scribe, I remarked
S36 T30S B.T.
24" Fir bears S.51°E. 29.7 ft. O.B.T. - I bark scribed S31 T31S B.T.
At Corner Point Set 1" x 30" Iron Rod from which:
7" Chip. bears N.43°W. 47.0 ft. dist. mkd: S36 R4W B.T.
30" Fir bears N.40°E. 17.0 ft. dist. mkd: S31 T30S B.T.
9" La. bears N.80°E. 45.0 ft. dist. mkd: S31 T30S R3W B.T.

Section Corner Common to Sections 3 & 4. 150
Monumented with an Iron Pipe 1 1/2" diam., 3" below surface of the
ground & marked RS298, from which:
A Cedar 20" diam. bears S.5°E. 48 lks. Mkd. S3 BT. #189
A D. Fir 48" " bears S10°W. 27 lks. dist., Mkd. S4 BT.

1/4 Section Corner on the North Bdy. of Section 4. 151
Monumented with an Iron Pipe 1 1/2" diam., 8" above the ground
and Mkd. RE298, from which:
A Madrona 8" diam., bears S. 3°E., 28 lks. dist., mkd. S4 RS298 BT. #184
A D. Fir 6" diam., bears S.26 1/2°W. 35 lks. dist., mkd. S4 RS298 BT.

Center 1/4 Section Corner, Section 4. 152
Monumented with an Iron Pipe 1 1/2" diam., 8" above ground & mkd.
RS298, from which:
D. Fir 16" diam., bears N. 87°E., 6 lks. dist., mkd. C 1/2 S4 RS298 BT.
Cedar 8" diam., bears S.13 1/2°E., 15 lks. " " C 1/2 S4 RS298 BT.
D. Fir 8" diam., bears S. 45°W., 9 lks. " " C 1/2 S4 RS298 BT.
Cedar 6" " " N.24 1/4°W., 14 lks. " " C 1/2 S4 RS298 BT.
FOUND 1970 - SEE M 42 - 1

1/4 Section Corner between Sections 3 & 4. 153
Monumented with an Iron Pipe 3 ft. long 1 1/2" diam., 8" above
ground & mkd. RS298, from which: SEE COR. #125
A D. Fir 28" diam., bears S. 78°E., 34 lks. dist., mkd. 1/4 S3 RS298BT
A Cedar 26" diam., bears N.76°W., 56 lks. dist., mkd. 1/4 S4 RS298BT

1/4 Section corner to Sections 26 and 35, as determined by O.B.T.'s.: 154
40" Fir bears North 22.4 feet O.B.T.
30" Fir bears S.63°E. 21.1 feet, found scribe.
At Corner Point Set 3" x 30" Iron Pipe from which:
3" Alder bears S.71°E. 31.0 ft. dist. mkd. 1/4 S35 B.T.
50" Fir bears S.50°E. 25.0 ft. dist., bark scribed 1/4 S35 B.T.
Shively Creek bears West 250.0 ft. distance.

S. W. Corner Section 34. 155
At Corner Point Set 1/2" x 1/2" x 30" Angle Iron, from which:
12" Alder bears East 7.0 ft. dist. mkd. S34 B.T.
8" Fir bears N.36°E. 26.0 ft. dist. mkd. S34 B.T.
10" Laurel " N. 2°W. 33.6 ft. dist. mkd. S33 T30S R4W B.T.
See Sketch in file.

1/2 Corner Section 33 & 34, as det. by O.B.T.'s.: 156
30" Fir N.42°E. 7.3 ft. dist. O.B.T.
15" Fir N.56°W. 6.6 ft. dist. O.B.T.
At Corner Point Set 1/2" x 1/2" x 30" Angle Iron from which:
5" Laurel bears S.13°E. 22.7 ft. dist. mkd. 1/4 S34 B.T.
5" Alder bears N.69°W. 15.5 ft. dist. mkd. 1/4 S33 B.T.
18" Fir bears North 4.7 ft. dist. mkd. 1/4 S B.T.

Marvin C. Ramsey,
For J. H. Baxter & Co.
Witnesses: R. Burch & J. Beed
Filed May 6, 1959
C. S. File No. 51/19

See C.S. 7/6

John H
Markham, Jr.
For Stomar
Lbr. Co.
10/7/59
C.S. 42/356

Nov. 17, 1959
C.S. File
No. 42/356