

Douglas County Surveyor's Record of
Government Corners Renewed

30 T. S. 4 R. W. W. M.

S. W. Corner George Day D. L. C. No. 47.

Found Original 8" W. Oak B.T., now 16", N.80°E., 60.72 feet,
scribing partly rotted.

To renew, I scribe: 33" W.O. S.86°40'E., 80.6 feet.

157
(Ren #26)

For Lee Ellefson
T.L. Weaver
By: R.M. Thompson
Feb. 16, 1960
M 17 - 17

Section Corner to Sections 27 - 28 - 33 - 34,
as determined by O. B. T's:

16" Dead Fir Snag N.38°E. 8.9 ft. O.B.T., fd. scribe.

40" Fir S.75°E. 29.7 ft. O.B.T.

40" Dead Fir S.85°W. 44.0 ft. O.B.T.

20" Fir Stump, logged, N.26°W. 24.4 ft. O.B.T.

At Corner Point Set Wood Post from which:

60" Fir bears S.52°W. 40.0 ft. mkd. S33 T30S B.T.

50" Fir bears N.31°W. 107.0 ft. mkd. S25 T30S R4W B.T.

158

John H.
Markham, Jr.
For Stomar
Lumber
June 29,
1960
C.S. File
42/356

$\frac{1}{4}$ Section Corner to Sections 28 and 33.

as determined by O. B. T's:

15" Fir N. 3°W. 29.0 ft. O.B.T., fd. scribe.

30" La. S.37°W. 18.5 ft. O.B.T., I rescribed $\frac{1}{4}$ S33 B.T.

At Corner Point Set 1" x 30" I. P. from which:

9" Chip. bears S.44°E. 23.0 ft. mkd. $\frac{1}{4}$ S33 B.T.

10" Fir bears S.62°W. 24.3 ft. mkd. $\frac{1}{4}$ S33 B.T.

5" Cedar bears S.62°W. 27.6 ft. mkd. $\frac{1}{4}$ S33 B.T.

Top of ridge bears East 135.0 feet.

159

John H. Markham, Jr.
For Stomar Lumber Co.
Wit: R. G. Boyd
August 3, 1960
C. S. File No. 42/356

$\frac{1}{4}$ Section Corner to Sections 26 and 27.

as determined by O.B.T's:

36" Fir Stump, logged, bears N.47°E. 9.6 ft. O.B.T., fd. scribe.

26" Fir Stump, logged, bears North 19.5 ft. O.B.T.

At Corner Point found dead 22" Fir Snag scribed on West

face & Set $\frac{3}{4}$ " x 40" I. P. from which:

12" La. bears S.80°W. 39.0 ft. mkd. $\frac{1}{4}$ S27 T30S R4W B.T.

12" Chip " S.43°W. 34.3 ft. mkd. $\frac{1}{4}$ S27 B.T.

12" Fir bears S.11°W. 21.7 ft. mkd. $\frac{1}{4}$ S26 B.T.

3" Fir bears S.50°E. 8.0 ft. $\frac{1}{4}$ S B.T.

160

$\frac{1}{4}$ Section Corner to Sections 27 and 28.

Set from field notes taken by me before road construction.

Corner point falls in road & both O. B. T.'s. were destroyed.

From Corner Point:

8" La. N.26°W. 30.0 ft. mkd. $\frac{1}{4}$ S28 T30S R4W B.T.

30" Fir N.25°E. 17.3 ft. mkd. $\frac{1}{4}$ S27 B.T.

9" La. S.67°E. 31.0 ft. mkd. $\frac{1}{4}$ S27 R4W B.T.

161

Section Corner Sec. 34, T30S R4W, & Sec. 3, T31S R4W.
as determined by O. B. T's:

40" Fir S.5°E. 2.6 ft. O.B.T., fd. scribe on bark &
rescribed $\frac{1}{4}$ S 3 B.T.

30" Cedar N.27°E. 6.0 ft. O.B.T., I rescribed $\frac{1}{4}$ S34 B.T.

At Corner Point Set Stone from which:

14" Chip. bears S.62°W. 33.5 ft. mkd. $\frac{1}{4}$ S3 R4W B.T.

10" La. bears S.52°W. 24.5 ft. mkd. $\frac{1}{4}$ S3 T31S R4W B.T.

Note - This is not a $\frac{1}{4}$ corner to either section, but rather
a point on Twp. Line since both section had closing
corners.

162

Section Corner to Sections 28 - 29 - 32 - 33.

As determined by O.B.T's.: 42" Fir N.79°E. 89.8 ft. O.B.T.

32" Dead Fir N.68°W. 46.2 ft. O.B.T.

40" Dead Fir S.89°W. 55.8 ft. O.B.T.

At Corner Point fd. Stone & Set $\frac{3}{4}$ " x 30" Iron Pipe from which:

9" La. bears N.64°W. 12.6 ft. Mkd: S29 T30S R4W B.T.

10" Fir N.47°E. 6.5 ft. Mkd: S28 B.T.

17" Fir S.31°E. 9.7 ft. Mkd: S33 B.T.

163

John H. Markham, Jr.
June 24, 1961
C.S. File 42/356