

Douglas County Surveyor's Record of
Government Corners Renewed

T. 30 S. T. S. R. 4 W. R. W. W. M.

KOBE-CHAPMAN CO., EUGENE, ORE. 21681

James W. Byron, Deputy County Surveyor
Mike Darby and Wm. Stoffel
March 1963

C. S. File No. 52/138

C. S. File No. 52/126

Closing Corner CC T30S 176
R4W S 1/S 6 R3W T31S
Found - Orig. 14", now 24" Maple S.67°W. 42.5 ft., shows good scribing.
Orig. 36", now 40" Fir S.55½°E. 22.6 ft., shows scribing.
Orig. N.E. BT. shows scar. Find Corner Stone as recorded.
Set - Brass Cap alongside Cor. Stone Mkd: County Surveyor's Office, 1963 CC T30S
R4W S1/S6 R3W
Rescribe, now 24" Maple T31S S.67°W. 43.0 ft. S1 CS BT CC. T31S

Renewed Corner R4W R3W T30S 177
S36 / S31 T31S
S 1 T31S
Found - 1" I. Bar at Corner & BT's. as recorded by Markham, 1959. SAME AS #174
Orig., now 13" Laurel N.16°W. 33.0 ft., bark scribed, we rescribe,
(wood) T30S R4W S36 CS BT. Chinquapin to N.W. now dead.

Section Corner to Sections 13 - 14 - 23 - 24. 178
Found - 7/8" I. Rod at corner. Orig. 16", now 24" B. Oak S.75°E. 6.6 ft.,
shows reverse scribing. SEE COR. # 81
Orig. 20", now 24" B.O. N.4°E. 27.1 ft. We rescribe this BT.
Also find Orig. N.E. & N. W. BT's., show scars.

South ¼ Corner to Section 35 only, T29-4W. 179
Found - 1" I. Pipe at Corner - 14" Cedar N.30°W. 20.0 ft., now down.
12" Fir N.57°E. 61.0 ft., now stump. (shows scribing.)
New BT's: 20" Cedar N.42°W. 28.8 ft. scribed ¼ S35 CS BT.
7" W.Oak N.57°W. 32.4 ft. scribed ¼ S35 CS BT.
C.S. File No. 52/126

Section Corner to Sections 36 and 35 only, T29-4W. 180
Found - 1" I. Pipe at corner and both BT's. as recorded by Frear, 1918
(See Renewed Cor. No. 3, Vol. 3 for Frear's Corner.) M 1-3
We add "BT" in wood to 48" Cedar S.32°W. 6.0 feet.

South ¼ Corner to Section 36 only, T29-4W. 181
Found - 1" I. Pipe at Corner, 19.8 ft. East of S 2/S 1.
Orig. BT's. are same BT's. as for Secs. 2 and 1.
New BT: 7" Laurel bears N.3°E. 24.9 ft. scribed ¼ S36 CS BT.

Corner to Sections 2 and 1, only. 182
Found - 1" I. Pipe at Corner & BT's. as recorded by Frear, 1918.
New BT: 9" Laurel bears S.3°W. 14.7 ft. scribed S2 T30S R4W CS BT.
11" W.Oak bears S.76°W. 33.5 ft. scribed S2 CS BT. Ren #11

North ¼ Corner to Section 5. 183
Found - 1" I. Pipe at Corner - 20" Laurel S.52°W. 73.0 ft., shows scribing.
S. E. BT., now stump. SEE COR. # 84
New BT: 11" W.Oak bears S.64°E. 88.0 ft. scribed ¼ S5 CS BT.

North ¼ Corner Section 4. 184
Found - 1¼" I. Pipe at Corner. - 8" Laurel S.3°E. 18.5 ft. We rescribed
this BT. ¼ S4 CS BT. - SEE COR. # 151
6" Fir S.26°W. 23.1 ft., shows scribing.

CORNER TO Sections 33 and 34 only, T29 - 4W. 185
Found - 2" I. Pipe at Corner - 16" Laurel N.42°E. 46.5 ft., down, shows scribing.
20" Fir N.72°W. 36.2 ft., shows scribing.
New BT: 9" Laurel bears N.48°E. 41.8 ft. scribed S34 T29S R4W S5 BT.

South ¼ Corner Section 32 only, T29-4W. 186
Found - 2" I. Pipe at Corner & both BT's. recorded by Markham, now down.
Both Original BT's. N.W. BT down.
New BT's: 9" R. Fir bears N.56°W. 7.9 ft. scribed ¼ S32.
12" R. Fir bears N.83°E. 2.5 ft. scribed ¼ S32 CS BT.