


Douglas County Surveyor's Record of  
Government Corners Renewed

T. 30 S. T.S. R. 4 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97101

232  
 $\frac{1}{4}$  Section Corner to Sections 5 and 6.  
 Found - 1" I.Pipe at Corner & Orig. 36", now 42" Laurel N.65°E.  
 (not N.75°W.) 15.8 ft. Renewed Corner No. 75.  
 38" B.Oak N.25°E. 66.0 ft., not N.45°W. 64.0 ft.  
 Fence Corner Thus:




New BT's: 9" R.Fir N.19°E. 27.8 ft. scribed  $\frac{1}{4}$  S5 CS BT.  
 Rescribe Orig., now 42" Laurel N.65°W. 17.0 ft.  $\frac{1}{4}$  S6 CS BT.

234  
 N. W. Corner D. L. C. No. 46.  
 Found - 2 $\frac{1}{2}$ " I.Pipe, 3.5 ft. above surface, & both Orig. BT's.  
 Orig. 12", now down, 24" Laurel S.25°W. 13.2 ft., open & fd. scribng.  
 Orig. 14", now 30" Laurel N.20°E. 12.5 ft., shows scar.  
 New BT's: 12" R.Fir bears S.70°W. 23.8 ft. scribed Cl NW 46 CS BT.  
 10" W.Fir bears South 3.7 feet scribed Cl NW 46 CS BT.

235  
 N. W. Corner D. L. C. Corner No. 47.  
 Found -  $\frac{1}{2}$ " I.P. at Corner (flush) & 24", now down 36" Cedar N.1°W.  
 74.6 ft., shows scars. See Renewal Cor. No. 28.  
 New BT's: 6" Cedar bears N.81°E. 19.9 ft. scribed NW Cl 47 CS BT.  
 5" Cedar bears S.32°E. 35.8 ft. scribed NW Cl 47 CS BT.

Corner Thus:



FOUND SEE M 42-1

236  
 $\frac{1}{4}$  Corner to Sections 5 and 4.  
 Found - 1 $\frac{1}{2}$ " I.Pipe at Corner & Both BT's. as recorded, 1957, Cor. No. 121.  
 S.E. BT. dead. S.W. BT. down.  
 New BT's: 9" Laurel bears S.23°W. 8.5 ft. scribed  $\frac{1}{4}$  S5 CS BT.  
 9" W.Fir bears S.39°E. 25.7 ft. scribed  $\frac{1}{4}$  S4 CS BT.

237  
 $\frac{1}{4}$  Corner to Sections 7 and 8.  
 Found - Orig., now 32" W.Oak N.20°W. 267.3 ft. We open & find good scribng.  
 Part of Shell & remains of Orig. BT. to East. Find bearing  
 should be S.65°E. 83.8 ft., not N.65°E. 83.8 ft., as it  
 would then check record bear. & dist. to N.W. BT. See Cor.#112.  
 John Markham's  $\frac{1}{4}$  Cor. 7/8 bears South 65.4 ft.  
 Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1963  
 $\frac{1}{4}$  S7/S8 T30S R4W.  
 New BT's: 6" R.Fir bears S.12°E. 18.8 ft. scribed  $\frac{1}{4}$  S8 CS BT.  
 12" B.Oak bears S.36°W. 24.4 ft. scribed  $\frac{1}{4}$  S7 CS BT.

238  
 S. E. Corner D. L. C. No. 48.  
 Found - 1" I.P. at Cor. & both BT's. as recorded by Wenderoth, 1945.  
 S.W. BT., now dead (partly) (See Cor. No. 68)  
 8" W.O. N.3°W. 46.2 ft. is O.K.  
 New BT: 7" R.Fir bears N.68°W. 20.3 ft. scribed SE DLC 48 CS BT.  
 Note - N. S. Fence 10 ft. West.

239  
~~N. E. Corner D. L. C. No. 47.~~ (Should Be: N.W. Cor. DLC No. 48)  
 Found -  $\frac{1}{2}$ " I.P. at corner 6.0 ft. East of N.-S. fence. See Ren.#262  
 24", now 24" B.Oak Snag S.78°E., not S.48°E. 17.8 ft., shows  
 faint scribng. Find Laurel Stump Hole that checks for SW.BT.  
 New BT's: 20" R.Fir bears S.75°W. 41.6 ft. scribed NE Cl 47 CS BT.  
 6" Laurel bears S.17°E. 14.2 ft. scribed NE Cl 47 CS BT.

240  
 N. W. Corner D. L. C. No. 49.  
 Found - All BT's. as recorded, See Corner No. 109.  
 10", now 14" Cedar N.44°E. 23.6 ft., shows scribng.  
 8"; Fir, S.77°W. 19.2 ft., shows scribng.  
 18" Fir Stump S.65°W. 6.5 ft., shows scar. Corner Pipe not found.  
 Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1963  
 N.W. DLC 49 T30S R4W

James W. Byron, Deputy County Surveyor  
 Mike Darby and Wm. Stoffel.  
 August 1963 C. S. FILE No. 53/26

Ren # 4