

Douglas County Surveyor's Record of
Government Corners Renewed

T. 30 S. T. S. R. 4 W R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

James W. Byron
& Crew
Jan. 22, 1964
C. S. File
No. 53/26

S. E. Corner D. L. C. No. 44. 255
Found - Stone At Corner, checks record. (See Ren. Cor. No. 40)
Find O. BT., 30" Down Oak N.89°W. 427.7 ft., shows old face,
and axe work, no scribing found.
Note - Corner checks call to ravine 2 chains north.
Set - Brass Cap at Corner Mkd: S.E. DLC 44 T30S R4W County Surveyor's
Office, 1964
New BT's: 18" W.Oak bears S.5°W. 18.8 ft. scribed SE ~~CK~~ 44 CS BT.
10" W.Oak bears S.21°E. 18.5 ft. scribed SE DLC 44 CS BT.

John H.
Markham, Jr.
Wit:
G. Vaughn
1951

Corner for Townships 29 & 30, South, Ranges 4 & 5 West. 256
All old BT's. standing & in good shape, as follows:
12" Cedar N. 75° E. 1.5 ft. - 15" Cedar N. 17° W. 12.0 ft.
16" Cedar S. 76° W. 23.0 ft. - 24" Cedar S. 66° E. 41.0 ft.
At Corner Point found Wood Post & Set - 1" x 30" Iron Pipe.
New BT's: 48" Fir bears S. 80° E. 9.5 ft. Mkd: T30S R4W S6 BT.
South 1/4 Corner Section 31 bears N. 76° 30' E. 700.0 ft.

John M. Powell
Frank Jones & J. Brady
February 1966
C. S. File No. 54/20

Sec. Cor. to Secs. 3 & 2 only, T31-4W. 257
Found - I. Rod at Cor., See Ren. #58, T31-4W.
Orig.-20" Fir, now 25", S. 14° W. 44.2 ft., shows scar.
9" Laurel, now down, N. 50° E. 43.0 ft.
7" Laurel, now 9", N. 64° E. 38.4 ft., bark scribed
7" Chinquapin, now down, S. 63° E. 43.5 ft.
14" Chinquapin, now 16", S. 73° W. 37.5 ft., scribe visible.
Set - Brass Cap at Cor. Mkd: County Surveyor's S 34 T30S
(Alongside I.Rod) Office, 1966 R4W S 3/S 2 T31S
Rescribed: 9" Laurel N. 64° E. 38.4 ft. scribed T30S R4W S34 CS BT.

Sec. Cor. To Sections 34 & 35 only, T30-4W. 258
Found - Iron Pipe, See Ren. #146. Fd. B.C. 8/81
7" Fir N. 21° E. 13.7 ft., shows good scars. BLM Admin. Survey
27" Cedar S. 40° W. 18.4 ft., scribe visible "S2". See GIS File
9" Laurel S. 61° E. 28.2 ft., bark scribed "S2 R31S R4W BT".
Set - Brass Cap at Cor.Mkd: County Surveyor's T30S S 34 / S 35
(Alongside I.P.) Office, 1966 T31S R4W S 2
Rescribed: 9" Laurel S. 61° E. 28.2 ft. scribed
"T31S R4W S 2 CS BT".

J. M. Powell
12/10/71
C.S. 53/26

1/4 Corner, Sections 31, 32. 259
Found - Stone, mkd. 1/4 chipped off. Rock in ground approx right size.
Burnt roots of maple, S.52°W., 20.1 ft.
No trace of NE BT.
Note - Call of 5.50 chains hits good by pacing. I do not agree with
survey M21 - 33 and rec. dist. 497.6 ft. I chain both ways
for 562.0 ft. Old axe work on tree north of cor. 1/4 chopped
in bark, also squared post by rock.
Set - Brass cap at 1/4 cor. mkd: County Surveyors T 30 S R 4 W
Office 1/4 S31 | S32
1971
Replaced corner stone along side brass cap.
New BT's- 50" D. Fir, S.6°E., 26.5 ft. 1/4 S32 CS BT (bark scribed).
14" D. fir, N.53°W., 16.0 ft. scribed 1/4 S31 CS BT.

J. M. Powell
& J. Heritage
2/17/72
C.S. 53/26

Closing Corner to Sections 3 & 2, T30-4W. 12/10/71
Found - Co.Surveyor's Brass Cap, 1956 (No record)
12" Cedar BT mkd. by J. Markham, S.8°W. 66.5', shows scar.
No trace of Orig. BT's. nor I.P. set by Markham. ren#92.
Mkd.New BT: 8" W.Oak S.55°E. 64.5 ft. mkd:"T30SR4W S2 CC CS BT.
This corner lies S.86°W. 168.0 ft. of Sec. Cor. S35 &, as
notes, corner lies on west edge of upper road. 260

2/17/72