

Douglas County Surveyor's Record of  
Government Corners Renewed

30 T. S. 4 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

265

Debbie L. Stewart, Surveyor's Office  
G. Langlitz  
A. Cangie, G. Quibell  
April 21, 1976  
C.S. 59/8

S.E. Corner DLC #50  
Found - 1 1/2" I.P. and probable remains of a 4" stake set by F.C. Frear  
Deputy Co. Surveyor. Ren. #9  
No trace of orig. bearing tree.

From which:

A windblown Fir, 12" bears S.56°E., 4.6 ft. We open to find visible  
scribe "CS 50 BT". Ren. #9

The probable remains of a NW BT also down, 10". Its root wad bears  
N.88 1/4°W., 7.6 ft. Ren. #9. We do not unearth, blaze is buried  
face down, and we do not open.

Set - A 1" x 30" I.P. with brass cap stamped County Surveyors Office  
T 30 S R 4 W  
S.E. | D.L.C.  
Cor. | 50

with the fd. 1 1/2" I.P. on the west side of brass cap. 1976

From which: New BT's

12" D. Fir bears N.3 1/2°W., 44.8 ft. scribed "SE DLC 50 CS BT"  
in double blaze.

6" Madrone bears N.62°W., 3.5 ft. scribed "SE DLC 50 CS BT" in  
double blaze.

4/21/76

266

1/4 Corner for Secs. 34 and 35.

Found - A 1" x 30" I. Pipe. (Rec. calls for 3/4" x 30" I. Rod) Ren. #144-A  
A 12" now 16" Fir bears S.42°E., 24.0 ft. Tree alive with "35"  
visible in pitched over scar.

A 12" now 22" Fir bears S.74°W., 21.0 ft. Tree alive with well  
healed blaze.

A 7" now 9" Laurel bears N.43°W., 13.6 ft. Tree is alive with "1/4  
S34 BT" visible bark scribe.

Set - At true corner point: A 1" x 36" I. Pipe with Brass cap stamped:  
"Douglas County Surveyor"

T 30 S R 4 W

S 34 S 35

1/4

1976

Placed 1" I. Pipe on North side of cap.

Did not mark new trees.

Note: To reach corner go approx. 1000 ft. West of Rd. #30-4-22.0 to SE  
Cor. Sec. 34 than North 253.0 ft. to 1/4 Cor. which lies in North-  
South cutting line.

6/10/76

267

1/4 Corner for Secs. 3 and 10.

Found - 1" Iron rod 6" above ground and bent over. Ren. #128

6" now 16" W. Oak bears N.32°W., 50.8 ft. with rotted out blaze  
and Stomar Lmbr. Co. tag (O.B.T. use to set brass cap).

A 14" B. Oak bears N.79°W., 55.5 ft. with well healed double blaze.

A 15" Madrone bears N.42°W., 87.6 ft. (Ren. #128, 86.7 ft. good to  
face). Tree is triple trunked, measured to south fork with visible  
scribing on almost healed single blaze.

A 8" now 10" W. Oak bears N.38°E., 81.0 ft. with a well healed  
double blaze.

Set - A 1" x 36" I.P. with brass cap 5" above ground marked:  
"Douglas County Surveyor" 1977

T 30 S R 4 W

1/4

S 3

S 10

Set - A steel fence post 7" S.E. of brass cap and a wooden lath with  
flagging 1.0 ft. N. W. and a 14" x 8" x 10" boulder at west side.

Note: An east-west fence bears North 38 ft. Corner is on North edge of  
cultivated field.

10/6/77

M. Lenora Ladig, Surveyors Office  
Pete L. Earle  
June 10, 1976  
C.S. 59/15

R. B. Kimberling  
M. W. Cline  
Doug. Co.  
Surveyors Office  
C.S. 59/40