

Douglas County Surveyor's Record of
Government Corners Renewed

30

T. S.

5

R. W. W. M.

M. B. Germond
F. C. Frear
Wit. Jim Wolford
Hank Weaver
Gene Richardson
John Dick
Sept. 17-1942
May 1917.

M. B. Germond
F. C. Frear
Wit. Hank Weaver
May 1917.

M. B. Germond
F. C. Frear
Wit. Hank Weaver
May 1917.

M. B. Germond
F. C. Frear
Wit. Hank Weaver
May 1917.

F. C. Frear Dep.
Ion Hawkins
J. W. Hanks
Feb. 18, 1918.

✓ 1/4 CORNER BET. SECS. 19 & 20

Rifle Barrel from which ~~Renew~~
A B. Oak 24" bears N. 69° E. 46.5 Ft.
A B. Oak 30" " S. 14 1/2° W. 72.0 Ft. Old trees
A W. Oak 12" " West 11.3 Ft.
A Pine 12" " N. 33° E. 24.8 Ft. New trees

36

SEE CORNER NO. 161

✓ SECTION CORNER BETWEEN SECTIONS 4 and 5.

I find one old bearing tree and set in a new corner
which is a 3/4" x 24" Gal. Iron Pipe from which
A White Oak 5" dia. bears S. 15° 30' E., 23 2/3 lks.
A White Oak 13" dia. bears S. 46° 18' W., 272.6 lks.

37

SEE CORNER NO. 246

✓ SECTION CORNER COMMON TO SECTIONS 4, 5, 8 and 9.

I reset this corner from testimony of Hank Weaver
and John Dicks as well as from B.T.s set in by Oscar Thiel.
I renew corner with a 3/4" x 30" Gal. Iron Pipe, from which
A White Oak 6" dia. bears N. 42° 10' E., .065 chs.
A White Oak 12" dia. bears N. 26° 50' W., .105 chs.
A White Oak 7" dia. bears S. 9° 25' E., .035 chs.
I also note that the stump of the trees marked by O. Thiel
bears as follows.
A White Oak stump bears S. 16° 20' E., 91 2/3 lks.
A White Oak stump bears S. 40° 20' W., 50 lks.

38

SEE CORNER NO. 148

✓ SECTION CORNER COMMON TO SECTIONS 6, and 7.

I reset this corner from one old original bearing tree
which I find plainly marked. New corner is a 1" x 30"
Iron Bolt and 12" x 15" x 8" stone from which
A White Oak 14" dia. bears S. 39° 10' W., 4.07 chs.
A White Oak 12" dia. bears S. 10° 10' E., 3.64 chs.
A Black Oak 10" dia. bears N. 61° 45' W., 3.25 chs.
A Black Oak 24" dia. bears N. 30° 00' W., 3.94 chs. old B.T.

39

SEE ALSO #28

✓ SECTION CORNER COMMON TO SECTIONS 5, 6, 7 and 8.

I set this corner in by proportional measurements. New
corner is 1" x 48" Buggy Axle set 10" deep in the ground,
from which a 3" Cedar stake bears N. 45° E., 58 ft.,
Cedar stake is set in mound of stone
A 3" Cedar stake bears S. 45° E., 58 ft.

40

SEE CORNER NO. 200

✓ 1/4 CORNER BETWEEN SECTIONS 5 and 6.

This corner is set on true line between section corners
and at proportional distances. New corner is a 1" x 36"
Gal. Iron Pipe from which
A Dago Prune tree 10" dia. bears N. 36° W., 9.0 ft.
A Dago Prune tree 10" dia. bears S. 22 1/2° W., 11.5 ft.

41

✓ 1/4 CORNER BETWEEN SECTIONS 5 and 8.

This corner is set on true line between section corners
and at midway point. New corner is 1" x 60" Buggy Axle,
from which
A Red Fir 24" dia. bears S. 48 1/2° E., 23.3 ft.
A Red Fir 24" dia. bears N. 65 1/2° W., 43.0 ft.

42

SEE CORNER NO. 152

✓ CORNER OF SECTIONS 13, 14, 23 and 24.

Renew from old B.T.s. Set in a 1/2" x 2" x 16" Iron bar,
from which
All old original B.T.s bear as given and all plainly
remarked.

43

SEE CORNER NO. 144