

County Surveyor's Record, Douglas County, Oregon

T 30 S, R 5 W, W. M.

CHAINS

1/4 SEC. COR. 7-18

64

Set 1" x 36" iron pipe with brass cap, 2' underground, mkd. County Surveyors Office 1/4 cor. S 7 S 18. Marked B. T's.

12" Oak, N 56° W 24.3 ft, mkd. 1/4 S 7 CS BT.
24" Oak, S 35° E 72.0 ft, mkd. 1/4 S 18 CS BT.

203

S EC. COR. 7-18 *Ramp line*

65

Set 1" G. iron pipe with brass cap mkd. Co. Surveyors Office, S 7/18 T 30 S, R 5 W. Set 2" underground. Marked B. T.

28" Oak, N 25° W 149.5 mkd. S 13, T 30 S, R 6 W.
12" Bull Pine, S 56 1/2° E 68.5 ft., mkd. S 18, T 30 S, R 5 W.
Both CS BT.

DLC #43, EXT. L COR.

66

Reset from original B.T., Red Oak 4 1/2" diam., bearing N 10° E 62.0 ft.

Set 3/4" I.P. with brass cap marked Cnty. Surv. Office, Ext "L", DLC. No. 43 T 30 S, R 5 W. Marked new B. T's.

18" Fir S 75° W 26.8 ft. marked Ext. L, DLC #43 C.S. B T.
R.E. 2741
10" Fir, N 32° E 16.0 ft. marked Ext. L DLC #43 C.S. B.T.
R. E. 2741.

SEC. COR. 19-20-30-29

67

1 O. B. T. alive and standing, 30" Laurel N 5° W 27.7 ft.
Found stake set by State, Hwy. crew, checks for recorded bearing and distance. Use as temp. Cor. Reset Cor.

Set 1" G. I. P. with brass cap marked County Surveyor's Office
19/20 T 30 S, R 5 W. Scribed new B. T's.

30/29
20" Fir N 19° E 5.0 ft. mkd. S 20, T 30 S, R 5 W, CS. BT.
R.E. 2741
18" Fir S 52 1/2° E 10.4 ft. mkd. S 29 T 30 S, R 5 W, CS. BT.
R.E. 2741
20" Fir N 22° W, 22.2 ft. mkd. S 19 T 30 S, R 5 W, CS. BT.
R.E. 2741
18" Maple S 28 1/2° W 70.1 ft. mkd. S 30, T 30 S, R 5 W CS. BT.
R. E. 2741.

N. W. COR. DLC # 58 - N. E. COR. DLC #59

68

Set by measurement and old land marks, from SW. Cor. DLC #51 and SE Cor. DLC #51.

Drive 1" Iron Pipe for corner. *SEE COR. NO. 120*
Scribe 72" Maple S 44° 04' W 346.6 ft.
14" Oak S 29° 40' E 432.6 ft.

S. E. CORNER DLC #51

69

Set from measurement from SW Cor and Interior "L" Corner

Drive 1" Iron Pipe for corner.
Scribe 10" Twin W. Oak N 55° E 183.0 ft.
12" Maple N 85° 15' E 109.9 ft.

INTERIOR "L" CORNER DLC #51

70

Found Old B. T., 16" Madrone N 40° W 59.4 ft., dead and rotten.

Drive 1 1/2" Iron Pipe for corner.
Scribe 8" W. Oak S 50° 25' E 27.9 ft.
10" W. Oak S 30° W 36.2 ft.

*FD I.P. 10/85
BY BAUMANN
1993-0028
0180 or 93 M117-19*
*NO. 58
M10227
7/86
Dis. 1/20*

N. W. CORNER J. ROBERTS DLC #59

71

Set by measurement from SW and SE Cor. DLC #51.

Drive 1" Iron Bolt for corner
Scribe 14" Fir N 4° 30' E 41.1 ft.
12" Madrone S 80° 30' W 18.0 ft.

238

Richardson - Dep. Cnty. Surv.
Evans - Witness
May 1948 *Filed 39/171*

Surveyor
A. R. Evans
June 11, 1948
Witnesses
Kershner and Godfrey

George J. Wenderoth - Dep'ty. Surv.
Frank Ioso
Charles Leiser - Witnesses
May 1949
M 21-79