

Douglas County Surveyor's Record of  
Government Corners Renewed

30 T. S. 5 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97196

Sec. 27-28-33 and 34.  
July 13, 1900

**SEE CORNER NO. 154**

72

Set W. Oak post 4 x 4 inches square 3 1/2 ft. long.  
from which B. Oak 8 in. diam bears N. 18° E 26 lks..  
Fir 8 inches in diam bears N 57° W 49 lks.  
Laurel 6 inches in diam. bears S 80 1/2° W 55 lks.  
Laurel 6 inches in diam, bears S 69 1/2° E 35 lks.  
In presence of Jasper, Yokum and H Hodges. The old  
B.T. had been cut down, stump standing.

(SEE ALSO  
F.B. 60 Pa. 2)  
1912 INFO.

Mar. 17, 1937:

The fir and the two Laurels shown above as B T's for Sec. Cor.  
27-28-33 and 34 have all been rotted out and destroyed.

A 2" iron pipe was set from the high stump of an 18" b. Oak,  
an original B T. which bears N 18° E 26 lks and from above, 2"  
pipe, A 14" Fir was set for B T N 1° W 58.5', ← F.O. 5/25/77 c.s. 59/34  
A 14" Fir S 4° W 43.8' and a tree S 74° W. 82'.

N.E. Cor. C1 48

Set post marked New B. T. Old B. T. stump remaining.

B. Oak 12"- S 49 W 69 lks.

- SEE REN. # 129

73

Briggs

N. W. Cor. C 1 48 set post marked New B.T.

**RE-RENEWED, SEE CORNER NO. 252**

74

B. Oak 8" S 75° E 68 lks  
Briggs

NW COR. DLC #44

**SEE CORNER NO. 198**

75

Set from NE Cor, Found.  
Set 1" I.P., 40" long from which  
5" Fir bears S 66° W 8.5 ft., mkd. Cl. 44, 2880, BT  
19" Fir bears S 78° e 33.5 ft., mkd. Cl. 44, 2880, BT.

N NE COR. A. J. TILLER DLC # 63

Set axle with gear attached at proper distance

O. B. T's. still standing

24" B. Oak N 86° W 32 lks. (36")

10" W. Oak S 20° W 37 lks. (20")

FD. OK 4/15/78  
J.H.M. Jr. 58/168  
c.s.

76

SEC. COR. 28-29-32-33

Determined from remains of O. B. T.

B. O. 23" diam., East 7.3 ft. rescribe S 33 2880 B.T.

W. O. 27" diam., S 55° W 49.5 ft. rescribe S 32 2880 B.T.

A stump hole N 55° W 34.0 ft. dist. At corner point found pile of  
rock and drove a 3/4" x 24" iron pipe 20 inches in ground from which

W. O. 14" diam., bears N 68° W 107.0 ft. mkd. S 29 2880 B.T.

There is a fence running N & S from this cor. The road is 141.0 ft.  
South of this corner.

211

77

1/4 SEC. COR. 28-33

Determined from remains of O. B. T.

W. O. stump S 25° E 60.0 ft., scribe still legible

At corner point set 1/2" x 24" iron pipe 18" in ground from which

Fir 17" diam. bears N 80° E 17.5 ft. mkd. 1/4 S S28 2880 B.T.

Laurel 11" diam., bears S 51° W 98.0 ft. mkd. 1/4 S S33 2880 B.T.

The fence corner is 16.2 ft. South of 1/4 cor. There are fences  
running N-S-E-W from this corner.

218

78

Surv. John H. Markham, Jr.  
Set - April 1949  
Surv-Evans Smith  
Farrell See File 40/189  
Witness

Jan. 1949  
M/F 76 - c.s. 19/8

John Markham Jr. - Surveyor  
Bollenbaugh) Witnesses  
Proctor

11-11-49  
C.S. 40/213

(SEE ALSO  
F.B. 60  
Pg. 2)