

Douglas County Surveyor's Record of
Government Corners Renewed

30 T. S. 5 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97196

NE CORNER DLC # 62, Wm. P. Preston 79
Determined from remains of O. B. T., a stump hole bearing S 35° W
60 lks. (record course and dist. S 30° W 70 lks.)
At corner pt. found 1/2" I. P. and mound of rocks, from which
11" W. Oak bears S 7° W 35.0 ft. mkd. CL. 62, 2880 B T.
19" W. Oak bears N 6° E 141.0 ft. dist. mkd. CL. 62 2880 B T.

John Markham - Surv.
Vaughn) Wlt.
Pickett)
M 42-15
12/3/49
c.s. 40/257

1/4 SECTION CORNER 2 SECS. 29 & 30 80
Determined from remains of O. B. T.
A B. Oak 24" diam. bears N 75° E 26.4 ft. dist., this O.B.T., I
rescribe 1/4 S S 29 B.T.
A B. Oak stump bears N 2 1/2° W 26.0 ft. dist.
At Cor. pt. set 2" x 2" oak post, from which
A La. 8" diam. bears N 32° W 7.0 ft. dist. mkd. 1/4 S S30 2880, B.T.
This is a fence running North, South and East from this corner.

John Markham - Surv.
G. Vaughan & W. Vaughan
Witnesses
April 23, 1950

1/4 SECTION CORNER - SECS. 29 & 32 81
Determined from remains of original B.T.
A fir 30" diam. bears S 60° W 55.4 ft. dist., scribe legible.
At corner pt. I set 1" x 30" I. P. 24" in ground - from which
A La. 8" diam. bears N 18° W 18.5 ft. dist. mkd. 1/4 S S29 2880 B.T.

SEE CORNER NO. 132

CENTER OF SEC. 19 - T 30S R 5W 82
I find iron pin gone.
Reset 3/4" x 36" iron bolt, from which
Old Oak BT N 68 1/2° E 103 ft. (was N 78° E)
Pine BT S 79° E 75 ft. O.K.

NOTE:
THIS APPROXES
TO BE APPROVED BY
RENEWED FROM IMPROVED
1/4 SET BY THE SURVEYOR
(RECORD V. 3 P. 145) SEE
G.S. 40/258
MAY 1981
M 87-22

Floyd Frear - Surv.
Andy Andrews
Leo Kershner
Glen Baughman
Witnesses
June 29, 1950
c.s. 40/258

1 SECTION CORNER 28 - 29
SEG. COR. SEC. 25-36 East Boundary T 30 S, R 6 W 83
Setp per field notes
At a point 92.5 ft. North of closing corner 30 - 31, T 30 S, R 5 W
Set 1 1/2" x 30" iron pipe 15" in ground, from which
Old B.T. bears S 74° E, 42.0 ft. distant
Old B.T. bears N 63° E, 70.0 ft. distant
A B. O. 6" diam. bears S 74° W, 10.0 ft. distant marked S 36,
2880, B.T.
A W. O. 8" diam. bears N 44° W, 29.0 ft. distant marked S 25,
2880, B.T.

John Markham, Jr.
Geo. Vaughn - Witness
September 5, 1950
c.s. 40/277

S.W. COR. WEAVER DLC 37 84
Old bearing tree down. Set post from which mark new bearing tree
B. Oak 24 in. dia. N 25° E 346 lks.
Briggs - April 15, 1890

Vol. 1 P. 144

1/4 SECTION CORNER 28 - 29 85
At corner point found stone and drove 1" x 24" I.P.
Both O.B.T. dead, one down, from which
A Fir 16" diam. bears N 13° E, 5.0 ft. dist. marked 1/4 S, B.T.
A Fir, 8" diam. bears N 40° W, 36.0 ft. dist. marked 1/4 S 29, B.T.

John H. Markham, Jr.
Engineer
Witnesses:
W. E. Markham
Feb. 15, 1951

S.E. CORNER N.P. BRIGGS, DLC 46 86
Determined by O.B.T.
A B. Oak snag bears N 5° E, 10.5 ft. dist. - all scribes showing
At corner point found stone and set 1" x 24" I.P., from which
A Fir 6" diam. bears S 4° E, 24.5 ft. dist. marked CL.46, B.T.
A B. Oak 11" diam. bears N 13° E, 56.0 ft. dist. marked CL.46

1/4 SECTION CORNER 2 and 3 87
A Fir 20 ins. diam. bears N 42° 30' W, 13.2 ft. dist., I rescribe
this O. B. T.
A B. O. windfall bears N 39° 30' E, 12.0 ft. dist. - scribe showing
At corner point set 1" x 24" iron pipe, from which
A Fir 1 1/4 ins. diam., bears S 47° E, 5.0 ft. dist. marked 1/4 S 2, T 30 S,
R 5 W, 2880, B. T.

John Markham, Jr.
Engineer
April 4, 1951