

Douglas County Surveyor's Record of
Government Corners Renewed

30 T. S. 5 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97190

John H. Markham, Jr. - Eng.
Geo. & Wm. Vaughn - Witrn.
April 22, 1951

NORTH 1/4 SEC. COR. 3 - Never set by government CS 40/259 88
At midpoint on township line set 1" x 30" iron pipe, from which
A Maple 20 in. diam. bears S 83° E, 51.0 ft. dist. marked 1/4 S 3 B.T.

N.W. COR. SEC. 2
At corner point drove 1" x 30" truck axle in original stone monument, ~~88-A~~
from which
A Fir 5 in. diam. bears S 87° E 23.2 ft. dist. marked S 2, T 30 S,
R 5 W, B.T.
An Oak 6 in. diam. bears S 29° W 18.7 ft. dist. marked S 3, 2880, B.T.

N.E. COR. SEC. 4 89
Determined by O.B.T. - A Fir 60 in. diam. bears S 45° E 56.0 ft. dist. O.B.T.
A Laurel 26 in. diam. bears N 10° W 21.0 ft. dist. O.B.T.; I remark
S 34, T 29 S, R 5 W, B.T.
At corner point set 1" x 30" iron pipe, from which
A Fir 10 in. diam. bears S 41° W, 8.0 ft. dist. marked S 4, 2880, B.T.
see CS 7/4 for more info

CORNER FOR TOWNSHIPS 29S & 30S, Ranges 4 & 5 West
Refer to T 29 S, R 4 W

NW CORNER OF LOT 6, SECTION 28, (as set 132.01 E., of the SW corner ^{not 1/4 of section}
D.L.C. 50) Cor. see Survey notes
At the corner point set 1" x 30" Iron Pipe from which
A Fir 16" diameter bears N 79° E, 12.6' distant marked Lot 6 B.T.
A White Oak 7" diameter bears N 78° W, 24.8' distant marked
Lot 6, B.T.

S.W. CORNER D.L.C. 50 (determined by renewed notes) 90
A Black Oak 36" diameter bears N 72° E, 116.8' distant. I remarked
this O.B.T. Cl. 50 - REN #3 235
At corner point set 1" x 30" Iron Pipe from which
A White Oak 10" diameter bears N 38° E, 58.8' distant marked Cl. 50
B.T.

CORNER FOR SECTIONS 22 - 23 - 26 and 27. 91

Found - 24" Fir, S 73° W. 115.8 feet
30" Pine, N 63° 50' W. 52.8 feet

Drive car axle for corner. REN. #8
Scribe 30" Pine, N 23° 25' W. 105 feet. SEE CORNER NO. 192

1/4 Corner Section bet. Section 1 and 12.

NORTHWEST CORNER D.L.C. NO. 62 PRESTON 92

442.2 feet South and 151.2 feet west of corner 22, 23, 26 and 27 763
Drive 1 1/4" I. Pipe for corner.

14" Double White Oak, N 68° 35' W. 34.7 feet (see also REN. #10)
12" Alder, N 52° 23' E. 44.3 feet

East 1/4 Cor. Sec. 24 93
as determined by O. B. T.
A W. Oak stump 22" diam. bears N 51 1/2° W, 86.0' fd. scribe
A B. Oak 30" diam. bears S 55° E, 30'. I remarked this O.B.T.
1/2 S 519 B.T.
At the corner set 1/2" x 30" Iron Pipe from which.
A W. Oak 7" diam. bears N 23° W, 23.0' dist. mk'd. 4524 B.T. 172
This corner lies on West bank of Creek & about 40' South of
South edge of C. O. P. Co. R/W
There is a fence running N. & S. about 20' W. of Cor.

John H. Markham, Jr.
Engineer
Witn. Geo. Vaughn
July 24, 1951

Geo. Wenderoth
Wit: Geo. Leider
June 1951.

Geo. Wenderoth
Wit: Chas. Leiser
June 1951
C.S. FILE 41/18

John H. Markham Jr.
Wit: D. I. Combs
11/6/52
drawer 48/
envelope 80