

Douglas County Surveyor's Record of
Government Corners Renewed

30 T. S. 5 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

A. R. Evans, Deputy County
Surveyor
July, August, 1951.
C. S. File No. 45/69.

$\frac{1}{4}$ corner to ~~sec. 12, T30S, R5W.,~~ and Sec. 7, T30S; R4W. *ONLY*
Set $\frac{5}{8}$ inch Iron rod by proportional measurement.
Blazed and scribed:
20" Fir, N.40°E., 23.2 feet mkd. $\frac{1}{4}$ S 7 - T 30, R 4, R.E. 2741-CSBT.
14" Fir, N.29°W., 23.0 feet, mkd. $\frac{1}{4}$ S 12, T 30; R 5, R.E. 2741-CSBT.

117

Center $\frac{1}{4}$ corner of Sec. 12.
Set $\frac{1}{2}$ inch Iron Pipe.
Blazed and Scribed:
8" Cedar, S.70°W., 10.4 feet.
8" Cedar, S.85°E., 20.7 feet.
Both marked C $\frac{1}{4}$ S - 12 (Agr) C. S. B. T.

118

George Wenderoth,
Dep. Co. Surv.
June 5, 1956.
C. S. File
No. 47/88.

S. E. Corner of The Joseph Roberts D. L. C. No. 59.
Found a $\frac{3}{4}$ inch iron pipe and 24 inch Alder, S.6°E., 47.5 feet. *REN.#5*
Mark:
A 12 inch Ash, N.46°08'W., 51.5 feet.

119

James W. Byron
July 30, 1954.
C. S. File
No. 45/119

Northwest Corner D. L. C. No. 58. (N. E. cor. of D. L. C. 59.)
Found corner as described in renewed notes. #68
At corner point set iron pipe with brass cap.

120

FD OK 8/6/79 L. MANCINI, Co Surveyor Office C.S. 60/54 *6 MAR 10 7/81 M106-10*

$\frac{1}{4}$ corner to secs. 26 and 27.
Corner set $\frac{1}{2}$ way between section corners.
 $\frac{3}{4}$ inch I. Pipe at corner,
From which:
20 inch Madrona, N.50°43'W., 42.5 feet.
12 inch Fir, N.6°16'E., 30.0 feet.

121

George Wenderoth
1953 - 4.
C. S. File No. 41/18.
1953-54

Southwest corner of the W. Preston D.L.C. No. 62.
I. Rod at corner point. *REN #9*
From which:
12 inch Fir, S.25°E., 6.0 feet. *SEE Vol. 3 Pg. 107*
18 inch W. Oak, N.70°E., 33.0 feet.

122

FD OK 7/91 R. BROWN M115-63

Section corner to secs. 26, 27, 34 and 35.
 $\frac{1}{2}$ inch I. Pipe at corner point. *SEE Vol. 3 Pg. 107 REN #6*
From which:
24 inch Fir, N.87°40'E., 68.5 feet.
14 inch W. Oak, S.60°30'W., 63.0 feet.
36 inch B. Oak, S.78°30'E., 33.3 feet.
24 inch B. Oak, N.78°45'W., 54.6 feet.

123

George J. Wenderoth
April 3, 1957
C. S. File
No. 47/170.

Section corner to secs. 16, 17, 20 and 21.
Found B. T., a 30 inch B. Oak, S.47°E., 456.7 feet, uprooted and rotten-scribe marks found.
Drive 1 inch iron pipe.
Scribe: 16 inch B. Oak, S.83°12'E., 417.6 feet.
12 inch Madrone, N.56°35'E., 601.7 feet.

124