

Douglas County Surveyor's Record of
Government Corners Renewed

30 T. S. 5 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21891

$\frac{1}{2}$ corner to sec. 36, T30S, R5W., and sec. 31, T30S, R4W. 125
Found original Fir BT, now 48 inches, S.29°W., 50.8 feet, alive and in good condition. I open and find good scribing ($\frac{1}{2}$ S). The original 18 inch Laurel, N.40°E., is rotted-no scribing found. Both BTs check for bearing and distance.

Set an iron pipe with brass cap at corner marked:

$\frac{1}{2}$ S
36 | 31 T 30 S County Surveyor's
R5W | R4W Office, 1957

From which:

10 inch Cedar bears S.60°E., 19.4 feet scribed $\frac{1}{2}$ S 31 CS.BT.
Bark scribed original 48 inch Fir, S.29°W.; 50.8 feet scribed $\frac{1}{2}$ S 36 CS BT. Bark scribing just above old face.

Closing corner to sec. 36, T30S, R5W., and sec. 1, T31S, R5W. 126
Found remains of old BTs to Northeast and Southeast badly rotted but scribe marks plainly visible. Clump of Laurel saplings & depression in ground showing location of old tree fit for bearing and distance to Laurel B.T. in Southwest quadrant.

Set an iron pipe (1 inch) with brass cap for corner stamped:

County Surveyor's
T30S R5W | T31S R4W
36

T31S | 1
1957
Office

From which:

12 inch Fir, S.18°E., 18.9 feet, mkd. T31S R4W S6 CS BT.
12 inch Fir, N.3°W., 28.2 feet, mkd. T30S R5W S36 CS BT.
6 inch Live Oak, S.29°W., 33.0 feet, mkd. T31S R5W S1 CS BT.

Southwest corner of Clark DLC No. 51. 127
Found a 1 $\frac{1}{2}$ inch iron pipe and 26 inch Fir as renewed by Wenderoth in 1945.
Madr. gone. Ren. #57
I scribe a 12 inch Madrone, S.65°53'E., 54.1 feet. 237

Most Westerly S.W. corner of the Samuel Gazley D. L. C. No. 49. 128
Axle shaft,
from which: Renewed, see corner no. 187
46 inch B. Oak, N.58°35'W., 43.5 feet.

N. E. corner of the James F. Gazley D. L. C. No. 48 and Interior L corner of the Samuel Gazley D. L. C. No. 49. 129
1 inch iron pipe, Ren #73
from which:
30 inch B. Oak, N.82°12'W., 33.0 feet.
24 inch B. Oak, N.39°04'E., 29.6 feet.
6

S. E. corner of the James F. Gazley D.L.C. No. 48 and the most Southerly S. W. corner of the Samuel Gazley D.L.C. No. 49. 130
Car Axle,
from which: Renewed, see corner no. 255
30 inch B. Oak, N.1°25'W., 319.2 feet.
Maple Stump, N.51°54'E., 98.8 feet. SEE REN # 109

S. E. corner of the Samuel Gazley D.L.C. No. 49. 131
1 inch iron pipe, SEE #17
from which: Renewed, see corner no. 191
40 inch Pine, N.38°45'W., 481.9 feet.
8 inch Maple, N.72°W., 142.8 feet.

County Surveyor's Office
April 11, 1957.
C. S. File No. 47/175.

R. M. Thompson
June 7, 1957
C. S. File
No. 42/280.

George J. Wenderoth
1954
C. S. File No. 45/137.