

Douglas County Surveyor's Record of
Government Corners Renewed

30 T. S. 5 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97196

James W. Byron
M. Godfrey
S. Bilow
Dec. 5, 1957
C.S. File No. 46/64

$\frac{1}{4}$ Section Corner to Section 29 & 32. 132
Found - 1" I. P. at Corner. *SEE CORNER NO. 208*
The 30" Fir S.60°W. 55.4 ft. is low cut stump now, No Scribing.
Checks bearing & distance.
The 10" Madrona N.12°16'W. 18.7 ft. now dead. Checks bearing & dist.
New BTs: 18" R. Fir bears S.24°E. 10.2 ft. scribed $\frac{1}{4}$ S32 CS BT.
13" R. Fir bears N.51°E. 8.2 ft. scribed $\frac{1}{4}$ S29 CS BT.

Section Corner to Sections 1, 2, 11, & 12. 133
As Det. by O. B. T.s. - 15" Maple bears N.72°E. 36.3 ft. O.B.T.
38" Fir stump (logged) N.31 $\frac{1}{2}$ °W. 15.0 ft. O.B.T.
24" Fir stump (logged) S.33°E. 15.8 ft. O.B.T.
At Corner point set $\frac{3}{4}$ "x35" Iron Pipe from which:
4" Laurel bears S.11°E. 31.0 ft. dist. mkd. S12 B.T.
6" Cedar bears S.85°E. 25.7 ft. dist. mkd. S 1 B.T.
14" Laurel bears N.57°E. 79.5 ft. dist. mkd. S 1 T30S R5W W.M. B.T.
9" Maple bears N. 6°W. 31.2 ft. dist. mkd. S 2 B.T.
Road bears North 62.0 ft.

$\frac{1}{4}$ Section Corner to Sections 2 & 11. 134
As Det. by O.B.T. - 15" W.O. Stump bears N.74°W. 11.2 ft. dist. fd.scribe
14" W.O. stump bears S.25°W. 15.2 ft. O.B.T.
At Corner point set 1"x30" Iron Pipe from which:
11" Cedar bears S.78°30'W. 53.1 ft. dist. mkd. $\frac{1}{4}$ S11 T30S B.T.
10" Fir bears N.80°30'W. 46.7 ft. dist. mkd. $\frac{1}{4}$ S 2 B.T. 180
10" Fir bears N.21°W. 61.0 ft. dist. mkd. $\frac{1}{4}$ S 2 B.T.
Top of Ridge bears East 200.0 ft. Road bears North 31.0 ft.

$\frac{1}{4}$ Section Corner to Sections 10 & 11. 135
As Det. by O.B.T. - 12" Maple snag bears N.88°W. 41.6 ft. O.B.T.
15" Maple snag bears N.61°E. 4.6 ft. O.B.T.
At Cor. point found 15" Maple scribed. I rescribed East face of
Maple $\frac{1}{4}$ S and Set $\frac{3}{4}$ " x30" Iron Pipe from which: #307
7" Fir bears N.56°W. 41.6 ft. dist. mkd. $\frac{1}{4}$ S10 B.T.
12" Maple " N.34°W. 63.0 ft. dist. mkd. $\frac{1}{4}$ S10 B.T.
10" Yew bears S.46°W. 71.0 ft. dist. mkd. $\frac{1}{4}$ S10 B.T.
Creek bears South 66.0 ft. dist.

$\frac{1}{4}$ Section Corner to Sections 10 & 15. 136
As Det. by O.B.T. - 40" Pine bears N.45°W. 10.6 ft. dist. O.B.T. fd.scribe.
At Corner Point set 2"x2" Wood Post from which: 178
24" Laurel bears N.28°E. 34.7 ft. dist. mkd. $\frac{1}{4}$ S10 B.T.
12" Fir bears N.59°E. 30.6 ft. dist. mkd. $\frac{1}{4}$ S10 B.T.
24" Laurel bears S.26°E. 50.0' dist. mkd. $\frac{1}{4}$ S15 B.T.
6" Fir bears S.16 $\frac{1}{2}$ °W. 20.9 ft. dist. mkd. $\frac{1}{4}$ S15 B.T.

Section Corner to Sections 10, 11, 14, & 15. 137
As Det. by O. B. T.s. - 44" Pine Stump (logged) bears S.35°E. 132.0' O.B.T.
65" Fir Windfall bears N.35°E. 120.5 ft. dist. O.B.T.
At Corner Point set $\frac{3}{4}$ " x30" Iron Pipe from which:
20" Fir bears N.25°W. 18.3 ft. dist. mkd. S10 B.T.
6" Fir bears N.25°E. 46.0 ft. dist. mkd. S11 B.T.
16" Fir bears N.81°E. 41.0 ft. dist. mkd. S14 B.T.
16" Fir bears S.66°W. 35.4 ft. dist. mkd. S15 B.T.
Creek bears East 15.0 ft. dist.
 $\frac{1}{4}$ Corner 10/15 bears West (21°30' Var.) 2638.0 ft.
Fence Corner bears S.76°E. Approx. 105.0 ft.

$\frac{1}{4}$ Section Corner to Sections 11 and 14. 138
At Midpoint, I set I. P. from which: 182
6" B.O. bears N.7°W. 69.0 ft. dist. mkd. $\frac{1}{4}$ S11 B.T.
5" W.O. bears N.26°E. 61.8 ft. dist. mkd. $\frac{1}{4}$ S11 B.T.
24" Laurel " N.51°W. 75.0 ft. dist. mkd. $\frac{1}{4}$ S11 T30S B.T.
E.-W. Fence bears North 59.0 ft. - Sec. Cor. bears East 2525.0 ft.
Sec. Cor. bears West 2525.0 ft. (Var. 18°48')

John H. Markham, Jr.
For. Stomar Lumber Co.
Witnesses: W.E. Crawford
R.G. Boyd
March 20 - 25, 1958
C.S. File No. 42/349

J.L. Markham