

Douglas County Surveyor's Record of
Government Corners Renewed

30 T. S. 5 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97196

Section Corner to Sections 11, 12, 13, & 14.

139

As Det. by O.B.T'S. - 16" Fir stump bears N.50°E. 10.5 ft. O.B.T. fd. Sch.
15" Fir stump bears N.32°W. 13.2 ft. dist. O.B.T., Fd. scribe.

At Corner Point set 1½" x 40" Iron Pipe from which:

5" Laurel bears N.32°W. 11.6 ft. dist. mkd. S11 B.T.
12" Fir bears N.19°W. 24.5 ft. dist. mkd. S11 B.T.
10" Fir bears N.10°E. 21.0 ft. dist. mkd. S12 B.T.
30" Fir bears S.20°W. 35.4 ft. dist. mkd. S14 B.T.

Fence Corner bears S.45°W. 16.5 ft. distance.

John H. Markham, Jr.
For Stomar Lumber Co
March, 1958
C.S. File 42/349

West ¼ Corner to Section 25.

140

Found - 24" B. O. S.45°E. 125 lks. Cut out the upper blaze & found old
scribe "S" intact.

14" B. O. N.67°W. 219 lks. was gone.

Set an Oak Stake at the Corner & Marked two new Witness Trees:

30" B. O. N.50°E. 79 ft. mkd. ¼ S25 BT - 1581
14" W. O. N.63°W. 97 ft. mkd. ¼ S26 BT -

South ¼ Section Corner to Section 25.

141

At prop. distance between the S.W. Corner of Sec. 25 & S.E. Cor. Sec. 25
5,106.6 ft., we set a Madrone Stake for Corner Mkd. ¼ S 225
new witness trees:

24" Fir N.15°E. 30 ft. ¼ S25 BT - 1581
22" Fir S.13°E. 40 ft. ¼ S36 BT -

Corner located on North Slope very near top of Ridge in old Burn.

H. L. Northcraft
T. Schattlenkerk
H. Rishel
R. Wenner
May, 1950
C. S. File No. 40/281

These Corners have
A. Boyer's No. 1581,
not authentic.

East ¼ Corner to Section 25.

142

Found - Old 30" Oak S.30°W. 400 lks. The upper blaze had been cut out
& marks were gone. Cut out old lower blaze & found "BT" intact.
Remarked old tree with "BT" near old marks.

Set an Oak Stake at the Corner with a mound of stone.

New BT.: 30" Fir S.20°E. 273 ft. Mkd. ¼ S30 BT - 1581.

Note: 30" Oak should be S.0°30'W. instead of S.30°W.. Corner as set
found & discrepancy noted by J. Markham, 2880, 12/23/50.
Corner as set here not moved.

Section Corner to Sections 2, 3, 10, & 11.

143

As determined by Old BT's: 26" B. Oak N.65°W. 75 ft.
26" P. Pine S.37°W. 82 ft.
22" B. Oak N.46°E. 31 ft.

At Corner found Original Stone & Set 1" x 30" Iron Pipe, from which:

5" Madrone bears N.51°E. 20.0 ft. dist. Mkd. S 2 BT.
6" Madrone bears N.17°E. 32.0 ft. dist. Mkd. S 2x BT.
9" Madrone bears N.19°W. 26.8 ft. dist. Mkd. S 3 BT.
10" Madrone bears S.78°W. 65.0 ft. dist. Mkd. S10 BT R5W.
7" Madrone bears S.26°E. 13.0 ft. dist. Mkd. S11 T30S BT.

Old fence bears S.70°E. & N.70°W. through Corner.

Corner lies on nose of East Ridge.

Burton W. Holt, #418
V.E. Essary
J.H. Markham, Jr.
July 22, 1958
C. S. File No. 42/377

Section Corner to Sections 13, 14, 23, & 24.

144

Found - Orig. 20", now 24" B. Oak Snag S.25°W. 6.6 ft. Open & find good
scribing "W 5".

Orig. 15", now 24" B. Oak Snag N.45°E. 18.2 ft. Record 13.2 ft.
shows good scribing "S 3".

B. Oak, now 24", that checks record distance & bearing for
original N. W. BT., but I do not find scribing nor do I
find Iron Bar set by Frear, 1918, Coc # 43

Note: Fence Corner bears S.58°W. 4.0 ft.

Set Brass Cap at Corner Mkd: County Surveyor's Office, 1958 S14|S13 S23|S24 T30S R5W

New BT's: 21" R. Fir bears S.80°E. 26.8 ft. scribed S24 T30S R5W CS BT.

12" Cedar bears N.62°E. 52.3 ft. scribed S13 T30S R5W CS BT.

7" R. Fir bears N.16°W. 31.2 ft. scribed S14 CS BT.

14" Cedar bears S.18°W. 66.3 ft. scribed S23 T30S R5W CS BT.

James W. Byron, Deputy
M. Godfrey
S. A. Blow
August, 1958
C.S. File No. 49/107