

Douglas County Surveyor's Record of
Government Corners Renewed

T. 30 S. T. S. R. 5 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Section Corner to Sections 29 - 30 - 31 - 32. 209
Found - $\frac{3}{4}$ " I. Pipe (flush) at Corner (See Cors. No. 61 & 97) #286
38" B.O. N.45°W. 31.5 ft., shows scribing.
N. E. BT., now stump.
30" B.O. S.42°W. 92.9 ft., shows good scar.
14" B.O. S.54 $\frac{1}{2}$ °E. 94.6 ft., shows good scar.
New BT's: Rescribe, now 38" B.O. N.45°W. 32.5 ft. S30 T30SR5W CS BT.
6" W.Oak bears N.31°E. 60.0 ft. scribed S29 CS BT.

$\frac{1}{4}$ Section Corner to Sections 30 and 29. 210
Found - $\frac{3}{8}$ " I. Rod at Corner. (See Corner No. 80) #277
Now 14" Laurel N.32°W. 7.0 ft., shows good bark scribing.
Orig. N. E. BT., now snag.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1963
S30/S29 T30S R5W.
New BT: 14" Fir bears N.71°E. 11.6 ft. scribed $\frac{1}{4}$ S29 CS BT.
Rescribe 14" Laurel N.32°W. 7.0 ft. $\frac{1}{4}$ S30 CS BT.

Section Corner to Secs. 28 - 29 - 32 - 33. 211
Found - $\frac{3}{4}$ " I. Pipe at Corner and all Bearing Trees, - SEE GOV'T. NOTES
as recorded in Renewal Cor. No. 77. - VOL. 35, P. 14397
New BT: 6" W.Oak bears S. 2° E. 11.4 ft. scribed T30S R5W S33 CS BT.

$\frac{1}{4}$ Sec. Corner to Sections 29 and 28. 212
Found - Both BT's. as recorded Cor. No. 85, now down,
N. W. Bearing Tree shows scribing.
Note - Corner is area disturbed by roots of N.E. BT.
I. Pipe set at corner not found.
New BT's: 10" R.Fir bears S.26°W. 12.8 ft. scribed $\frac{1}{4}$ S29 CS BT.
15" R.Fir bears S.73°E. 41.6 ft. scribed $\frac{1}{4}$ S28 CS BT.

Section Corner to Secs. 20 - 21 - 28 - 29. 213
Found - All Original BT's. Orig. S.E. & S.W. BT's. alive,
show scars. Orig. N.W. BT., now stump.
Orig. N.E. BT., now snag.
Also find BT's. and Stone as recorded Cor. No. 52,
except do not find N.W. BT.
Set - Brass Cap at Cor. Mkd: County Surveyor's T30S R5W S20 | S21
Office, 1963 S29 | S28
New BT's: 7" R.Fir bears S.80°E. 6.0 ft. scribed S28 T30S R5W CS BT.
8" R.Fir bears S.28°E. 33.6 ft. scribed S28 T30S R5W CS BT.
8" Laurel bears S.52°W. 38.0 ft. scribed S29 T30S R5W CS BT.
5" W.Oak bears N.44°E. 16.2 ft. scribed S21 CS BT.
Note - Corner is on the ridge 40 ft. south of old logging road
and 75 ft. west of fence. #264

S. W. Corner D. L. C. No. 47. 214
Found - $\frac{3}{4}$ " I. Pipe at Cor. & both BT's. as recorded, Cor. No. 51,
each shows scribing. Fence corner bears N.33°E. 8.0 ft.
New BT: 12" R.Fir bears N.39°E. 41.5 ft. scribed CL 47 SW CS BT.

S. E. Corner D. L. C. No. 47. 215
Found - Stone at Corner & both BT's. as recorded Cor. No. 2.
S. W. BT. shows scribing.
Fence Corner to West & North bears N.20°W. 6.0 ft.
Set - Brass Cap alongside Cor. Stone & Mkd: County Surveyor's
Office, 1963, S. E. DLC 47 T30S R5W.
New BT's: Rescribe, now 24" W.Oak South 7.9 ft. SE DLC 47 CS BT.
Rescribe, now 20" Laurel S.81°W. 15.9 ft. SE DLC 47 CS BT.

James W. Byron, Deputy County Surveyor
Mike Darby and Jim Halterman
October & November 1963
C. S. File No. 53/26

Pa. OK 1-22
R. DeLAW M114-37