

Douglas County Surveyor's Record of
Government Corners Renewed

T. 30 S. T. S. R. 5 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

JAMES W. BYRON, CO. SURV
JOHN M. POWELL & Crew
Jan. 23, 1969
C.S. File No. 54/77

Section Corner to Sections 19 and 30 only, T30-5W.
This corner set from survey - set at correct distance N. - S. by proportionate measurement.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1969

R	T 30 S	R
6	S 19	5
W S 25	S 30	W

Bearing Objects: No trees reasonable for BT's.
Two 3/4" Iron Rods East 15.0 ft. and 20.0 ft.
Fence Post North 53.38 ft.
Fence Post North at Sec. Cor. to Secs. 24 & 25 only, T30-6W.
Note - This corner lies 106.77 ft. south of Sec Cor. 24 & 25 only.

#325 244
FD. O.K. by
J. H. MARKHAM, JR.
MAY 24, 1982

RE-RENEWED, SEE CORNER NO.

M 92-33

W. Byron
Co. Surv.
M. Powell
& Crew
S. 54/84
M 37-44

South 1/4 Corner Section 35 only.
This corner set from survey of pro-rated distances.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1969

T29 S	R 5 W
1/4	S 35
T30S	

New BT's: 13" D. Fir N. 4 1/2° E. 46.8 ft. mkd: 1/4 S35 CS BT.
10" Laurel N. 58° E. 22.3 ft. mkd: 1/4 S35 CS BT.
This corner lies north 4.0 ft. of East-West fence line.

April 7, 1969

Powell
Crew
S.No. 53/26

1/4 Cor. sections 5 and 4.

Found- 3/4 Iron pipe at 1/4 cor. See Ren. #37.
5" W. Oak now 10" S. 15 1/2° E. 15.6 ft., opened and founded scribe of (1/4)

13" W. Oak now 24" S. 46 1/4° W. 179.6 ft. shows an axe face.
Set - Brass cap at 1/4 cor. mkd: County Surveyor's Office 1969
(Set 3/4" I.P. along side)

New BT's - 6" Laurel S. 79 1/2° E. 30.7 ft. scribed- 1/4 S4 CS BT.
8" Douglas Fir S. 88° W. 114.6 ft. scribed- 1/4 S5 CS BT.

Note - This 1/4 cor. lies on a N. slope over looking populated area.
Jan. 1970

OK 1/86, DEGROOT
M100-77A4B

FD OK 9/30 1990-0080

246
FD. OK 2/92
G. BAUGHMAN
M114-43

James W. Byron, County Surveyor
John M. Powell & Crew
March, 1970
C. S. File No. 54/108 M 39 - 45

North 1/4 Corner to Section 4 only, T30-5W.
This corner set from survey at pro-rated distance:

Set - Brass Cap at 1/4 Cor. Mkd: County Surveyor's Office, 1970

T29S	R5W	1/4
T30S		S 4

New BT's: 6" B. Oak S. 77 1/2° W. 4.5 ft. mkd: 1/4 S 4 CS BT".
13" Laurel S. 80° W. 42.3 ft. mkd: 1/4 S 4 CS BT".

3/2/70

RE-RENEWED, SEE CORNER NO.

South 1/4 Corner to Section 33 only, T29S-R5W.

This corner set from survey at pro-rated distance:

Set - Brass Cap at 1/4 Cor. Mkd: County Surveyor's Office, 1970

T29S	R5W	1/4	S 33
T30S			

New BT's: 14" W. Oak N. 65° E. 85.5 ft. mkd: 1/4 S 33 CS BT".
18" B. Oak N. 12° W. 129.0 ft. mkd: 1/4 S33 CS BT".

This corner lies 6.0 ft. N. of E-W Fence Line & 140.0 ft. S. of Ravine.
2/5/70

Center 1/4 Corner Section 4.

This corner set from survey, See M 39 - 45.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1970

T 30 S	R 5 W
C	1/4
S 4	

New BT's" 19" W. Oak S. 69° E. 17.7 ft. mkd: "C 1/4 S 4 CS BT".
14" Laurel N. 65° W. 28.3 ft. mkd: "C 1/4 S 4 CS BT".

3/5/70

Section Corner To Sections 28, 27, 33, and 34. See Ren. #175.

Found: 30" B. Oak, now 30", N. 18° E., 16.7 ft. Shows good scar.
13" Cedar, now 17", S. 55° E., 54.5 ft. Scribe visible R5W & other marks.
6" Laurel, now 6", S. 81° W., 37.0 ft. Scribe visible T30S R5W S33 CS BT.

Also 2" I. pipe rusted & BLM Brass Cap which is to be removed.
Set; Brass Cap at sec. cor. alongside BLM Cap mkd: T 30 S R 5 W

County Surveyor's Office, 1971

S 28	S 27
S 33	S 34

Cont. over,

MARCH 71

John M. Powell & Crew
July 29, 1971
C. S. File 53/26

250