

Douglas County Surveyor's Record of
Government Corners Renewed

30

T. S.

5

R. W. W. M.

ROKE-CHAPMAN CO., EUGENE, ORE. 21801

S.E. Cor. to DLC 46
Ren.#86
Found- A 1" X 24" outer diam. IP Laying on the ground from which:
A 10" Fir stump,(was 6" fir) with visible scribe"BT" bears S 4°E.,24.4ft.
A stump hole bears N5°E.,10.5 ft.
An original 18" now 36" black oak showing good scar bearsN37 1/2°W.,208.1 ft
(call: N37 1/2°W.,213.2 ft.) No sign of other tree.
At the corner as determined by record distance and bearing from OBT we
SET- A 1" x 30" IP with brass cap stamped: T 30 S R 5W
DOUGLAS CO SURVEYOR
1975

263

Clell Goodwin
Gary Langlitz
Vic Cangie
Lenora Ladig
CS 57/36
10/16/75

From which: an OBT 36" Black oak bears N37 1/2°W.,213.2ft.
A 10" Fir stump bears S3°E.,20.3 ft.
A 14" Black Oak scribed "SE Cor. DLC # 46 CS BT" in a double blaze bears
N29°E.,46.3 ft.
A 21" incense cedar scribed "SE Cor. DLC 46 CSBT."in a double blaze bears
N 71 1/2°E.,33.2 ft. Compass Declination 20°East 10/16/75
Section Corner Sec.20,21,29 and 28 REN #213

Found-A 1963 Co.Surveyors brass cap on a 1" x30" IP
BT- A 22" (possibly original 20") oak tree alive and scarred but hollow bears
S56°E.,31.8ft. (call:S 60°E., 29.0 ft)
A 11" Madrone with visible scribe " S 20 CSBT" alive but hollow bears N8 1/2°
W.,7.2 ft.(Call: N11°W.,7.2)
A 6" oak alive and well healed bears N 44°E.,16.2 ft.
A 10" fir snag bears S 74°E.,6.2 ft (call" S80°E.,6.0 ft)
A 13" madrone with scribed face rotted out bears S 53°E.,9.1 ft. (call: S55
1/2°E.,9.2 ft.)
A 9" fir snag bears S 28°E.,33.6ft.
A 10" madrone alive and well healed bears S 52°W.,38.°ft.
New BT's- A 13" fir bearing N 86°W.,59.0 ft. marked "T 30 S R5W S20 CSBT"
in a double blaze. Compass Declination 20° East 10/23/75

264

SW Cor. DLC # 47 REN # 214
Found 3/4 I pipe
From Which: Orig 21" now 33" Laurel bears S 17°E.,13.9 ft.(call S 19°E.,
13.9 ft)
Orig. 36" now 39" Laurel bearsN71°W.,20.2 ft.(call N 69°W.,19.2 ft)
Set: 1" X 30" I.Pipe with brass cap marked: T 30 S R 5W
DOUGLAS CO. SURVEYOR S.W. Cor.
1975 DLC 47

265

SET: Brass cap to match orig. call 3/4 I Pipe bears N 70°E.,1.35 ft.
12" R.Fir bears N 41°E.,14.8 ft. (call N39°E.,41.5 ft by notes-tag
+ indicates calls as N 41°E.,14.5 ft. Compass declination 20°E. 10/24/75

N.E. cor. DLC #46
At the corner as determined by a re-survey we set a brass cap on a 1" X 30"
I.P. Stamped
DOUGLAS CO. SURVEYOR T 30 S R 5W
1975 N.E. Cor. DLC 46

266

Clell Goodwin
Gary Langlitz
Lenora Ladig
11/24/75
CS 57/39

We find no original evidence of this corner.
BO-An aluminum cap marked "Douglas Co Surveyor W.C. +" Bears S2°08'36"W 30.00 ft.
A plastic cap marked "Douglas Co Surveyor" on a 5/8 IR bearsN2°08' 36"E.,
40.26 ft.
A 28" ponderosa pine scribed "NE DLC 46 CS BT" in a single blaze bears N77
1/2°E.,113.0 ft.
This corner lies on tip of a dike between a log pond and the south Umpqua
River Compass Declination 20° East 11/24/75

267

Witness corner for NW Cor. DLC #51
Found - A 1" Pipe, set flush in the East road shoulder of Gazley Rd. Ren. #108
One apparent BT, A 42" Oak, bearing N.54 1/2°W., 126.7 ft. with
a well-healed double blaze, with poster saying S.54 1/2°E.,
125.4 ft. posted by CS in 3/61. C.S. 52/72. This information
was used to locate the found I.P. The records of the County
Surveyor do not give an origin for the I.P. or the 42" B.Oak.
There is no recorded call to the BT.

Gary Langlitz, Co.
Surveyors Office
M. Lenora Ladig
Karen Cheney
5/17/76

This corner fits well for distance from the SE cor. of Sec. 21, T.30S., R5W.C.S. 59/15

RESEARCH Shows THIS TO
BE 1946. RECORDED IN
REN. # 44
4/10/83 Z.K.

RENEWED CORNER NO. #303
4/10/83