

**Douglas County Surveyor's Record of  
Government Corners Renewed**

T 30      T. S.      R 5      R. W. W. M.

HOKE-CHAPMAN CO., EUGENE, ORE. 21881

275

Section Corner for sections 30 and 31 only.

- Found - A 1" x 44" I.P. set 32" in the ground.  
 A 15" Orig. now 42" remains of stump at ground level bears N.44 1/2°E., 62.2 ft. (Rec. N.42°E., 64.0 ft.)  
 A stump hole bears approx. S.80°E., 55.0 ft. (Rec. 56.1 ft.)  
 A 6" now 18" B. Oak is down, orig. position approx. bears N.7°W., 31.0 ft. I chop open well healed blaze to find scribing has been chopped out.  
 A 5" now 15" B. Oak bears S.88°W., 42.6 @ 22°=39.5 ft. (Rec. S.85°W., 40.3 ft.) with a badly rotted blaze apparently chopped out.  
 A 10" now 20" Fir stump 5 ft. high, bears N.31°E., (Rec. N.29°E) 61.4 ft. with visible scribing "S30 CC" in a partly healed double blaze. Ren. #62  
 A 16" now 18" Fir stump bears S.72°22'E., 13.8 ft. with a rotted out blaze. Ren. #223  
 A 16" now 18" D. Fir bears S.3 1/2°E., (Rec. S.6°E.) 24.2 ft. with a double well healed blaze.

Set - A 1" x 36" I.P. with a brass cap set at ground level and marked:  
 "Douglas County Surveyor"

R	T 30 S	R
6S 36	S 30	5
W	S 31	W
	1978	

- New BT's- A 6" D. Fir bears N.41°E., 20.1 ft. I double blaze and scribe "T30S R5W S30 CS BT".  
 A 7" D. Fir bears S.16°E., 6.7 ft. I double blaze and scribe "T30S R5W S31 CS BT".

Corner is 6 ft. east of a N-S wire fence, 125 ft. East of a dirt road West of small creek.

4/13/78

276

Section corner for Secs. 32 and 33; and Secs. 5 and 4 of T.31-5

- Found - A 1" I.P. with attached brass cap marked "County Surveyors Office" T30S R5W S32 S33 S5 S4 T31S R5W 1957. Monument is approx. 14" high and firmly set. Did not find iron pipe. Ren. #219  
 1858 BT, Fragmentary remains around root hole of a rec. 64" Madrone bearing N.85°E., 4.0 ft. to the area of the apparent face.  
 1858 remains of a badly decayed madrone (fd. no scribing or blaze) Root hole bears S.52°W., 19.8 ft.  
 A Fir 8" now a 12" stump 3 1/2 ft. high bears N.63°E., 24.0 ft. scribed "CS BT" legible on a double blaze. Ren. #7-T31-5  
 A Fir 10" now a 13" snag, 12 ft. high bears S.35°W., 14.5 ft. to face 15.0 ft. to center, scribing "S4 T31S R5W CS BT" visible in unhealed blaze. Ren. #7-T31-5  
 A Fir, 10" now a 13" snag, 10 ft. high, bears S.83°E., 11.5 ft. to face 12 ft. to center (Rec. 14.0 ft.) scribing "T S" visible in burned out double blaze. Ren. #7-T31-5  
 A Fir 16" now a 30 ft. high snag bears N.89°W., 68.8 ft. (Rec. West 70.5 ft.) scribed "T30S R5W S32 CS BT" on a partially healed double blaze. Ren. #157  
 A 9" Madrone now dead with a new growth around old trunk bears S.85°E., 70.2 ft. (Rec. S.87°E) scribed "S 4 T31S R5W CS BT" on a double blaze.  
 A 48" Cedar now a 40 ft. high snag bears S.38°W., 100.7 ft. scribed "S5 T31S R5W CS BT" on a single blaze.  
 A Fir 16" now a 20 ft. high snag bears N.84°W., 75.2 ft. (Rec. N.86°W., 71.1 ft.) scribed "S32 T30S R5W CS BT" on a 3 ft. high blaze.  
 A madrone 18" now a 19" diam., 12 ft. high snag bears N.70°E., 86.4 ft. blaze rotted out.  
 A R. Fir bearing S.66°E., 35.7 ft. is now a tipped out snag partially rotted.

New BT - A Madrone 4", bears N.67°E., 7.2 ft. Bark scribed "S33 CS BT" No other trees available at this time.

6/27/78

R. B. Kimberling  
 F. C. Silagy  
 P.L. Earle  
 Doug. Co. Surveyors Office  
 April 13, 1978  
 C.S. 59/46

Larry E. Monrean, Doug. Co. Surveyors Office  
 F. C. Silagy, witness  
 June 27, 1978  
 C.S. 60/11