

Douglas County Surveyor's Record of
Government Corners Renewed

T 30 T. S. R 5 R. W. W. M.

KORE-CHAPMAN CO., EUGENE, ORE. 21881

277

1/4 Corner for Secs. 30 and 29.

Found - A 1" x 36" I.P. with brass cap set 12" above ground and marked "T30S 1/4 S30 S29 R5W 1963. I reset from bearing and distance to O.B.T. See Ren's 80 and 210

A 14" now 22" 6 ft. high Oak snag bears N.75°E., 26.4 ft. with scribing "BT" in new blaze, orig. blaze rotted away.

A 8" now 14" Madrone (Laurel) bears N.25°W., 10.2 ft. (Rec. N.32°W. 7.0 ft.) with scribing "S3 -CS- T" in a partly healed single blaze.

A 14" now 16", 4 ft. high Fir snag bears N.59°E., 12.1 ft. (Rec. N.71°E., 11.6 ft. with scribing "1/4 S29 CS BT" in a single blaze.

Set - I reset brass cap at record bearing and distance to O.B.T., 6" above ground, stamped "Reset 1978".

Set - I set a 5/8" x 30" I.R. at old brass cap location with Douglas Co. cap set at ground level and stamped "1978".

New BT- A 10" Madrone bears N.56 1/2°E., 34.9 ft. I bark scribe "1/4 S29 CS BT".

Corner is 9 ft. west of the intersection of a N-S barbed wire fence with a picket fence to the east.

6/28/78

278

Section corner for Secs. 29, 28, 32 and 33.

Found - A 2 1/2" O.D. Iron Pipe with brass cap set 9" above ground in an 18" mound of stone marked "T30S R5W S29 S28 S32 S33 1967 Cadastral Survey". Vol. 35 Pg. 14397

An orig. 12" now 21" Oak stump bears N.85°E., 9.2 ft. (Rec. S.89 1/2°E., 7.3 ft.)

A stump hole bears N.55°W., 35.6 ft.

A 12" now 34" White Oak bears S.57°W., 50.0 ft. (Rec. S.55°W. 49.5" with possible scribe marks visible in an almost healed single blaze. Ren. #77

A 14" now 17" White Oak bears N.67°W., 109.5 ft. (Rec. N.68°W., 107.0 ft.) with a well healed double blaze. Ren. #211

A 6" now 8" Oak stump bears S.2°E., 11.4 ft. with visible scribing "CS BT" in bottom of blaze.

New BT's-A 8" White Oak bears S.2°W., 18.6 ft. I double blaze and scribe "T30S R5W S32 CS BT".

A 9" D. Fir bears N.2 1/2°E., 73.0 ft. I double blaze and scribe "T30S R5W S28 CS BT"

Corner is 140 ft. North of Jordan Cr. Road, 20 ft. west of the west edge of a clearing, 50 ft. west of a driveway.

6/28/78

279

Section corner for 1 and 12 only, T.30-6.

Found - A 3/4" I. rod buried 18" under ground. Ren. #205

An 8" W. Oak now 12" with well healed double blaze bears S.59°W., 143.6 ft.

A 12" B. Oak now 14" with partially healed double blaze bears N.65°W., 106.8 ft..

A 3/4" I. Rod 18" above ground, 1.5 ft. north of RR r/w fence bears N.65°W., 49.6 ft. We drive rod 10" farther into ground

New Accessories:

A 1 1/2" x 1 1/2" x 48" angle iron post set 24" in ground bear west 59.9 ft. dist. post in RR r/w fence.

2 inch high letters "X B0" chisled on face of easterly culvert headwall under SP tracks, "X" is 0.65 ft. below top of 7.5 ft. long headwall, bears N.34°W., 144.9 ft.

Corner in large plowed field.

10/2/79

280

Section corner for Secs. 6 and 7 only.

Found - No original post found. No stone found. No pipe found.

A 1" x 30" I. Bolt buried 8 in. below surface. Ren. #39

A 20" W. Oak now 22" with well healed single blaze, bears S.39°W., 268.6 ft. Ren. #39

A 20" B. Oak now 22" with well healed double blaze bears N.62°W., 215.8 ft. to center, 214.5 ft. to face. Ren. #39. Note: Ren. #204 is in error on dist. to this tree.

A 16" B. Oak now 18" with previously opened blaze showing visible scribe "S7 T30 5" bears S.10°E., 241.2 ft. to center, 240.2 ft. to face.

(OVER) NEXT PAGE

R. B. Kimberling
S. J. Flause
Douglas County Surveyors Office
June 28, 1978
C.S. 60/11

FD. OK 8-91
R. BROWN M113-68

-29

L. E. Monrean, Doug. Co. Surveyors
Office
K. Reed; P. Earle; T. Plouff
October 2 and 4, 1979
C.S. 60/34

Accessories Fd.
4/84 O. Subv.
OFFICE: C.S. 62/18

For 1984 Convention
Report. See C.S. 62/18