Douglas County Surveyor's Record of Government Corners Renewed

T 30 T. S. R 5 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

280

CONT -----

L. Monrean; Do. Co. Surveyors Office
K. Reed; P. Earle; T. Plouff
October 4, 1979
C.S. 60/34

An 11" B. Oak, now an 18" in diam. 2.0 ft. high stump bears S.29°E., 213.7 ft. Ren. #204

Set - A 1" x 36" I. Pipe with brass cap stamped "Douglas County Surveyor" T30S R6W S12 S6 S7 R5W 1979", at corner position 14" below su surface of ground. Set I. bolt along northerly edge of cap 2 in. lower.

No new accessories. Corner lies in large plowed field.

— — — — — — — — — —

281

Township Corner, Southwest Corner Sec. 31

Found - Mound of stone (1878 re-survey) 28" at its base and 24" high. At center of mound we find an opening going down through the mound measuring 6 1/2" by 7". Post set in mound not found. A dry creek bed course N.65°W.,bears South 5.5 ft. The 1878 resurvey record indicates a creek 2 lks. wide course west bears South 3.5 ft.

3/4" I.P. set by Wenderoth in 1946. Ren. #59, CS 39/118. A review of the record of survey performed by Wenderoth indicates that the i.p. was set at a position as determined by an arbitrary method of distance allocation rather than by evidence of the orig. corner or its accessories. The I.P. set by Wenderoth bears N.46°26'34"W., 76.24 ft.

Orig. 15" R.Fir bearing S.70°W., 37.6 ft. We find rotted remains of a fir stump bearing S.70°W., 36.2 ft. The remaining portion of the stump is a bark ring broken down to near crown level measuring 24" diam. We also find a portion of the wood in the stump. The wood is buried as it has healed over an opened area facing the mound of stone. The blaze has an old axed notch near the bottom. No scribing found.

Orig. 10" Laurel bearing N.45°W., 49.3 ft. We find an old decayed root crown bearing N.35°W., 51.3 ft. The root crown measures 40" with a 20" Madrone growing from westerly portion of root crown. Tree has a badly decayed center.

Orig. 12" Laurel bearing N.70°E., 17.8 ft. We find a depression in ground bearing N.68 1/2°E., 16.8 ft.

Orig. 12" Laurel bearing S.75°E., 36.3 ft. We find a 24" Madrone bearing S.75°E., 33.1 ft. Tree has burned out center. Old axe marks at depth of approx. 6". No scribing found.

Set - At center of mound of stone, We set a 1" x 36" I.P. with brass cap stamped "Douglas County Surveyor" 1979

Monument is 18" in the ground with mound of stone 20" high.

T 30 S

R 6 W	S36 | S31	R 5 W
	S 1 | S 6	

T 31 S

Note - Prior to locating the orig. corner location, several days had been spent in searching for it. We determined to set a monument at the point as determined by double proportion procedure. This procedure was accomplished May 15, 1979. A final search effort lead to the evidence located in this report. As we have blazed trees prior to the location of the true corner position, a note will accompany information for any BT on which the blaze is not oriented toward the corner. See 5/15/79 attached notes in C.S. 61/3.

New BT's -A D.Fir, 17", scribed "T31S R6W S1 CS BT" on a double blaze (oriented N.24 E.) bears S.70°W., 61.4 ft.

A 10" Maple scribed "T30S R6W S36 CS BT" on a double blaze (oriented West) bears N.45°W., 14.1 ft.

A 20" D.Fir scribed "T30S S36 CS BT" on a double blaze (oriented S.14°E.) bears N.49°W., 66.8 ft.

A 12" D.Fir scribed "T30S R6W S36 CS BT" on a double blaze bears N.74 1/2°W., 83.6 ft.

A 28" D.Fir scribed "T31S R5W S6 CS BT" on a double blaze bears S.52 1/2°E., 32.1 ft.

Found - From Wenderoth's I.P. Ren. #59, we find the following BT's

A 26" Fir, now a 20" rotted stump with no markes visible on open double blaze bears N.81 1/2°E., 16.7 ft. (Rec. N.81°28'E,16'

An 8" now 12" I.Cedar, alive with well healed double blaze bears S.5 1/2°E., 41.6 ft. (Rec. S.5°35'E., 41.6 ft.)

C O N T. N E X T P A G E

Douglas County Surveyors Office
Gary Langlitz, Party Chief
L.E. Monrean; Karen Reed; Peter Earle
June 4, 1979
RM 3 - 26 C.S. 61/3