

Douglas County Surveyor's Record of  
Government Corners Renewed

T 30 T. S. R 5 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21081

286

Section corner for Secs. 29, 30, 31 and 32.

Found - A 1" I.P. flush with ground set by Wenderoth. C.S. 39/118 and  
Renewals #61 and 97

Original monument not found.

Orig. 10" now 21" B. Oak. We open and find old axe marks, no  
scribing in rotted center portion. Tree bears N.6 1/2°W., 7.9 ft.  
(Rec. N.5°W.,)

Orig. 15" now 24" B. Oak. We open and find old axe marks. No  
scribing in rotted center. Tree bears S.66°W., 46.2 ft. (Rec.  
S.65°W.)

A 12" now 18" B. Oak with faint blaze visible bears S.57 1/2°E.  
94.6 ft. Renewals #61 and 97

A 30" now 34" B. Oak with well healed double blaze bears S.6°W.  
92.9 ft. (Rec. S.4°42'W.) Ren. 61 and 97

A 38" B. Oak with well healed blaze and reblaze (Ren. #209) bears  
N.44°W., 32.8 ft. (Rec. N.44°45'W., 31.5 ft.)

All other recorded bearing trees searched for and not found.

Set - At the section corner position as referenced by found 1 inch I.P.  
We Set a 1" x 36" I.P. 35" into the ground with attached brass cap  
marked "Douglas County Surveyor" T30S R5W S30 S29 S31 S32 1979  
1" I.P. buried along easterly edge of brass cap monument.

New BT's-A 8"D. Fir scribed "S29 CS BT" on a double blaze bears N.82°E.,  
65.8 ft.

A 14" D. Fir scribed "T30S R5W S31 CS BT" on a double blaze bears  
S.89 1/2°W., 10.1 ft.

Corner is located at intersection of fences running north, south and east.  
- - - - - 7/9/79

1/4 Corner for Secs. 32 and 33.

Found - 1" I.P., 1.2 ft. above ground. See Ren. #34

A 12" Laurel now an undetermined diam. rotted tree remnants in  
hole bears N.25°W., 27.7 ft. (Orig.)

An 8" Laurel, now a roothole, bears S.10°E., 19.1 ft. (orig.)

A 12" Fir, now a 20" rotted stump with scribe "CS BT" visible  
bears N.29 1/2°E., 42.0 ft. Upper portion of tree has illegible  
scribe marks. Ren. #34

A 4" Laurel, now a 12", bears S.50°W., 18 ft. to face, 18.7 ft.  
to center dist. with visible partial scribing. Ren. #34

An 8" B. Oak, now an 11" bears S.54 1/2°E., 31.4 ft. with well  
healed double blaze. Ren. #155

Set - Replaced 1" I.P. with a 1" x 36" I.P. with brass cap marked:  
"Douglas County Surveyor" T30S R5W 1/4 S32 S33 1979.  
Place 1" I.P. along west side.

New BT's- A 9" Fir bears N.46°E., 41.6 ft. dist. scribed "1/4 S33 CS BT"  
in a double blaze.

A 15" Fir scribed "1/4 S32 CS BT" bears N.43 1/2°W., 40.3 ft. with  
double blaze.

A 9" Fir scribed 1/4 S32 CSBT" in a double blaze bears S.36°W.,  
31.5 ft.

Fence corner fence runs north and west.  
- - - - - 7/5/79

Center 1/4 Corner for Sec. 31

Set - A 1" x 36" I.P. with brass cap marked "Douglas County  
Surveyor" T30S R5W C 1/4 S31 1979

Center 1/4 set by intersection of straight lines connecting  
opposite 1/4 corners.

New BT's- An 10" Fir scribed "C 1/4 S31 CS BT" in double blaze bears S.6°E.,  
54.3 ft. dist.

A 9" Pine scribed "C 1/4 S31 CS BT" in a double blaze bears  
N.82°E., 214.7 ft. dist.

Corner lies 5.5 ft. easterly of a random N.S. fence line.  
- - - - - 7/19/79

Douglas County Surveyors Office  
Gary Langlitz, Party Chief  
Karen Reed; Frank Silagy; Vicki Woodral  
Stephen Flause; Ed Monrean  
June-July 1979  
RM 3 - 26 C.S. 61/3

Fd. 7/90  
M 112-4

Fd. 9/28-91  
R. Brown M 113-68

287

288