

Douglas County Surveyor's Record of
Government Corners Renewed

T 30 T. S. R 5 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

293

CE 1/16 Section 31

Set - At position of center east on sixteenth corner Sec. 31 as determined by survey, WE SET an iron pipe 1" x 36" with brass cap attached flush with ground. Cap is stamped "Douglas County Surveyor" T30S R5W C E 1/16 C S31 1979. Set witness post and sign 2 feet south.

New BT's- A 11" D. Fir scribed "CE 1/16 S31 CS BT" on a double blaze bears S.77 3/4°E., 209.6 ft.
A 20" W. Oak blazed and scribed "CE 1/16 S31 CS BT" bears S.35°E., 67.2 ft.

Note: Monument is approx. 187 feet west of a N-S fence.

7/17/79

294

Center west 1/16 Corner Sec. 32

Set - At center of west 1/16 corner of section 32, T30S R5W as determined by survey, WE SET a 5/8" x 30" iron rod with aluminum cap marked: "C W 1/16 S32 C . Monument set 2 inches below surface

New Accessories:

A bridge spike set in center line of paved road to county waste disposal site stamped "BO 1" bears S.5°16'02"W., 319.00ft. Spike is set on line between CW 1/16 S32 and W 1/16 on south line of S. 32.

A 5/8" I.R. with alum. cap stamped "BO 2" bears S.89°07'33"E., 135.00 feet is on line between CW 1/16 S32 and C 1/4 S32. This monument is approx 2 feet west of a north south fence line.

Note: This corner is located in leveled graveled area as prepared for county stock pile.

8/8/79

295

SW 1/16 Corner Sec. 32

Set - At the intersection of lines between properly proportioned corners as determined by survey, WE SET a 1" x 36" I.P. 30" into the ground attached brass cap is stamped: "Douglas County Surveyor" T30S R5W SW 1/16 S32 1979"

New BT's-A 8" D. Fir scribed "SW 1/16 S32 CS BT" on a double blaze bears N.86 1/2°W., 51.9 ft.

A 8" D. Fir scribed "SW 1/16 S32 CS BT" on a double blaze bears S.60°E., 23.9 ft. to the center of the base. The center of the tree at the "BT" blaze bears S.86 1/2°E., 21.3 ft.

No other suitable trees available in the area to reference.

7/10/79

296

South 1/16 Corner for Secs. 31 and 32

Set - At position of S 1/16 between S31 and S32 as determined by survey WE SET a 1" x 36" I.P. with brass cap attached 30" in the ground marked: Douglas County Surveyor T30S R5W S1/16 S31 S32 1979"

New BT's-A 7" Fir bears S.10°E., 35.0 ft. marked with double blaze "S 1/16 S32 CS" in upper blaze. "BT" in lower blaze.

No other trees suitable for scribing in area.

Note: Corner is north approx. 70 feet below old logging road going east and west on north slope.

7/12/79

297

SE 1/16 Corner for Sec. 31

Set -At position of SE 1/16 corner section 31 as determined by survey WE SET a 1" x 36" iron pipe 34 inches into the ground with attached brass cap stamped "Douglas County Surveyor" T30S R5W SE 1/16 + S31 1979.

New BT's- A 9" D. Fir scribed "SE 1/16 S31 CS BT" on a double blaze bears N.59°E., 27.0 ft.

A 16" Maple scribed "SE 1/16 31 CS CT" on a double blaze bears S.10°E., 85.7 ft. This tree located in creek bottom running northerly.

7/16/79

Douglas County Surveyors Office
Gary Langlitz - Karen Reed - L.E. Monrean
P. Earle; Vicki Woodral; F. Silagy
July - Aug. 1979
RM 3 - 26 C.S. 61/3

Fd 7/90
M112-4

Fd 7/90
M112-4