

**Douglas County Surveyor's Record of
Government Corners Renewed**

30 T. S. 6 R. W. W. M.

J. W. Cole, Surveyor
Wit.
Ben B. Irving, Chain
January 23, 1924.

Renewed by
Frank Cain and
recorded by
J. W. Cole
February 3, 1923.

Frank Cain
recorded by
F. C. Frear
C. S. April
1919.

F. C. Frear
F. Cain
F. Cain
F. Cain
F. C. Frear
H. A. Rasor
J. B. Henslee
Cecil Black
Ralph Johnson
Apr. 15, 1919.
Oct. 7, 1919

Cot. S, 1915.

- 1 ✓ CORNERS TO WM. THURMAN D.L.C. No. 49. **CORNER NO. #69**
Renew N.W. Corner from ~~original~~ ~~line~~ ~~line~~ both standing and
alive. Set Oak Post 4" x 4" x 3 1/2".
- 2 ✓ S.W. CORNER **CORNER NO. #58**
Renew corner from Oak B.T. no evidence of ~~set B.T.~~
Oak Post for corner.
- 3 ✓ N.E. CORNER. **49**
Renew corner by setting an Oak Post from which original
B.T.s bear N.55°E., 21 lks. Could find no evidence of
other B.T. Jesse W. Cole, Deputy
- 4 ✓ CORNER BETWEEN SECTIONS 34 and 35. **CORNER NO. #233**
Reset from 20" White Oak B.T. stump which bears S.60°E.,
3.14 chs., marks main. I set a 3/4" dia. Iron Bolt and
a 10" x 12" x 18" Sandstone from which
a 4" Pine tree bears N.45 1/2°E., 75 1/2 lks. C.S.B.T.
- 5 ✓ N.E. CORNER OF CLAIM 40. **CORNER NO. 173**
Reestablished by setting a 6" x 8" x 16" boulder marked
X 40 from which
A 42" Black Oak scribed C. 40 C.S. T.303.-R.6W. bears
N.72°20'E., 61 lks.
- 6 ✓ CORNER SECTIONS 11 and 14. **CORNER NO. 145**
Renewed from which
A White Oak 30" bears S.41°05'W., 2.32 ch.
- 7 ✓ S.E. CORNER OF I. B. NICHOLS CLAIM 44. (Renewed) **CORNER NO. #16**
Reestablished as per old B.T.
An 18" dia. bears S.64°E., 1.27 ch.
- 8 ✓ SECTION POST ON SOUTH BOUNDARY OF SECTION 36. **CORNER NO. 42**
Old B.T.s decayed, I mark a red fir 12" in dia. for
section post from which;
A White Oak 16" in dia. marked 1/4 S. C.S. bears
S. 5 1/2°E., 79 lks.
A Black Oak 22" in dia. marked 1/4 S. C.S. bears
N.72 1/2°E., 28 lks.
- 9 ✓ S.E. CORNER OF THE JAMES CATCHING D.L.C. No. 43.
Found the corner in bad shape and renewed it as
follows:
Set an Iron pipe 1" in dia., 30" long, 22" in ground;
for the corner, and from which;
A Black Oak 18" in dia. marked C.S., C. 43, bears 206
S.54°E., 40 1/2 lks.
A Black Oak 16" in dia. marked C.S., C.43, T.30S.R.6W.
S.25 bears N.27°W., 42 lks.
Established in the presence of P. A. Wilson, C. E. Osborn
and G. Griegs.
- 10 ✓ CORNER TO SECTIONS 27, 28, 33 and 34. **CORNER NO. 164**
Set an Iron Pipe 1 1/2" x 40" and mound of rock from
remains of stump of old Oak B.T. bears N.58°W., 127.4 ft.
A 40" Pine B.T. bears South 246.6 ft. No other trees
to be found and I set corner so that bearing and distance
to Oak checked but only distance to pine would check.
Marked new trees
A White Oak 12" dia. N.19°00'W., 92.6 ft.
A Black Oak 15" dia. S.65°00'E., 355.0 ft.
An Ash 8" dia. N.21°00'E., 62.0 ft.
An Ash 8" dia. S.24°15'W., 264.0 ft.