

Douglas County Surveyor's Record of
Government Corners Renewed

30

T. S.

6

R. W. W. M.

✓ CORNER BETWEEN 29, 30, 31 and 32. 11

I set a granite rock 10" x 12" x 18" marked C.S. and 5 notches on East side, --one notch on South side from which remains of old tree fallen and decayed showed all scars bears N.6°30'E., 239.0 ft.

A 24" Black Oak alive bearing scars N.78°W., 153.0 ft.

A stump of 40" Black Oak in which I found old face with scribe mark B, bears S.60°W., 126.0 ft.

Marked boulder 4' x 8' x 4' N.36°E., 52.2 ft.

A 12" White Oak N.47°W., 20.0 ft.

A 8" White Oak S.19°15'W., 36.0 ft.

148

✓ N.W. CORNER OF THE RIDDLE D.L.C. NO. 39. 12

I renewed the corner from original B.T.s. I set a sandstone 8 x 10 x 15 marked CL. 39 C.S. from which stump of original B.T. with scribe marks visible N.3°E., 25.8 ft.

A Black Oak 26" nearly dead bears N.82°E., 54.0 ft.

blazes face westerly, top blaze chopped out but old wood bearing scribe marks were found in the hollow of the tree when it was chopped open the lower blaze. I also found a portion of scribe marks below. This corner does not correspond with all calls of the field notes but I could find no position that would fulfill all calls.

I marked new trees

A White Oak 10" dia. bears S.49°30'E., 45.5 ft.

A White Oak 10" dia. bears S.52°30'W., 39.0 ft.

149

✓ CORNER OF 20, 21, 28 and 29. 13

I renew corner from one C.S.P. a Laurel still standing and scribe mark plain. Marked new Bearing Trees as follows;

A Fir 12" dia. bears S.13°E., 22.0 ft.

Laurel 5" dia. bears S.70°W., 10.0 ft.

Laurel 6" dia. bears N.14°E., 18.0 ft.

✓ 1/4 CORNER ON NORTH SIDE OF SECTION 1. 14

Set on North line of section 1 and in position to bear out facing of an original B.T. Drove a 3/4" x 36" G. I. Pipe from which

A White Oak 16" dia. bears N.15°38'W., 34 lks. blazed and scribed S. B.T. (Orig. B.T.)

A White Oak 8" dia. bears N.86°12'W., 71 lks. blazed and scribed 1/4 S.36 C.S.B.T.

✓ SECTION CORNER BETWEEN 25 and 26. 15

Position identified by four original B.T.s and hole filled with rotten wood as part of original stake. Set a 5" x 60" post (fir) in mound of rock. Original B.T.s

Black Oak 12" dia. N.47°17'E., 91 lks.) dead and rotting

Black Oak 8" dia. S.20°11'E., 46 lks.) orig. scribe marks

A Pine 36" dia. N.37°19'W., 56 lks.

A Pine 30" dia. S.34°20'W., 41 lks.

Replaced Oak B.T.s

Fir 12" dia. N.75°28'E., 12 lks. Blazed and scribed

T.29S., R.6", S.36 C.S.B.T.

Fir 13" dia. S.38°20'E., 9 lks. blazed and scribed

T.30S., R.6W., S.1 C.S.B.T.

SE COR. D.L.C. 44, I. B. NICHOLS 16

Set a 1" x 30" I. P. with a brass cap marked County Surveyor Office SE D.L.C. 44, 14" underground. Marked new B. T.'s

10" Ash bearing S 10° W 107.0 ft. dist.

16" Ash bearing N 83 1/2° E 117.4 ft. dist.

See Also #7

Nov. 10, 1947

January 25, 1924.
J. W. Cole, Surveyor
Ben B. Irving, chain

July 14, 1928.
H. I. Epstein
Witnesses
Clifford Field
J. I. Long

Ben B. Irving, D.C.S.
Witnesses
N. E. Richardson and Allen Moore
April and May 1929
(Survey or Marks and Hellenberg)

N. E. Richardson
Deputy Cnty. Surv.
L. S. Kershner
D. V. Logsdon
Witnesses.

SEE CORNER NO. 65

SEE CORNER NO. 127

SEE CORNER NO. 90

T29 30 S
R. 6 W