

Douglas County Surveyor's Record of
Government Corners Renewed

30 T. S. 6 R. W. W. M.

Wit. N. E. Richardson
Allen Moore

Ben B. Irving, Deputy Surveyor
April and May 1929.
Witnesses I. H. Smick, N. E. Richardson

Note: The records of corner descriptions of the Public Survey office at Portland does not agree with corners as found on ground. Remainder of field notes check reasonably close. After consultation with Dist. Attorney and Co. Surveyor and in view of the fact that no corners in field checked records and that age of corners corresponded with original work it was decided to use field corners as the true corner and they were renewed accordingly. Ben B. Irving

- ✓ SECTION CORNER BETWEEN 1, 2, 11 and 12. 17
 From facing of two original B.T.s drove a 3" x 36"
 G. I. Pipe in a mound of rock. Original B.T.s
 A Pine 24" dia. bears S. 85° E., 117 lks.
 A Pine 24" dia. bears N. 50° E., 36 lks.
 New B.T.s
 A Fir 10" dia. bears S. 00° 50' W., 47 lks. blazed and
 scribed T. 303 R. 6 W., S. 11 C. S. B. T.
 A Fir 14" dia. bears N. 85° 00' W., 39 lks. blazed and
 scribed T. 303 R. 6 W. S. 2 C. S. B. T.

- ✓ CORNER SECTION BETWEEN 11 and 12. 18
 Note: See W. F. Briggs survey in Vol. 00 Page 113-114
 December 9th 1873, for this corner. By Epstein
 Set from an old post in fence corner as best evidence
 available for location. This is on N. and S. line and location
 described in original field notes. Drove 3" x 36"
 G. I. Pipe from which
 A Cedar 12" dia. bears S. 15° W., 99 lks. blazed and
 scribed S. 11 C. S. B. T.
 A Cedar 10" dia. bears S. 54° E., 82 lks. blazed and
 scribed S. 12 C. S. B. T.

- ✓ SECTION CORNER BETWEEN 1 and 12 ON RANGE LINE. 19
 Location of this corner identified from one O.B.T. and
 position of Section corner 8 on Range line.
 Drove 1 1/2" x 18" shaft set underground from which
 A White Oak 6" dia. bears S. 59° 46' W., 160 lks. blazed
 and scribed S. 12 T. 303 R. 6 W. C. S. B. T.
 Stump of O.B.T. as recorded.
 Section Corner between 6 and 7 T. 303 R. 5 W. bears
 S. 0° 51' E., 3.98 chains

- ✓ N.W. CORNER OF REMICK COWLES D.L.C. 37. 20
 Position identified from O.B.T. which we chopped out.
 There is no doubt as to its being the original B.T.
 although it contains no scribe marks. Drove 3" x 36"
 G. I. Pipe for corner from which a
 Black Oak 18" dia. bears S. 49° E., 71 lks. O.B.T. which I
 scribe Cl. 37 C. S. B. T.
 Fir 22" dia. bears N. 15° W., 20 lks. scribed Cl. 37
 C. S. B. T.

- ✓ SECTION CORNER ON EAST SIDE OF SECTION 12. 21
 Set by proportional measurement a 1" x 36" G. I. Pipe
 driven 26" underground in plowed field (shoe from grain
 drill laid on top) from which
 An Apple 12" dia. bears S. 10° W., 244 lks. scribed
 S. 12 C. S. B. T.

- ✓ SECTION CORNER BETWEEN 12 and 13 ON RANGE LINE. 22
 Reset from one O.B.T. and stump of another. A 1" x 48"
 G. I. Pipe driven 14" underground in grape orchard, from
 which
 An Ash 30" dia. bears N. 73° W., 162 lks. Original
 which I rescribed T. 303 R. 6 W. S. 12 C. S. B. T. 138
 White Oak 6" dia. bears S. 51° W., 75 lks. blazed
 and scribed T. 303 R. 6 W. S. 13 C. S. B. T.
 A Prune 8" dia. bears S. 76° E., 2 lks. blazed and
 scribed T. 303 R. 5 W. S. 18 C. S. B. T.
 A Maple 14" dia. bears N. 57 1/2° E., 326 lks. blazed
 and scribed T. 303 R. 5 W. S. 7 C. S. B. T.