

Douglas County Surveyor's Record of  
Government Corners Renewed

30 T. S. 6 R. W. W. M.

✓ S.W. CORNER OF REMICK COWLES D.L.C. 37. 23  
 Set from N.W. Corner of D.L.C. 52 and N.W. Corner of Claim 37 drove 1" x 18" Shaft 6" underground in mound of rock from which  
 A White Oak 12" dia. bears S. 70° W., 27 lks. blazed and scribed S.W. Cor. Cl. 37 C.S.B.T.  
 A White Oak 10" dia. bears S. 80° E., 70 lks. blazed and scribed S.W. cor. Cl. 37 C.S.B.T.

✓ N.W. CORNER OF D.L.C. # 52. 24  
 A Rail Coupling (Angle Bar) and Original B.T. Set as new B.T.s  
 White Oak 30" dia. bears S. 1° E., 126 lks. scribed N.W. Cor. Cl. 52 C.S.B.T.  
 Black Oak 25" dia. bears S. 57° E., 125 lks. scribed N.W. Cor. Cl. 52 C.S.B.T.  
 White Oak dia. bears S. 3° W., 130 lks. (orig B.T.)

✓ 1/4 CORNER BETWEEN SECTIONS 12 and 13. 25  
 Set by proportional measurement between section corners. Drove 3/4" x 36" G. I. Pipe 12" under ground in field.  
 A White Oak 12" dia. bears S. 60° W., 359 lks. blazed and scribed 1/4 S. 13 C.S.B.T.  
 A White Oak 6" dia. bears S. 32° W., 279 lks. blazed and scribed 1/4 S. 13 C.S.B.T.  
 Center line Balkhead N. end of S.P.R.R. bridge No. "545 D" Sta. 421+17.4 bears S. 30° E., 244 lks.

✓ SECTION CORNER BETWEEN 11, 12, 13 and 14. 26  
 Set from stumps of two original B.T.s as described in original field notes. Drove 1 1/2" x 54" G. I. Pipe flush with ground. Placed two large rocks on top, from which  
 A White Oak 24" dia. bears S. 29° 6' E., 96 lks. blazed and scribed S. 13 T. 30 S. R. 6 W. C.S.B.T.  
 A White Oak 16" dia. bears S. 17° 29' W., 88 lks. blazed and scribed S. 14 C.S.B.T.  
 A White Oak 16" dia. bears N. 74° 53' W., 311 lks. blazed and scribed S. 12 C.S.B.T.

✓ 1/4 CORNER BETWEEN SECTIONS 24 and 25. 27  
 Set from stump of Red Fir and Maple O.B.T. no scribe mark visible, but cut out blazes. Mr. S. H. Rockhill has seen scribe marks. Set 1" x 24" Iron Pipe for corner from which  
 A 12" Fir bears S. 51° 15' W., 47.5 ft. marked C.S. B.T.  
 A 12" Black Oak bears N. 89° 45' W., 26.5 ft. marked C.S. 1/4 S. B.T.

✓ S.W. CORNER OF J. W. BURTON D.L.C. # 46. 28  
 Original B.T. stump standing. Made new B.T.  
 A Black Oak 16" dia. bears S. 29° E., 780 lks.

✓ 1/4 CORNER BETWEEN SECTIONS 14 and 23. 29  
 Position identified from badly rotted stump of O.B.T. S. 45° E., 57 lks. Old blazed out letters B.T. plainly visible, remainder of markings have been obliterated. Drove an Iron Pipe 60" long for corner 48" in the ground. Set 6" square post alongside. New B.T.s  
 A White Oak 18" dia. bears S. 79° E., 34.0 ft. scribed 1/4 S. S. 23 C.S.B.T.  
 A Black Oak 20" dia. bears N. 49° W., 50.0 ft. scribed 1/4 S. S. 14 C.S.B.T.

NOV. 1970 - FOUND O.K. TAGGED TREES  
JMP  
ES. 53/40

Fd. by: Stockhoff  
April, 1984  
M 96-43

Ben B. Irving Deputy County Surveyor  
 Witnesses  
 I. H. Smick  
 N. E. Richardson  
 April and May 1929.

H. L. Eppstein  
 Lt.  
 B. A. Lane  
 S. H. Rockhill  
 June 25, 1937.

J. F. Briggs  
 Jan. 14, 1892.  
 Wlt.  
 Ben B. Irving D.C.S.  
 R. L. Irving  
 March 20, 1939

V. 16-E. 55

also in 1917 by Jensen

23

24

25

26

27

28

29

RENEWED CORNER NO. 434

CORNER NO. 190

CORNER NO. 205

207

COXS-CRAFFMAN CO. - EUGENE, ORE. - 97402