

Douglas County Surveyor's Record of
Government Corners Renewed

30 T. S. 6 R. W. W. M.

KOPE-CHAPMAN CO., EUGENE, ORE. 97196

George J. Wenderoth
Deputy County Surveyor
A. R. Evans - Surv.
F. D. Smith
M. L. Farrell
Witnesses
Jan. 1949

J. H. Markham - Surveyor
R. E. 2880
Oct 20, 1949

John H. Markham, Jr.
Surveyor
Feb. 15, 1950
C.S. 40/231

April 1946

SW. COR. ROBERT TRIMBLE DLC #52 45
Set by measurement from NW corner and SE Corner.
Drive 1" iron pipe and mark new B. T.
36" W. Oak N 74° 05' W 5.7 ft.
30" B. Oak N 27° 40' E 69.5 ft.

SE. COR. ROBERT TRIMBLE DLC #52 46
Set by measurement from $\frac{1}{4}$ cor. and from old B. T. rotted out but in
right position
Drive $\frac{3}{4}$ " iron pipe and set new B. T.
10" W. Oak N 33° 19' E 42.2 ft.
8" B. Oak S 36° 15' E 81.1 ft.

$\frac{1}{4}$ COR. EAST SIDE SEC. 13 47
Old B. T. 26" W. Oak S 48° W 59.4 ft., uprooted.
Drive $\frac{3}{4}$ " iron pipe and marked B. T.
26" B. Oak N 14° 15' E 22.0 ft.
23" W. Oak S 88° 20' W 116.9 ft.

SE COR. WM. JUDD DLC #51 48
Set by measurement from corners of DLC #52
Set 1" square spike 18" long and marked following B. T's. 133
14" W. Oak N 66° 45' E 42.0 ft.
5" W. Oak S 26° 00' E 23.7 ft.

~~NE COR. A. J. Tiller DLC #63~~
~~Set axle with gear attached at proper distance.~~
~~O. B. T's. still standing~~ T30S-R5W!
~~24" B. Oak N 86° W 32 lks. (36")~~
~~10" W. Oak S 20° W 37 lks. (20")~~

$\frac{1}{4}$ COR. 25-36 49
No evidence of corner.
Set post marked N. B. T. from which
B Oak, 4" diam., bears North 7 lks.
B Oak, 5" diam., bears S 70° E 14 lks.

$\frac{1}{4}$ COR. 25-36 50
Determined from a probable B. T., Oak stump which bears East 30.0 ft.
Set a wood stake from which
7" Laurel bears North 27.0 ft. mkd. S 25, $\frac{1}{4}$ S 2880 B T.
6" Laurel bears S 33° E 23.0 ft., mkd. S 36, $\frac{1}{2}$ S, 2880 B T.
There is a fence running West and South from this corner,
it being 470 ft. West to the centerline of Shoestring Road.

SEC COR. 25-26-35-36 51
Determine from O. B. T's. SEE CORNER NO. 121
Oak stump bears N 89° W 17.8 ft., scribe legible.
B. O. S 42° E 58 ft., rescribe S 36, 2880 B. T.
W. O. S 58° W 49 lks. with scar
At corner point found 2 wooden stakes from which
12" Laurel bears N 23° E 85 ft. dist, mkd. S 25, 2880 B.T.
12" Fir bears N 24° W 45 ft., mkd. S 26, 2880, B.T.
7" Laurel bears S 64° W 9.5 ft., mks. S 35, 2880, B.T.
This corner being centered perfectly on top of main ridge.
There is a fence running N & S from cor, the gate being
60 ft. North of cor.

SEC. COR. 35-36-1-2 (T 31 S, R 6 W) 52
Determined from O. B. T's. S.E. 35 T30S R6W
33" Laurel bearing S 83° E 23.0 ft., remark S 1 2880 B T.
16" Laurel bearing S 5° W 54.0 ft. remark S 2 2880 B T.
24" Laurel bearing N 29° W 39.0 ft. remark S 35 2880 B T.
Stump bears N 36° E 51.0 ft.
At cor point found 1 $\frac{1}{2}$ " iron pipe and set 1" x 30" Iron pipe 15" in
ground from which
10" Fir bears N 55° E 41.0 ft. mkd. S 36 2880 B T.
There are fences running N-S and W from this corner.

MAY 1969 - FO. O.K. SEE M 37-62 JMP.
FO. 4/29/78 - R. KIMBERLING - COUNTY - C.S. 40/11

SEE:
GOVT. LINE
NOTES Vol.
Pg 8