

Douglas County Surveyor's Record of
Government Corners Renewed

30 T. S. 6 R. W. W. M.

KOVE-CHAPMAN CO., EUGENE, ORE. 97190

NE COR. DLC #48

Determined corner from old B. T.'s. *FD. 5/81 MARKHAM M87-58* **53**
 36" E. O. bears S 55° W 46.2 ft., rescribe Cl. 48 B T.
 20" W. O. bears N 32° W 39.0 ft., rescribed Cl. 48 B T.
 At corner point found 1/4" x 1" iron bar. Set a 1" x 30" iron pipe
 20" in the ground for corner, from which
 14" E. O. bears N 2° E 18.0 ft., mkd. Cl. 48, 2880 B T.

J. H. Markham
Surveyor
S. R. Nickols
Geo. Vaughn
Witnesses
3/26/50 C.S. 40/237

SEC. COR 25-36 EAST BOUNDARY T 30 S, R 6 W

Set per field notes. **54**
 At a point 92.5 ft. North of closing corner 30-31, T 30 S, R 5 W
 Set 1" x 30" iron pipe 15" in ground, from which
 Old B.T. bears S 74° E, 42.0 ft. distant
 Old B.T. Bears N 63° E, 70.0 ft. distant
 A B.O. 6" diam. bears S 74° W, 10.0 ft. distant marked S 36
 2880, B.T.
 A W.O. 8" diam. bears N 44° W, 29.0 ft. distant marked S 25,
 2880, B.T.

J. H. Markham, Jr.
Engineer
Geo. Vaughn-Witness

FD 3/86 D. BENTZ M101-1

1/4 SEC. COR. SEC. 26-27 SEE FB. 110 Pg. 18. **55**

Determined from old B.T.
 A W. Oak 20" diam. bears S 10° E 123.42 ft. dist., this
 old B.T. Irescribe 1/4 S B.T. *167*
 At corner point set 1/2" steel rod from which
 A W. Oak 20" diam. bears S 88° E 77.7 ft. dist.
 marked 1/4 S, S 26, 2880 B.T.
 An Ash 7" diam. bears S 80° W, 13.2 ft. dist.
 marked 1/4 S, 2880 B.T.

J. H. Markham, Jr.
Engineer
Geo. E. Vaughn
Witnesses
Oct. 15, 1950

N.W. CORNER DLC 42 **56**

Set 40.92 ft. North of 1/4 Sec. Cor. 26-27
 At corner point set 1" I. P. from which *166*
 A Cotton wood 40" diam. bears N 73° E, 55.3 ft.
 dist. marked Cl. 42, 2880, B.T.
 An Ash 7" diam. bears N 81° W 123.2 ft. dist.
 marked Cl. 42, 2880, B.T.

1/4 SEC. COR. 14-15 **57**

As determined by O. B. T. A B. Oak stump bears S 35° E, 10.0
 ft. dist.
 At corner point set 1" x 30" I.P. 13" in ground, from which
 A Fir 18" in diam. bears S 44° W, 2.0 ft. dist. marked
 1/4 S 15, 2880, B.T.
 A Laurel 22" diam. bears S 14° E, 54.0 ft. dist. marked
 1/4 S, S 14, T 30 S, R 6 W, 2880, B.T.

J. H. Markham, Jr. Eng.
Wit. Archie Lousignont
Dec. 4, 1950
C.S. 40/295

7/2/70 - FOUND CORNER - 1" IRON PIPE - C.S. FILE 53/40 6/1/81 M87-10

S.W. Corner D.L.C. 49 **58**

As determined by O.B.T. B. Oak stump bears N 54° E 164.0 ft.
 distant. *150*
 At corner point set 1" x 30" I.P. 18" in ground, from which
 A W. Oak 12" diam. bears N 13° W 80.0 ft. dist. marked Cl. 49,
 2880, B.T.
 A Laurel 4" diam. bears N 51° E, 56.3 ft. dist. marked Cl. 49
 2880, B.T.

Wit. C. I. Poole &
R. E. Johnson
Dec Nov. 29, 1950

SEE ALSO RAN #2