

Douglas County Surveyor's Record of  
Government Corners Renewed

30

6

T. S.

R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97196

N.W. corner of sec. 28.

SEE ALSO #13

65

Found original B. T. with scribing clearly visible.  
Found two previously renewal BTs-One dead.  
I blazed and marked two New B.T.s:  
A 13 inch Fir N.45°W., 10.0 feet dist.  
An 8 inch Laurel N.18°E., 18.0 feet dist.  
Set an iron pipe with brass cap in point for corner.

J. R. Daugherty  
Sept., 1953  
Sur. file 41/235

1/4 corner secs. 25 and 30, T30S, R6W and T30S, R7W.

66

Set by proportional measurement.  
Set 4" x 4" x 36" pine stake in mound of rock.  
2 B.T.'s.:

14" pine - N.68°W., 27.7 feet, mkd. 1/4 S 25 - RE 2741 B. T.  
14" Pine, N.74 1/2°E., 54.8 feet, mkd 1/4 S - 30- RE 2741 B.T.

A. R. Evans  
Witness:  
G. E. Johnson  
June 14, 1953  
For D. Kartes  
See file 41/252

Section corner to secs. 25, 30, 31, and 36, T30S, R6W., and T30S, R7W.

Found 22" Pine, N.35°W., 12 lks.  
20" Pine S.23E., 170 lks., Both dead and down.  
Set 4" x 4" x 48" pine stake.

67

4 BTs.  
14" Pine, S.44 1/2° W., 31.6 feet, mkd. T30S-R7W., S. 36.  
18" Pine, S.15 1/2°E., 8.8 feet, mkd. T30S-R6W, S-31.  
16" Pine, N.19E., 48.5 feet, mkd. T30S, R6W, S 30.  
14" Pine, N.47W., 14.5 feet, mkd T30S, R7W, S 25 RE 2741 BT.

A. R. Evans  
Witnesses:  
G. E. Johnson  
6-15-53  
For D. Kartes  
Files 41/252

Section corner to secs. 32 & 33, T 30 S, R 6 W. and 4 & 5, T 31 S, R 6 W.  
Location identified from O. B. T. 8" (now 30") Fir, S.60°W., 32 lks.  
and O. B. T. 6" (now 20") Maple, N.80°W., 11 lks.

68

Blaze on Fir bearing tree has been chopped out and scribed  
letters "B T" and part of upper visible-Maple B T in place but  
not chopped out.  
Set 1 inch iron pipe with brass cap stamped

Ben B. Irving  
Ray G. Irving  
John Fee  
March 16, 1954  
File 45/253

County Surveyors

T30S, R6W

32 | 33

5 | 4

T31S, 1954

Office

12 inch Fir S.71°W., 21.2 feet scribed T31S, R6W., S 5 CS BT.  
20 inch maple - OBT., N.80°W., 7.3 ft. scribed T30S., R6W., S. 32 CS BT.  
4 inch Yew, S.19°E., 26.5 feet., scribed T31S, R6W., S. 4 CS BT.  
Oak, N.36 1/2°E., 80.6 feet, T30S, R6W., S 33 CS BT.

Ben B. Irving  
Ray G. Irving  
John Fee  
Chairmen  
County Surveyor

CORNER FOUND 7-1965 - C.B. 51/316  
BY M. RANSLEY

Northwest corner D. L. C. No. 49.

SEE Vol. 2 Pg. 240 REN #1

69

Set 1 inch iron pipe Brass Cap from old B. T. Stumps for corner mkd County  
Surveyor's Office DLC 49 1953 and set pipe 24 inches in ground.  
Stumps of orig. BT rotted but show evidence of having been chopped  
out - Checked original field notes.  
Is in corner of old fences.

Ben B. Irving, County Surveyor  
Jim Byron  
Ray Irving  
John Fee  
Filed in 45/  
with Riddle Loop Road Survey.  
Oct. 26, 1953

New BT's:

12 inch Fir, N.72 1/2°E., 17.0 feet, blazed and scribed DLC 49, CS BT.  
12 inch Fir, West 30.0 feet, blazed and scribed DLC 49, CS BT.

Southwest corner D. L. C. No. 48.

70

Found an iron pipe, 1 inch in diameter, in place at the corner and at  
old fence corner.  
This corner was set by John H. Markham Jr. prior to this survey.

N. E. Corner of the J. Q. C. Vandenbosch D. L. C. No. 47.

71

Found rock with x and iron pipe.

S. E. Corner of the J. Q. C. Vandenbosch D. L. C. No. 47.

72

Found 4 inch soil pipe and 2 B. T. is. Re No. 36  
Set 2 inch iron pipe in soil pipe.

A. R. Evans  
Sur. for Jim  
Carrell  
November, 1954.  
See C. S. File  
No. 41/324.

RENEWED CORNER NO. 168