

Douglas County Surveyor's Record of  
Government Corners Renewed

30 T. S. 6 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97199

73

Southeast corner of Donation Land Claim No. 40.  
At a point 158.0 feet South of the Southwest corner of Donation  
Land Claim No. 41, I set a  $\frac{1}{2}$  inch X 12 inch iron pipe for corner point.  
From which:

- A W. O. 16 inches diameter bears S.66°W., 23.0 feet distant. (This fits O. B. T. description exactly but I could not find scribe). I remarked this tree Cl. 40, BT.
  - A W. O., 24 inches diam., bears N.78°W., 133.5 feet dist., mkd. D. L. C. No. 40, B. T.
- There is a fence running North and South from corner.

74

Southwest corner D. L. C. No. 41.  
Determined by O. B. T. - A B. O., 20 inches diam., bears S.25°E., 73.0 feet dist.; I found scribe.  
At corner point I set  $\frac{3}{4}$  inch X 12 inch iron rod.  
From which:

- A W. O., 13 inches in diam., bears N.16°E., 60.5 feet dist., mkd. D. L. C. 41, T30S, R 6 W., B. T.
  - A W. O., 14 inches in diam., bears S.8°W., 92.5 feet distant, mkd. Cl. 41, 2880 B. T.
- There is a fence running North and South from this corner.

75

$\frac{1}{4}$  corner to sections 33 and 34.  
Determined by O. B. T. - A W. O. stump 30 inches in diameter bears S.48°W., 49.5 feet dist., - found old face.  
At corner point set 1 inch X 30 inch truck axle.  
From which:

- A W. O., 30 inches in diam., bears N.36°E., 60.5 feet dist., mkd.  $\frac{1}{4}$  S, S34, B. T.
  - An Ash, 13 inches in diam., bears S.73°W., 51.0 feet dist., mkd.  $\frac{1}{4}$  S, S33, B. T.
- Fence corner at County Road bears S.6°W., 160.5 feet dist.

76

$\frac{1}{4}$  sec. corner to secs. 8 and 9. SAME AS #80  
Determined by O. B. Ts.  
At corner point I set a 1 inch X 30 inch steel shaft,  
from which  
A 40 inch Cedar bears N.20°E., 19.8 feet dist. O. B. T. scribe showing.  
A 50 inch Pine bears N.18°W., 121.0 feet distant, O. B. T. scribe showing.  
May 9, 1955.

77

$\frac{1}{4}$  sec. corner to secs. 7 and 8.  
At the midpoint on section line, I set  $\frac{3}{4}$  inch x 36 inch iron pipe for  $\frac{1}{4}$  section corner.  
from which  
A 10 inch Fir bears N.53°E., 10.5 feet dist. marked  $\frac{1}{4}$  S 8 B. T.  
A 12 inch White Fir bears S.30°W., 9.0 feet dist., mkd.  $\frac{1}{4}$  S 7 B. T.  
Corner lies in small flat 120 feet West of swamp.  
May 7, 1955.

78

Section corner to secs. 33 & 34 (T30S, R6W) and secs. 3 & 4 (T31S, R6W).  
Determined by O. B. T.s:  
A 30 inch B. O. Snag bears N.11°W., 72 feet.  
A 25 inch B. O. Stump bears S.80°E., 69.0 feet.  
A 25 inch B. O. Stump hole bears N.30°E., 84.5 feet.  
A 25 inch B. O. Stump bears S.32°W., 41.0 feet.  
At corner point set  $\frac{3}{4}$  inch X 44 inch Iron pipe from which:  
A 14 inch La. bears N.74°E., 46.5 feet dist., mkd. S 34 B. T.  
A 15 inch La. bears N.22°E., 17.0 feet dist., mkd S 34 B. T.  
A 14 inch La. bears N.35°W., 29.0 feet dist., mkd S 33 B. T.  
A fence corner bears S.78°W., 9.2 feet dist. Fences run North - South - East and West.

10 - 16 - 1952

John H. Markham Jr.  
Witness: Harry Dayton  
Work done for Harry Dayton

C. S. File No. 41/78.

John H. Markham Jr.  
Witness: D. M. McMunn  
D. B. Barnes  
Done for Stomar Lumber Co.  
C. S. File No. 41/384.

John H. Markham Jr.  
Witness: Harry Dayton  
March 21, 1955.  
C. S. File No. 41/370..

**VOID**

SEE GOV'T. NOTES VOL. 32.

120A