

Douglas County Surveyor's Record of
Government Corners Renewed

30 T. S. 6 R. W. W. M.

KORE-CHAPMAN CO., EUGENE, ORE. 97196

79
Southeast corner of the R. Cowles Donation Land Claim No. 37.
Found 1 inch Iron Pipe and 1 orig. bearing tree:
B. O. (now 30") N. 31 1/2° W., 18 lks.

A. R. Evans
May, 1955.
C. S. File 41/397.

FIND. OK 9/92 R. BROWN PARTITION 1992-0072

1/4 sec. corner to secs. 8 - 9.
Determined by O. B. T.

SAME AS #76

80

At corner point set a 1" X 30" steel shaft from which
A 40" Cedar bears N. 20° E., 19.8 feet dist. O. B. T. scribe showing.
A 50" Pine bears N. 18° W., 121.0 feet dist. O. B. T. scribe showing.
Road bears North 115.0 feet.

John H. Markham Jr.
Work for Stomar Lumber Co.
May 9, 1955 and July 2, 1955.
C. S. File No. 42/18.

Section corner to secs. 15, 16, 21 and 22. CORNER DESTROYED SET NEW CORNER
Determined by O. B. T. SEE CORNER NO. 162-208
At corner point set a 1" X 30" I. P. from which
A 24" Ash bears East 18.7 feet dist. - O. B. T., found scribe.
A 7" W. O. bears N. 34° W., 12.0 feet dist., mkd. S. 16 B. T.
A 5" W. O. bears S. 24° W., 14.5 feet dist., mkd. S. 22 B. T.
A 8" W. O. bears S. 10° E., 15.0 feet dist., mkd. S. 22 B. T.
Jerry Creek bears East 23.0 feet.

81

North 1/4 corner to section 5 only.
Point for corner determined by O. B. T.s:
8 inch Dead Oak, N66W., 46.0 feet. (Hicks) SEE M 13-72
6 inch Dead Oak, S69W., 21.2 feet. (Hicks)
6 inch Dead Oak, S42W., 26.4 feet - found scribe - O. B. T. (1904).
At corner point found stone and set a 3/4 inch x 30 inch iron pipe,
from which:
A 12 inch Fir bears S36W., 24.7 feet dist., mkd. 1/4 S 5 B. T.
An 18 inch Cedar bears S. 53E., 31.5 feet dist., mkd. 1/4 S 5 B. T.
Dry Creek bears East 100.0 feet.
South 1/4 corner 32 bears East 635.5 feet.
Corner lies along E - W fence.

82

John H. Markham Jr.
Work done for Stomar Lumber Co.
August - September, 1956.
C. S. File No. 42/191.

North 1/4 sec. corner to sec. 6. (only)
A 44 inch Cedar bears N20W., 17.2 feet dist. - O. B. T. - found scribe.
At corner point found stone and set truck axle with flange up,
from which:
A 12 inch W. Fir, bears S83W., 36.0 feet dist. mkd. 1/4 S 6 B. T.
A 20 inch W. Fir, bears N51E., 24.7 feet dist. mkd. 1/4 S B. T.
Road bears N. 30° E., 62.0 feet.

83

Township corner to secs. 6, 1, 36 and 31, Twps. 29 & 30 S., Rgs. 6 & 7 W.
Point for corner determined by O. B. Ts:
A 24 inch W. O., bears N73E., 14.5 feet dist., - I rescribe S 31 B. T.
A 20 inch W. O., bears S20E., 33.0 feet dist., - II rescribe S 6 B. T.
A 44 inch Y. Pine windfall bears S19W., 30.4 feet dist. - O. B. T.
At corner point set 2 inch x 36 inch solid steel bolt,
from which:
A 21 inch W. O., bears N49W., 177.0 feet dist., mkd. S 36 T29S, R7W., B. T.
A 22 inch La. bears N4E., 55.0 feet distant mkd. S31, T29S, R6W., B. T.
A 14 inch W. O., bears S33E., 30.5 feet dist., mkd. S 6, T30S, R6W., B. T.
An old fence runs N - S.

84

1/2 corner to secs. 18 & 19. SEE CORNER NO. 158
Found scribe marks on old down pine.
Marked new witness trees:
Fir, 8 inches, N. 28° E., 7.9 feet.
Cedar, 6 inches, S. 14 1/2° E., 4.5 feet.
Scribed R. E. 3937 B. T.

85

Clifford M. Brydon
Feb. 13, 1957
C. S. File No. 42/251.