

Douglas County Surveyor's Record of  
Government Corners Renewed

30 T. S. 6 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

James W. Byron, Deputy County Surveyor - Survey for Dale Weekly  
May 15, 1956.  
C. S. File No. 47/93.

Section corner to secs. 3 & 4, T30S, R6W., and secs. 33 & 34, T29S, R6W. 86  
Location of corner determined by facing two old BTs not of record.  
Found old BT, 50 inch Fir, N.2°W., 36 feet-found scribe S 34.  
Found old BT, White Fir, snag only, S.7°E., 14 feet-found scribe T.R.W. 35.  
Set an iron pipe with brass cap for corner mkd.  $\frac{33}{4} \frac{34}{3}$ .

Blazed and scribed new trees:

- 12 inch W. Fir, N.19°W., 62.4 feet, mkd. T 29 S, R 6 W, S 33, C. S. BT.
- 26 inch W. Fir, N.63°30'E., 87 feet, mkd. T29S, R6W., S 34, C. S. BT.
- 18 inch W. Fir, S.55°30'E., 39 feet, mkd. T30S, R6W, S 3, C. S. BT.
- 4 inch R. Fir, S.60°W., 18.5 feet, mkd. S 4, C. S. BT.

$\frac{1}{4}$  corner to sec. 3, T30S, R6W., and sec. 34, T29S, R6W. 87  
Original B. T.s not found. Corner set midway and on true line between section corners.

Set an iron pipe with brass cap mkd.  $\frac{1}{4}$  S 34/3 T 29 S, R 6 W, Co. Surveyor's Office, 1956.

Scribed 2 trees:

- 36 inch Fir, N.36°E., 22.7 feet, mkd.  $\frac{1}{4}$  S 34, T29S, R6W, C. S. BT.
- A Fir, S.60°E., 37.0 feet, mkd.  $\frac{1}{4}$  S 3, T29S, R6W., C. S. BT.

Section corner to secs. 2 & 3, T30S, R6W., and secs. 34 & 35, T29S, R6W. 88  
Location of corner determined by facing old BTs found but not of record.  
Set an iron pipe with brass cap marked Sec. cor.  $\frac{34}{3} \frac{35}{2}$  T29S, R6W. 1956, County Surveyors Office.

From which:

- A 30 inch R. Fir bears S.10°E., 33 feet, bark scribed T30S, R6W., S 2 C. S. BT.
- A 6 inch R. Fir bears N.32°E., 56 feet, scribed T29S, R6W, S 35, C.S.BT.

$\frac{1}{4}$  corner to sec. 2, T30S, R6W., and sec. 35, T29S, R6W. 89  
Corner set half way between section corners.  
Set an iron pipe with brass cap at corner point marked  $\frac{1}{4}$  Cor.  $\frac{S 35 T29S}{S 2 T30S}$  R6W. County Surveyor's Office, 1956.

From which:

- A 14 inch W. Oak bears N.5°30'E., 29.0 feet scribed  $\frac{1}{4}$  S 35, T29S, R6W., C. S. BT.
- A 12 inch W. Oak bears S.51°E., 233.37 feet scribed  $\frac{1}{4}$  S 2 T 30 S, R 6 W., C. S. BT.

Section corner to secs. 1 & 2, T30S, R6W., and secs. 35 & 36, T 29 S, R 6 W. 90  
Found mound of rock and scribed post at corner. All BTs as renewed by Ben B. Irving in good condition.  
Set an iron pipe with brass cap marked  $\frac{35}{2} \frac{36}{1}$  1956, T 30 S, R 6 W., Co. Surveyor's Office.

Blazed and scribed:

- 12 inch R. Fir, S.36°W., 22.0 feet, T 30, S 2 C. S. BT.

SEE ALSO # 15

John H. Markham Jr.  
Work done for Hanna Coal & Ore Co.  
May 23, 1957 June 13, 1957  
C. S. File No. 42/269.

Section corner to secs. 17, 18, 19 & 20. 91  
Location of point for corner determined by O. B. T.: - SEE REN #33  
A 15 inch Pine bears N.50°W., 4.0 feet dist. - O. B. T.  
A 12 inch Pine bears S.59°W., 31.0 feet dist.- O. B. T.-fd. scribe.  
A 24 inch Pine bears N.25°E., 95.5 feet dist.- O. B. T.-fd. scribe.  
Set an iron pipe with brass cap in concrete at corner point mkd. T 30 S, R 6 W., 17-18-19-20, 2880, 1957,

From which:

- 18 inch Pine bears N.86°30'W., 29.7 feet dist, mkd. S 18 B. T.
- 32 inch Fir bears S.40°W., 54.2 feet dist. mkd. S 19 B. T.
- 8 inch Pine bears S.38°E., 12.1 feet dist. mkd. S 20 B. T.

Road bears North 183.0 feet.

181