

Douglas County Surveyor's Record of  
Government Corners Renewed

30 T. S. 6 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

$\frac{1}{4}$  corner to secs. 16 & 17.

92

Corner location determined by O. B. Ts:

- A 33 inch Cedar bears S.4°30'E., 88.0 feet - O. B. T. - found scribe.
- A 26 inch Pine bears S.6°W., 77.0 feet - O. B. T.
- A 30 inch Pine snag bears N.57°W., 12.0 feet dist. - O. B. T. - found scribe.

At corner point found scribed wood post in large pile of stones. - See Cor. #35

I set an iron pipe with brass cap in concrete at point for corner, mkd.

T 30 S, R 6 W.,  $\frac{1}{4}$  S, S 17 S 16 2880, 1957,

From which:

- 20 inch Pine bears S.13°E., 19.4 feet dist. mkd.  $\frac{1}{4}$  S 16 B. T.
- 12 inch Pine bears N.72°W., 33.4 feet dist. mkd.  $\frac{1}{4}$  S 17 B. T.
- 9 inch Pine bears N.83°E., 74.2 feet dist. mkd.  $\frac{1}{4}$  S 16 B. T.
- A road bears West 346.0 feet.

Center of Section 17.

93

Location of corner determined by O. B. T. - A 26 inch Pine stump (logged) bears S.77°E., 7.0 feet dist. - O. B. T. - A 24 inch Fir stump (logged) bears N.21°W., 28.5 feet dist. - O. B. T., fd. scribe. At corner point found scribed post in large mound of stone. - See Cor. #37

I set an iron pipe with brass cap in concrete mkd. T 30 S, R 6 W  $\frac{1}{4}$  S 17 center 2880 - 1957.

From which:

- A 16 inch Fir bears S.3°E., 197.0 feet dist. mkd.  $\frac{1}{4}$  S C.C. S 17 B. T.
- A 10 inch Fir bears N.50°E., 239.0 feet dist. mkd.  $\frac{1}{4}$  S 17 C.C. B. T.
- Mining road bears West 112.0 feet. This corner lies in mining area.

$\frac{1}{4}$  corner to secs. 17 & 18.

94

Point for corner determined by O. B. T.

Found a 1 inch drill steel shaft & scribed wood post in mound of stone at corner point. - See Cor. No. 94

I set an iron pipe with brass cap at corner point, in concrete, mkd. T 30 S, R 6 W,  $\frac{1}{4}$  S S 18 S 17 2880, 1957.

From which:

- A 16 inch Pine bears N.85°W., 21.7 feet dist. - O. B. T. - fd. scribe.
- A 27 inch Pine stump (logged) bears S.85°E., 31.5 feet dist. - O. B. T. - fd. scribe.
- A 11 inch Pine bears N.15°W., 50.0 feet dist. mkd.  $\frac{1}{4}$  S 18 B. T.
- A 17 inch Pine bears S.19°E., 16.0 feet dist. mkd.  $\frac{1}{4}$  S 17 B. T.
- Logging road bears West 83.5 feet dist.

Section corner to secs. 16, 17, 20 and 21.

95

Location of corner determined from O. B. T.:

- A 30 inch Pine, N.70°30'W., 36.0 feet, O. B. T., fd. scribe.
- A 36 inch Pine, S.11°30'W., 22.2 feet, O. B. T., fd. scribe. See Cor. No. 31
- A 20 inch Fir, N.42°E., 49.5 feet, O. B. T. fd. bark scribe.

At point for corner set an iron pipe with brass cap in concrete marked #253

T 30 S, R 6 W, S 16 S 17 S 20 S 21, 2880, 1957

From which:

- A 14 inch Pine bears N.21°E., 44.4 feet dist. mkd. S 16 B. T.
- A 20 inch Pine bears N.17°W., 44.4 feet dist. mkd. S 17 B. T.
- A 10 inch Fir bears S.56°30'W., 56.3 feet dist. mkd. S 20 B. T.
- An 18 inch Pine bears S.61°E., 83.0 feet dist. mkd. S 21 B. T.
- Road bears North 17.0 feet.

$\frac{1}{4}$  corner to secs. 17 & 20.

96

Location of corner determined by O. B. T.:

- A 36 inch Pine stump (logged) bears N.5°E., 9.2 feet dist. - O. B. T., found scribe. See Cor. #32

A 25 inch Pine snag bears S.45°W., 54.1 feet dist. O. B. T. - fd. scribe.

At corner point set an iron pipe with brass cap in concrete marked T 30 S, R 6 W.,  $\frac{1}{4}$  S S 17 S 20 2880, 1957.

From which:

- A 25 inch Fir bears S.29°W., 69.8 feet dist. mkd.  $\frac{1}{4}$  S 20 B. T.
- A 20 inch Fir bears S.56°E., 62.0 feet dist. mkd.  $\frac{1}{4}$  S 20 B. T.
- A 20 inch Cedar bears N.73°E., 51.6 feet dist. mkd.  $\frac{1}{4}$  S 17 B. T.
- A 13 inch Pine bears N.23°30'W., 53.6 feet dist. mkd.  $\frac{1}{4}$  S 17 B. T.
- Road bears South 15.0 feet dist.

John H. Markham Jr.  
Work done for Hanna Coal & Ore.  
May 23, 1957  
June 13, 1957  
C. S. File No. 42/269.