

Douglas County Surveyor's Record of  
Government Corners Renewed

30 T. S. 6 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

101

$\frac{1}{4}$  corner to secs. 3 and 10.  
Location of corner determined by O. B. T. - a 16 inch Fir stump (logged)  
bears S.30°W., 3.2 feet dist. - O. B. T. - fd. scribe.  
At corner point set  $\frac{3}{4}$  inch x 30 inch drill steel shaft 12 inches in the  
ground, from which:  
A 20 inch Fir bears N.61°E., 35.8 feet dist. mkd.  $\frac{1}{4}$  S 3 B.T.  
A 15 inch Fir bears N.33°E., 38.0 feet dist. mkd.  $\frac{1}{4}$  S 3 B.T.  
A 24 inch Fir bears N.15°W., 33.5 feet dist. mkd. bark scribed  
 $\frac{1}{4}$  S 3, T 30 S, R 6 W, B.T.

John H. Markham, Jr.  
July 18, 1957.  
C. S. File No.  
42/287.

102

$\frac{1}{4}$  Corner Section 33, T30S, R6W & Sec. 4 T31S, R6W.  
Found: Original N.W. BT (Now 26 inch W.O.). Checks bearing & Dist. to  
Scribed 4x4 inch stake set for Corner by R. Gee. BT opened by  
Gee "BT" scribing visible. The S.W. BT is Gone.  
Set: Brass Cap alongside post marked  $\frac{1}{4}$  Section 33 T30 S, R6 W  
County Surveyors Office, 1956 4 T 31S, R6W.  
From which: 24 inch R. Fir bears N 39°W 58.3 ft. scribed  $\frac{1}{4}$  S33 T30SR6W CS BT.  
24 inch W.O. bears N 60°E 4.0 ft. scribed  $\frac{1}{4}$  S33 CS BT.

James Byron  
Gomer Welker  
J. Fee  
October, 1956-Jan., 1957  
Dr. 48 / Rd. 93

103

$\frac{1}{4}$  Corner Sections 32 & 33.  
Found 1 inch Iron Pipe set by Armstrong who found scribing on old stump.  
No Scribing visible at this time.  
Set  $\frac{3}{4}$  inch Iron Rod  
I blaze & scribe: 8 inch Pine N 46°W 6.5 ft.  $\frac{1}{4}$  S32 CS BT.  
10 inch Pine N 77 $\frac{1}{2}$ °E 23.5 ft.  $\frac{1}{4}$  S33 CS BT.

#247

104

Kitchell M. S. #305 Corner #1, Section 18 as determined by old BTs.  
A 20" Pine bears S.65°W. 42.4 ft. distance O.B.T. found scribe.  
At corner point set brass cap in concrete. marked E.M.C. #1 T.30S.,  
R. 6W. 2880 1957. from which:  
A 26" Fir bears N. 29°W., 10.5 ft. distance marked M.S. 305 B.T.  
A 26" Fir bears S. 83°E., 19.0 ft. distance marked M.S. 305 B.T.  
 $\frac{1}{4}$  Corner 17 - 18 bears North 626.0 ft.

105

Kitchell M. S. #305 Corner #2 plus 1 as det. by Field Notes.  
A 30" Fir S.56E. 57.0' found scribe.  
At a point 233.0' S. 45°E. from corner #3, I set brass cap in  
concrete marked M.S. 305 2+1 T.30S R.6W. 2880 1957 from which:  
A 5" Cedar bears S. 33°W. 17.0' dist. marked M.S. 2+1 B.T.  
A 10" Pine bears N. 24°E. 6.7' dist. marked M. S.2+1 B.T.

John H. Markham, Jr.  
Witnesses: G. D. Myers  
E. D. Jenks  
For Hanna Coal & Ore.  
July, August, 1957  
C. S. File No. 42/288

106

Kitchell M.S. #305 Corner #2 and #4 which are common, Sec. 18, as det.  
by O.B.T and old mom. At a point 576.0' S. 45°W. from corner 3 & 5,  
I found old post in mound of stone -- a burnt out stump hole bears  
N. 68°E. 14.2' distance.  
At corner point set brass cap in concrete marked M.S. 2 & 4, T 30S.  
From Which: R. 6W. 2880 1957.  
A 7" Fir bears S. 11°W. 35.5' dist. marked M.S. 305 B.T.  
A 8" Fir bears N. 46°W. 19.7' dist. marked M.S. 305 B.T.

107

Kitchell M.S. #305 Corner #3, Section 18 as det. by O.B.T.  
A 30" Pine bears North 8.6' dist. O.B.T. found scribe.  
A 42" Pine Snag bears S. 72 $\frac{1}{2}$ °E. 56.5' dist. O.B.T.  
At corner point found large pile of stones and set brass cap in concrete  
marked M.S. 305 #3 T.30S R.6W. 2880 1957. from which:  
A 10" Fir bears S. 53°E. 11.5' dist. mkd. M.S. 3 B.T.  
A 8" Fir bears S. 19°E. 22.9' dist. mkd. M.S. 3 B.T.  
A 27" Pine bears N.60 $\frac{1}{2}$ °W. 33.1' dist. mkd. M.S. 3 B.T.