

Douglas County Surveyor's Record of  
Government Corners Renewed

30

T. S.

6

R. W. W. M.

KORE-CHAPMAN CO., EUGENE, ORE. 21881

Kitchell M.S. #305 Corner #3 plus 2, Section 18 as det. by field notes. 108  
At a point 233.1' N.45°E. from Corner #3, I found large pile of stone  
and set brass cap in concrete mkd. M.S. 305 #3+2 T30S R6W 2880 1957  
from which: 18" Cedar bears N.32½°W.36.3' dist. mkd. M.S. X B.T.  
7" Fir bears N.83°E. 7.0' dist. mkd. M.S. X B.T.

Kitchell M.S. #305 Corner #3 and #5 which are common, as det. by O.B.T.s 109  
8" Fir Sang bears S. 40E. 5.2' dist. O.B.T.  
At corner point found large pile of stone and set brass cap in  
concrete mkd. M.S. 305 3 & 5 T30S R6W 2880 1957 from which:  
A 10" Fir bears S.30°W. 33.4' dist. mkd. M.S. 305 B.T.  
A 14" Pine bears S.33°E. 22.0' on slope mkd. M.S. 305 B.T.  
¼ Corner bears South 250.0'

Emerald Lode Claim Corner #2, Section 18, as det. by O.B.T.s 110  
A 30" Pine bears N.28°W. 96.0' distance, found scribe.  
A 26" Pine Stump (logged) bears N.47½°E. 31.7' O.B.T.  
At corner point set brass cap in concrete mkd. E.M.C. #2  
T30S R6W 2880 1957 from which:  
A 15" Cedar bears N.80°W. 45.5' dist. mkd. M.S. 305 #2 B.T.  
A 22" Fir bears N.82°E. 30.6' dist. mkd. M.S. 305 B.T.

Emerald Lode Claim Corner #3, Section 18, as det. by O.B.T.s 111  
A 30" Pine bears S.42½°W 21.0' dist. found scribe.  
A 22" Pine Snag bears N.8°30'W. 59.0' dist. O.B.T.  
At corner point set brass cap in concrete mkd. E.M.C. #3,  
T.30S R6W 2880 1957 from which:  
A 30" Pine bears S.63°W. 72.2' dist. mkd. E.M.C. 3 B.T.  
A 20" Cedar bears N.56°E.114.2' dist. mkd. E.M.C. 3 B.T.  
Main mine road bears East 40'.

M.S. 306 Corner #3, Section 20, as det. by O.B.T.s 112  
A 36" Pine Stump (logged) bears S.85°E. 68.0' dist. O.B.T.  
A 12" Cedar bears South 62.7' O.B.T.  
At corner point found stone mom. & set brass cap in concrete mkd.  
M.S. 306 #3 T30s, R6W, 2880, 1957 from which:  
A 18" Fir bears S.70°E 25.6' dist. mkd. M.S. 306 B.T.  
A 10" Cedar bears S.64°W 71.1' dist. mkd. M.S. 306 B.T.  
A 20" Cedar bears N.27°W. 56.8' dist. mkd. M.S. 306 B.T.  
Road bears South 80.0' dist.  
¼ Corner 17/20 bears East 360.0'

M.S. 306 Corner #4, Section 20, as det. by O.B.T.s 113  
A 9" Cedar bears N.81½°E. 7.9' dist. found scribe O.B.T  
A 5" Pine windfall bears N.26°E 14.5' dist. found scribe O.B.T.  
At corner point found stone mom. & set brass cap in concrete mkd.  
M.S. 306 #4 T30S R6W 2880 1957 from which:  
A 10" Cedar bears S. 18°W. 16.6' dist. mkd. M.S. 306 B.T.  
A 11" Pine bears N. 73°W. 19.6' dist. mkd. M. S. 306 B.T.  
¼ Corner 17/20 bears North 600' and East 360.0'.

M.S. 306 Corner #5, Section 20, as det. by O.B.T.s 114  
14" Pine N.31°E. 25.1' O.B.T found scribe.  
14" Pine S.47°E. 13.9' O.B.T. found scribe.  
At corner point set brass cap in concrete marked: M.S. 306  
#5 T30S R6W 2880 1957 from which:  
15" Pine bears S.38°W. 19.2' mkd. M.S. 306 B.T.  
13" Pine bears N.23°E. 67.4' mkd. M.S. 306 B.T.  
12" Pine bears N.39°W. 79.5' mkd. M.S. 306 B.T.  
Road bears North 38.0'  
¼ Corner 17/20 bears North 600' and West 1140'.

John H. Markham, Jr.  
Witnesses: E. D. Jenks  
G. D. Myers.  
For Hanna Coal & Ore. Co.  
August, Sept. 1957  
C. S. File No. 42/288