

Douglas County Surveyor's Record of  
Government Corners Renewed

30 T. S. 6 R. W. W. M.

HOKE-CHAPMAN CO., EUGENE, ORE., 21881

115

M. S. 306 Corner #6, Section 20, as det. by O.B.T.s  
18" Pine windfall bears N.46°E. 18.5' dist. OB.T. Found scribe.  
At corner point set brass cap in concrete marked M.S. 306 #6 T30S  
R6W 2880 1957 from which:  
20" Pine bears N.81°30'E. 21.3' mkd. M.S. 306 B.T.  
24" Fir bears N. 6° W. 31.4' dist. bark scribed M.S. 306 B.T.  
12" Fir bears S.58° W. 12.5' dist. mkd. M. S. 306 B.T.  
26" Fir bears S.54° E. 42.4' dist. mark scribed M.S. 306 B.T.

John H. Markham, Jr.  
Witness: E. D. Jenks  
Sept. Oct., 1957  
For Hanna Coal & Ore. Co.  
C. S. File No. 42/288

116

M. S. 306 Corner #7, Section 20, as det. by O.B.T.s  
40" Pine bears N.41°W. 67.0' O.B.T.  
32" B.Oak bears S.41°W. 97.0' O.B.T., found scribe.  
At Corner point set brass cap in concrete marked: M.S. 306 #7  
T30S R6W 2880 1957 from which:  
A 20" Pine bears S.71°E. 93.7' dist. mkd. M.S. 306 B.T.  
A 20" Fir bears N.47°E. 17.1' dist. mkd. M.S. 306 B.T.  
A 20" Fir bears N.80°W. 25.5' dist. mkd. M.S. 306 B.T.  
A Fence runs East and West 70.0' South of Corner.  
Section Corner  $\frac{17}{20} | \frac{16}{21}$  bears North 1170.0'.

John H. Markham, Jr.  
Witness: R.G. Boyd  
For Stomar Ebr. Co.  
Dec. 13, 1957  
C.S. File # 42/321

117

$\frac{1}{4}$  Section Corner to Sections 4 & 5.  
Det. by Old BTs: 14" W.O. down bears S.45°W. 66.0 ft. O.B.T.  
#13-12-7 35" W.O. down bears S. 7°E. 29.7 ft. O.B.T.  
At Corner Point found Stone & 3" X 3" Scribed Post. I set 2" X 30"  
I.R. from which: 6" W.O. bears S.74°E. 63.0 ft. dist. mkd.  $\frac{1}{4}$  S4 T30S BT.  
5" W.O. bears S.5°W. 56.0 ft. dist. mkd.  $\frac{1}{4}$  S5 X BT.  
12" Fir bears S.86°W. 22.7 ft. dist. mkd.  $\frac{1}{4}$  S5 BT.  
Road Bears East 123.0 ft.

128

118

Section Corner to 10, 11, 14, and 15.  
Which is 2791 feet West of  $\frac{1}{4}$  Corner to 11, I find  
3 old BT's, which do not agree with old calls:  
20" B. O. S.85°E. 46.2 ft. Portion of "4" visible, down  
& rotted.  
24" B. O. N.50°E. 223.0 ft. Cut Stump, Neg. of "BT" visible.  
32" B. O. N.12 $\frac{1}{2}$ °W. 62.0 ft. with face.  
To renew, I scribe: 18" Y. Pine N.50°30'W. 65.5 ft.  
4" Madrone S.56°30'W. 32.0 ft.  
5" Madrone S. 5°30'W. 97.7 ft.  
5" Madrone N.35°20'W. 10.0 ft.  
Yellow Tag on 2" Madrone N.86°W. 10.0 ft.  
Note - Corner falls 15 feet North of E. & W. Fence.

Robert M. Thompson R.E., No. 3683  
Witness: L. Washburn & Ike Fuller  
For: Fuller Bros.  
Dec. 22, 1958  
C. S. File No. 41/62

119

$\frac{1}{4}$  Section Corner to Sections 15 and 16.  
I find a 40" Pine Snag S.80°E. 124 feet (BT visible)  
14" B. O. N.85°W. 198 feet (down)  
Stake in Rock Mound.  
To renew, I scribe: 14" I. Cedar N.43°E. 61.6 feet.

161

120

$\frac{1}{4}$  Sec. Cor. To Sec. 34, T30-6W. & Sec. 3, T31-6W.  
Found - Fir Snag, now 30", N.10°W. 19.1 ft. Opened & found good  
scribe Mkd: "TW."  
No trace of other BT.  
Set Iron Pipe with Brass Cap Mkd: "County Surveyor's Office, 1960  
T30S R6W  $\frac{1}{4}$   $\frac{S34}{S3}$   
Blaze & Scribe New Trees: 18" R.Fir N.89 $\frac{1}{2}$ °W. 20.0 ft. ( $\frac{1}{4}$  S34 CS BT)  
11" Maple S.9°W. 51.0 ft. ( $\frac{1}{4}$  S3 CS BT)

James W. Byren, Deputy  
Witness: Mile Godfrey  
Clife Putnam  
May 23, 1960  
C.S. File No. 52/25

120-A

Section Corner to Sec. 33 & 34, T30-R6W & Secs. 3 & 4, T31-6W.  
Found -  $\frac{3}{4}$ " Pipe Set by Markham - 14" Laurel N.74°E. 46.5 ft. scribe visible.  
14" Laurel N.35°W. 29.0 ft., scribing visible. SEE COR. #78  
15" Laurel N.22°E. 17 ft., down & dead.

FOOK  
8/8/61  
G. G. W. W.  
M. S. 306